


PHASE 1 PART A:

TWIN FALLS COUNTY - WRIGHT AVE. JAIL

2515 Wright Ave, Twin Falls, ID 83301



PH 1 PART A SHEET INDEX	
Sheet Number	Sheet Name

A1A-0.0	TITLE SHEET
A1A-0.1	CODE ANALYSIS
A1A-0.2	CODE ANALYSIS- OCCUPANCY
A1A-0.3	CODE ANALYSIS - EXITING
A1A-0.4	CODE ANALYSIS - FIRE & SMOKE
A1A-0.5	FIRE PENETRATIONS
A1A-0.6	CODE REQUIREMENTS
A1A-0.7	CODE REQUIREMENTS
A1A-1.0	PH 1 PART A DEMO SITE PLAN
A1A-1.1	PH 1 PART A REMODEL SITE PLAN
C-1	SITE PLAN
C-2	GRADING PLAN
C-3	UTILITY PLAN
C-4	DETAILS
C-5	LAND PLAT
A1A-1.2	PH 1 PART A DEMO FLOOR PLAN
A1A-1.3	PH 1 PART A DEMO ELEVATIONS
A1A-1.5	PH 1 PART A DEMO CEILING PLAN
A1A-2.0	PH 1 PART A FLOOR PLAN
A1A-2.1	ENLARGED FLOOR PLANS
A1A-2.3	ENLARGED FLOOR PLAN
A1A-2.4	ENLARGED FLOOR PLAN
A1A-3.0	PH 1 PART A EXTERIOR ELEVATIONS
A1A-4.0	PH 1 PART A ROOF PLAN
A1A-5.0	PH 1 PART A BUILDING SECTIONS
A1A-5.1	PH 1 PART A BUILDING SECTIONS
A1A-7.0	PH 1 PART A REMODEL CEILING PLAN
A1A-8.0	INTERIOR ELEVATIONS
A1A-9.0	FINISH SCHEDULE
A1A-9.1	DOOR SCHEDULE
A1A-10.0	DETAILS - SITE
A1A-10.1	DETAIL - TRASH ENCLOSURE
A1A-10.2	DETAILS - MATERIALS, DOORS, & WINDOWS
A1A-10.4	DETAILS STAIR
A1A-10.5	DETAILS MISC
A1A-10.6	DETAILS CEILING
A1A-10.7	DETAILS ROOF
A1A-10.8	ROOF DETAILS
A1A-10.9	DETAILS CASEWORK
S1.0	GENERAL STRUCTURAL NOTES
S1.1	GENERAL STRUCTURAL NOTES
S1.2	TYPICAL DETAILS
S1.3	TYPICAL DETAILS
S1.4	TYPICAL DETAILS
S2.0	FOUNDATION PLAN
S2.1	ROOF FRAMING PLAN
S3.0	FOUNDATION DETAILS
S4.0	FRAMING DETAILS
S4.1	ROOF FRAMING PLAN
M1A-1.0	PH 1 PART A DEMO MECH. FLOOR PLAN
M1A-1.1	PHASE 1 PART A MECH. FLOOR PLAN
M1A-1.2	PH 1 PART A MECH ROOF PLAN
M1A-2.1	MECHANICAL SCHEDULE
M1A-2.2	MECHANICAL DETAILS
P1A-1.0	PH 1 PART A DEMO PLUMB. FLOOR PLAN
P1A-1.1	PH 1 PART A PLUMBING FLOOR PLAN
P1A-1.2	PH 1 PART A PLUMBING FLOOR PLAN
P1A-2.1	PLUMBING SCHEDULES AND DETAILS
E1A-0.0	ELECTRICAL SYMBOLS & DETAILS
E1A-0.1	ELECTRICAL SITE PLAN
E1A-0.2	EXISTING LIGHTING PLAN
E1A-0.3	EXISTING POWER / SYSTEMS PLAN
E1A-1.0	LIGHTING PLAN
E1A-2.0	POWER PLAN
E1A-2.1	ELECTRICAL ROOF PLAN
E1A-3.0	SPECIAL SYSTEMS PLAN
E1A-4.0	FIRE ALARM SYSTEM PLAN
E1A-5.0	POWER RISER DIAGRAMS & SCHEDULES
E1A-5.1	ELECTRICAL SCHEDULES & DETAILS

GENERAL NOTES:


- ALL WORK SHALL MEET CURRENT ADOPTED STATE, LOCAL CODES, ORDINANCES, & 2018 IBC & I.E.B.C. 2018.
- ALL MECHANICAL, ELECTRICAL, & PLUMBING WORK SHALL MEET ALL CURRENT APPLICABLE STATE & LOCAL CODES.
- ALL UTILITIES SHALL BE PROPERLY IDENTIFIED & LOCATED BEFORE WORK BEGINS ON PROJECT.
- CONTRACTOR SHALL VERIFY ALL CONDITIONS & DIMENSIONS AT THE JOB SITE & NOTIFY THE ARCHITECT OF ANY DIMENSIONAL ERRORS, OMISSIONS, OR DISCREPANCIES BEFORE BEGINNING OR FABRICATING ANY WORK.
- DO NOT SCALE DRAWINGS.
- ALL DOOR HANDLES SHALL BE LEVER TYPE, ALL DOOR HARDWARE SHALL BE A.D.A COMPLIANT AS PER CURRENT ANSI 117.1
- AT MAIN ENTRANCE DOOR SHALL HAVE SINGLE ACTION LOCKING DEVICE &/ OR SIGNED "THIS DOOR TO REMAIN UNLOCKED WHEN BUILDING IS OCCUPIED."

TWIN FALLS FIRE DEPARTMENT NOTES:

- IT SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO INSURE THAT ALL DEFERRED SUBMITTALS REQUIRED BY THE FIRE DEPARTMENT **HAVE BEEN APPROVED BY THE STATE PRIOR TO THE INSTALLATION OF A FIRE ALARM AND/OR FIRE SPRINKLER SYSTEM.** IT SHALL ALSO BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO VERIFY THAT ALL APPROPRIATE TESTING AND/OR INSPECTIONS HAVE BEEN PERFORMED BEFORE COVERING OR CALLING FOR A FINAL INSPECTION.
- FIRE SPRINKLER UNDERGROUND PIPING THE UNDERGROUND FIRE SPRINKLER LINE MUST MEET NFPA 24 AND THE CITY OF TWIN FALLS STANDARDS. THE INSPECTION AND TESTING OF THE UNDERGROUND FIRE SPRINKLER LINE SHALL BE OVERSEEN BY THE TWIN FALLS FIRE MARSHAL. SPRINKLER SYSTEM(S) SHALL BE SENT TO THE STATE FIRE MARSHAL OFFICE AND DESIGNED IN ACCORDANCE WITH CURRENT NFPA 13 STANDARDS. IDAHO STATE FIRE MARSHAL 700 WEST STATE STREET, 3RD FLOOR BOISE, IDAHO 83720 PLANS SHALL MEET CURRENT IFC, NFPA 13R AND IDAHO STATE PLUMBING CODES, AND BE APPROVED PRIOR TO INSTALLATION.
- FDC VISUAL ALARM A VISUAL ALARM DEVICE (EXTERIOR HORN/STROBE) SHALL BE PROVIDED IN THE AREA OF THE FDC. APPROVED SIGNS SHALL BE INSTALLED ON THE FIRE RISER ROOM DOOR AND ON THE FIRE DEPARTMENT CONNECTION.

ABBREVIATIONS

AC	ACOUSTICAL CEILING	DIA	DIAMETER	GYP BD	GYPSUM BOARD	PL	PLATE, PLASTIC LAMINATE	T	THREAD
ADJ	ADJUSTABLE - ADJACENT	DIM	DIMENSION	HB	HOSE BIB	P-LAM	PLASTIC LAMINATE	TBB	TILE BACKER BOARD
AFF	ABOVE FINISH FLOOR	DF	DRINKING FOUNTAIN	HC	HANDICAPPED	PLWD	PLYWOOD	T&G	TONGUE AND GROOVE
AL	ALUMINUM	DP	DEEP	HDR	HEADER	PNL	PANEL	TO	TO OF
ALT	ALTERNATE	DR	DOOR	HM	HOLLOW METAL	PORC. TILE	PORCELAIN TILE	TOW	TOP OF WALL
ANOD	ANODIZED	DS	DOWNSPOUT	HORIZ	HORIZONTAL	FR	PAIR	TPD	TOILET PAPER DISPENSER
AP	ACOUSTICAL WALL PANEL	DWG	DRAWING	HT	HEIGHT	PSF	POUNDS PER SQUARE FOOT	TSKD	TOILET SEAT COVER DISPENSER
APPROX	APPROXIMATE	E	EAST	HVAC	HEATING/VENTILATING/	PSI	POUNDS PER SQUARE INCH	TT	TIRE TREAD
ARCH	ARCHITECT (-URAL)	(E)	EXISTING		AIR CONDITIONING	PT	PAIN, PRESSURE TREATED	TYP	TYPICAL
AW	ACOUSTICAL WALL	EA	EACH	ILO	IN LIEU OF	PTD	PAPER TOWEL DISPENSER	UNO	UNLESS NOTED OTHERWISE
AWF	ACOUSTICAL WALL FABRIC	EJ	EXPANSION JOINT	INSUL	INSULATION	QT	QUARTZ TILE	UIS	UNDERSIDE
BLDG	BUILDING	EL	ELEVATION	R	RISER	R	RUBBER SHEET FLOORING	VB	VAPOR BARRIER
BM	BEAM	ELEC	ELECTRIC (-AL)	JNT	JOINT	RB	RESILIENT BASE	VCT	VINYL COMPOSITION TILE
BOD	BOTTOM OF DECK	EP	ENAMEL PAINT	KD	KNOCK DOWN	RD	ROUGH OPENING	VERT	VERTICAL
BOT	BOTTOM	EQ	EQUAL	LAV	LAVATORY	RO	ROUGH OPENING	VG	VINYL GYM FLOORING
BTWN	BETWEEN	EW	EACH WAY	MCFF	MULTI-COLORED FINISH	RR	RESTROOM	VIF	VINYL INDUSTRIAL FLOORING
CB	CATCH BASIN	EXG	EXISTING	MDO	MEDIUM DENSITY	RSF	RUBBER SHEET FLOORING	VT	VAPOR RETARDER
CBT	CABINET	EXP	EXPANSION		OVERLAY PLYWOOD	S	SOUTH	VT	VINYL TILE
CJ	CORNER GUARD	EXT	EXTERIOR		MECHANIC (-AL)	SC	SOLID CORE	VWF	VINYL WALL FABRIC
CJ	CONTROL JOINT	FA	FIRE ALARM	MECH	MECHANIC (-AL)	SCU	STRUCTURAL CLAY UNIT	W	WEST
CL	CENTERLINE	FD	FLOOR DRAIN	MFR	MANUFACTURE (-R)	SD	SOAP DISPENSER	W/C	WATER CLOSET
CLG	CEILING	FE	FIRE EXTINGUISHER	MN	MINIMUM	SDSV	STATIC DISIPATIVE SHEET VINYL	WD	WOOD
CLR	CLEAR (-ANCE)	FEC	FIRE EXTINGUISHER CABINET	MISC	MISCELLANEOUS	SF	SPECIALTY FINISH	W/D	WASHER & DRYER
CMT	CERAMIC MOSAIC TILE	FF	FACTORY FINISH, FINISH FLOOR	MRGB	MOISTURE RESISTANT	SFGL	SAFETY GLASS	WDO	WINDOW
CMU	CONCRETE MASONRY UNIT	FIN	FINISH (-ED)		GYPSUM BOARD	SHTG	SHEATHING	WF	WALL FABRIC
CO	CLEAN OUT	FLR	FLOOR (-ING)	MTL	METAL	SIM	SIMILAR	W/FV	WOOD FACE VENEER
COL	COLUMN	FND	FOUNDATION	N	NORTH	SL	SLOPE	WG	WIRE GUARD
CONC	CONCRETE	(N)	FACE OF CONCRETE	(N)	NEW	SND	SANITARY NAPKIN DISPENSER	WGL	WELDED GLASS
CONT	CONTINUOUS, CONTINUE	NA, N/A	FIBERGLASS REINFORCED	NA, N/A	NOT APPLICABLE	SP	SPACE (-S)	WM	WIRE MESH
CORR	CORRIDOR	NDU	PLASTIC PANEL	NDU	NOT IN CONTRACT	SPEC	SPECIFICATION	W/O	WITHOUT
CP	CARPET	FRVR	FLAME RESISTANT VAPOR BARRIER		SANITARY NAPKIN	SQ	SQUARE	WOC	WALK-OFF CARPET
CS	CONCRETE SLAB, SEALED	FT	FOOT, FEET		DISPOSAL UNIT	S/S	STAINLESS STEEL	WP	WATERPROOFING
CT	CERAMIC TILE	FTG	FOOTING	NOM	NOMINAL	ST	STAIN	WPS	WALL PROTECTION SYSTEM
CTJ	CONTROL JOINT	FWC	FABRIC WALL COVERING	NTS	NOT TO SCALE	STL	STEEL	WR	WATER RESISTANT
CTR	COUNTER (-TOP)	GA	GAUGE	OC	ON CENTER	STR	STRUCTURE (-AL)	WRGB	WATER RESISTANT GYPSUM
DBL	DOUBLE	GALV	GALVANIZED	OD	OUTSIDE DIAMETER	STRG	STORAGE		WALLBOARD
DET	DETAIL	GH	GARMENT HOOK	OPP	OPPOSITE	SV	SHEET VINYL FLOORING	W/WF	WELDED WIRE FABRIC
		GMM	GLASS MESH MORTAR BOARD	PCMU	PRE-FACED CMU			W/	WITH



1 VICINITY MAP
N.T.S.

DESIGN TEAM:

CIVIL: CIVIL SCIENCE CONTACT: STEPHAN ANDERSEN ADDRESS: 376 FALLS AVE TWIN FALLS, ID 83301 PHONE: (208) 737-0007 X 210	STRUCTURAL: RIDGE STRUCTURAL ENGINEERING CONTACT: DAVID PORTER ADDRESS: 1020 E. LINCOLN RD IDAHO FALLS, ID 83401 PHONE: (208) 227-8404
MECHANICAL & PLUMBING: ENGINEERED SYSTEMS ASSOCIATES CONTACT: DAVE HANSEN ADDRESS: 1355 EAST CENTER POCATELLO, ID 83201 PHONE: (208) 233-0501	ELECTRICAL: PAYNE ENGINEERING INC CONTACT: SHAWN MEADOR ADDRESS: 1823 E. CENTER POCATELLO, ID 83201 PHONE: (208) 232-4439
CODE CONSULTANT: SHUMS CODA ASSOCIATES CONTACT: STEVE THOMAS ADDRESS: 5610 SOUTH ULSTER ST., STE 150 DENVER, CO 80237 PHONE: (303) 257-3572	

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2515 Wright Ave, Twin Falls, ID 83301
TITLE SHEET

Laughlin Ricks Architecture
architecture/planning
134 3rd Ave East, Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Drawn RCR Checked
#23029 PROJECT #

A1A-0.0

OCCUPANT LOAD

SMOKE COMPARTMENT 1

DAY ROOM FOR CELL BLOCK 13	560 SF / 30 = 19
TOTAL	19

SMOKE COMARTMENT 2

STORAGE / MECH/ EQUIPMENT	1,668 SF / 300 = 6
OFFICE / BUSINESS	5,959 SF / 150 = 40
TOTAL	46

SMOKE COMPARTMENT 3

BOOKING CELLS (2 BEDS EA UNIT)	10 X 2 = 20
OFFICE / BUSINESS	937 SF / 150 = 7
STORAGE / MECH/ EQUIPMENT	23 SF / 300 = 1
TOTAL	28


SMOKE COMPARTMENT 4

PARKING GARAGE	2,883 SF / 200 = 15
OFFICE / BUSINESS	483 SF / 150 = 4
TOTAL	19

GRAND TOTAL OCCUPANTS 112

- SMOKE BARRIER
- 1 HR FIRE PARTITION

PH 1 PART 1 - OCCUPANT LOAD
1/4" = 1'-0"



PLUMBING FIXTURE COUNT

OCCUPANT LOAD = 112
OCCUPANT LOAD - CELLS = 73

TOILETS

1 PER CELL
1 PER CELL = 22 PROVIDED
MEN 1 PER 25
1 PER 25 = 2 REQ'D
37 / 25 = 2 REQ'D
WOMEN 1 PER 25
1 PER 25 = 2 REQ'D
37 / 25 = 2 REQ'D
5 SINGLE USER TOILET ROOMS PROVIDED

LAVATORIES

1 PER CELL
1 PER CELL = 22 PROVIDED
MEN 1 PER 35
1 PER 35 = 1 REQ'D
37 / 35 = 1 REQ'D
WOMEN 1 PER 35
1 PER 35 = 1 REQ'D
37 / 35 = 1 REQ'D
5 SINGLE USER TOILET ROOMS PROVIDED

SHOWERS

1 PER 12 INMATES
19 + 20 = 39 INMATES
36 / 12 = 3 REQ'D
3 EXISTING

DRINKING FOUNTAIN

1 PER 100
2 FOUNTAINS REQUIRED
1 HIGH/LOW DRINKING FOUNTAIN PROVIDED


OTHER

1 SERVICE SINK
1 REQ'D
1 PROVIDED

SMOKE BARRIER SHALL EXTEND FROM THE FLOOR TO THE UNDERSIDE OF THE FLOOR DECK OR SLAB ABOVE. SMOKE-BARRIER WALLS USED TO SEPERATE SMOKE COMPARTMENTS SHALL FORM AN EFFECTIVE MEMBRANE CONTINUOUS FROM OUTSIDE WALL TO OUTSIDE WALL. MINIMUM ONE-HOUR FIRE-RESISTANCE.

FIRE PARTITION SHALL EXTEND FROM THE TOP OF THE FLOOR TO THE UNDERSIDE OF THE FLOOR DECK OR SLAB ABOVE.

1 PH 1 PART A MAIN FLOOR OCCUPANCY
1/8" = 1'-0"




PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
CODE ANALYSIS- OCCUPANCY

Laughlin Ricks Architecture
architecture/planning
134 3rd Ave East, Twin Falls, Idaho 83301
(208) 756-8050

DATE: 7.15.24
KM Draw
RCR Checked
#23029
PROJECT #

A1A-0.2



① PH 1 PART A MAIN FLOOR EXITING
1/8" = 1'-0"

LICENSED ARCHITECT
R. COLBY RICKS
STATE OF IDAHO
7.15.24

DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
CODE ANALYSIS - EXITING

Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Draw #23029
RCR Checked

A1A-0.3



LICENSED ARCHITECT
R. Colby Ricks
 R. COLBY RICKS
 STATE OF IDAHO
 7.15.24

DATE _____



PHASE 1 PART A FOR:
 TWIN FALLS COUNTY - WRIGHT AVE JAIL
 2815 Wright Ave, Twin Falls, ID 83301
 CODE ANALYSIS - FIRE & SMOKE

Laughlin Ricks Architecture
 architecture/planning
 134 3RD Ave East, * Twin Falls, Idaho 83301
 (208) 736-8050

DATE: 7.15.24
 KM Drawn RCR Checked
 #23029
 PROJECT #

A1A-0.4


PH 1 PART A MAIN FLOOR FIRE & SMOKE
 1/8" = 1'-0"




NOTE: AT RESTROOMS/TOILET ROOMS THE TOWEL, SOAP, AND SANITARY NAPKIN DISPENSERS ARE TO BE INSTALLED SO AS NOT TO EXCEED 40" AFF TO ANY OPERATING CONTROLS, RECEPTACLE, OR DISPENSER.

1. PROTECTION UNDER SINKS
606.6 EXPOSED PIPES AND SURFACES. WATER SUPPLY AND DRAINPIPES UNDER LAVATORIES AND SINKS SHALL BE INSULATED OR OTHERWISE CONFIGURED TO PROTECT AGAINST CONTACT. THERE SHALL BE NO SHARP OR ABRASIVE SURFACES UNDER LAVATORIES AND SINKS.
2. FLUSH CONTROLS
604.6 FLUSH CONTROLS. FLUSH CONTROLS SHALL BE HAND OPERATED OR AUTOMATIC. HAND OPERATED FLUSH CONTROLS SHALL BE LOCATED ON THE OPEN SIDE OF THE WATER CLOSET. EXCEPTION: IN AMBULATORY ACCESSIBLE COMPARTMENTS COMPLYING WITH SECTION 604.9, FLUSH CONTROLS SHALL BE PERMITTED TO BE LOCATED ON EITHER SIDE OF THE WATER CLOSET.
3. TOILET PAPER DISPENSER
604.7 DISPENSERS. TOILET PAPER DISPENSERS SHALL COMPLY WITH SECTION 309.4 AND SHALL BE 7 INCHES (180 mm) MINIMUM AND 9 INCHES (230 mm) MAXIMUM IN FRONT OF THE WATER CLOSET MEASURED TO THE CENTERLINE OF THE DISPENSER. THE OUTLET OF THE DISPENSER SHALL BE 15 INCHES (380 mm) MINIMUM AND 48 INCHES (1220 mm) MAXIMUM ABOVE THE FLOOR, AND SHALL NOT BE LOCATED BEHIND THE GRAB BARS. DISPENSERS SHALL NOT BE OF A TYPE THAT CONTROL DELIVERY, OR DO NOT ALLOW CONTINUOUS PAPER FLOW.





1 GENERAL - FIXTURE MOUNTING HEIGHTS
1/4" = 1'-0"




2 OPERABLE PARTS & REACH RANGES
3/8" = 1'-0"




4 SIGNAGE - SIGNAGE TYPES
1 1/2" = 1'-0"




3 DOOR CLEARANCE REQUIREMENTS
3/8" = 1'-0"



5 ACCESSIBLE ENTRANCE
1/4" = 1'-0"



6 VERTICAL CHANGES IN LEVEL
12" = 1'-0"



PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
CODE REQUIREMENTS

Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Draw RCR Checked
#23029 PROJECT #

A1A-0.6


DATE _____

PHASE 1 PART A FOR:
 TWIN FALLS COUNTY - WRIGHT AVE JAIL
 2815 Wright Ave, Twin Falls, ID 83301
 CODE REQUIREMENTS

Laughlin Ricks Architecture
 architecture/planning
 134 3RD Ave East, * Twin Falls, Idaho 83301
 (208) 756-8050


DATE: 7.15.24
 KM Draw RCR Checked
 #23029
 PROJECT #

A1A-0.7




1. SHALL BE FABRICATED FROM .080 ALUMINUM SHEET WITH MIN. OF .75" RADIUS CORNERS
2. FONT STYLE IS HANDEL GOTHIC BT CAPITAL FONTS WITH ADDITIONAL KERNING BETWEEN LETTERS
3. THE SIGN FACE SHALL HAVE A WHITE 3M DIAMOND GRADE REFLECTIVE SHEETING (3990 SERIES VIP TYPE IX) APPLIED AS A BACKGROUND
4. LETTERING/GRAPHICS SHALL BE ONE OF THE FOLLOWING:
 - A. 3M ELECTRO CUT FILM RED 117Z OR ORACAL 8300 TRANSPARENT CAL 201C RED OR EQUIVELANT IN DURABILITY, INVERSE CUT TO ALLOW REFLECTIVE BACKGROUND TO SHOW THROUGH LETTERING.
 - B. SCREEN PRINTED USING 3M 8801 SERIES TRAFFIC SIGN RED TRANSLUCENT INK
5. SIGNS USED IN BUILDING INTERIORS ARE NOT REQUIRED TO USE A REFLECTIVE BACKGROUND.
6. ALL SIGNAGE AND CHANGES MUST BE PRE-APPROVED BY THE FIRE MARSHAL

③ SIGNAGE - SIGNAGE TYPES - FIRE
 1 1/2" = 1'-0"




② LAVATORY CLEARANCE
 1" = 1'-0"




- RECESSED FOUNTAINS:**
1. WITHIN ALCOVES MINIMUM 63" WIDE, MINIMUM 18" DEEP WHEN DOUBLE DRINKING FOUNTAINS ARE REQUIRED AND 32" MIN. CLR. WHEN A SINGLE FOUNTAIN IS PERMITTED
 - A. CONTRACTORS SHALL COORDINATE WITH SIZE OF WATER FOUNTAIN TO BE USED AND SIZE ALCOVE ACCORDINGLY COMPLYING WITH REQUIREMENTS AND RECOMMENDATIONS AND COORDINATING WITH THE ARCHITECT.
- PROJECTED FOUNTAINS:**
1. WARNING FOR THE VISION IMPAIRED AT A PROJECTED DRINKING FOUNTAIN CAN BE PROVIDED BY EITHER OF THE FOLLOWING MEANS:
 - A. THE SURFACE OF THE FLOOR OR GROUND AT THE DRINKING FOUNTAIN CAN BE OF CONTRASTING COLOR WITH TEXTURE THAT CONTRASTS IN RESILIENCY WITH THE ADJACENT FINISHED FLOOR MATERIAL, SO THAT IT CAN BE SENSED BY A CANE WITH THE TEXTURE EXTENDING FROM THE WALL TO ONE FOOT BEYOND THE FRONT EDGE OF THE DRINKING FOUNTAIN AND ONE FOOT BEYOND EACH SIDE OF THE FOUNTAIN, OR
 - B. INSTALL WING WALLS ON EACH SIDE OF THE DRINKING FOUNTAIN TO PROJECT OUT FROM THE MAIN WALL AT LEAST AS FAR AS THE DRINKING FOUNTAIN AND TO WITHIN 6" OF THE PATH OF TRAVEL FLOOR FINISH. THERE MUST BE 32" CLEAR BETWEEN THE WING WALLS, OR
 - C. INSTALL ADA ACCESSORY CANE GUARD

NOTE:
 ILLUSTRATIONS SHOWN HERE ARE FOR DIMENSIONAL ACCESSIBILITY PURPOSES ONLY. A SECOND DRINKING FOUNTAIN SHOULD BE PROVIDED AT A MOUNTING HEIGHT SUITABLE TO PERSONS WITH LIMITED PHYSICAL BENDING ABILITY, ADJACENT TO THE ACCESSIBLE FOUNTAIN, MAINTAINING MINIMUM CLEARANCES NOTED AND AS REQUIRED. PROVIDE TEXTURED AREA OF CONTRASTING COLOR TO IDENTIFY WATER FOUNTAIN LOCATION AS NOTED. WHEN FOUNTAIN IS AT AN INTERIOR LOCATION, THE TEXTURED AREA SHALL ALSO BE DIFFERENT RESILIENCY THAN THAT OF THE ADJACENT FLOOR SURFACE FINISH. SEE TYPICAL ACCESSIBILITY NOTES SHEET FOR ADDITIONAL REQUIREMENTS.

④ DRINKING FOUNTAIN DETAIL 1
 1/4" = 1'-0"



DEMO KEYNOTES	
Key Value	Keynote Text
201	REMOVE FENCING IN ITS ENTIRETY




DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
 2815 Wright Ave, Twin Falls, ID 83301
PH 1 PART A DEMO SITE PLAN

Laughlin Ricks Architecture
 architecture/planning
 134 3RD Ave East, * Twin Falls, Idaho 83301
 (208) 736-8050

DATE: 7.15.24	
KM Drawn	RCR Checked
#23029	PROJECT #

A1A-1.0




① PH 1 PART A - DEMO SITE
 1" = 30'-0"

PARCEL ID: RPT54650010050
 PARCEL SF SIZE: 180,643.11
 ADDRESS: 2515 WRIGHT AVE, TWIN FALLS, ID 83301
 ZONING DISTRICT: M-2

PHASE 1 PART A & B
 15 EMPLOYEES PER SHIFT
 15 + 15 AT SHIFT CHANGE = 30
 PLUS 7 ATTORNEY ROOMS
 PLUS 2 VISITATION MONITORS
 TOTAL REQ'D = 39

LANDSCAPING:
 2 SF PER LINERAR FOOT OF FRONTAGE
 447 X 2 = 894 SF
 15,874 SF PROVIDED

PROPERTY SET BACKS:
 15' ON OTHER STREETS FROM PROPERTY LINE




DATE _____

PHASE 1 PART A FOR:
 TWIN FALLS COUNTY - WRIGHT AVE JAIL
 2515 Wright Ave, Twin Falls, ID 83301
 PH 1 PART A REMODEL SITE PLAN

Laughlin Ricks Architecture
 architecture/planning
 134 3RD Ave East, * Twin Falls, Idaho 83301
 (208) 736-8050



DATE: 7.15.24
 KM Drawn RCR Checked
 #23029 PROJECT #

A1A-1.1



① PH 1 PART A - REMODEL SITE
 1" = 30'-0"

Plot Date: 7/19/2024 10:24 AM Plotted By: Stephen Andersen
 Date Created: 7/19/2024 1:10:40 PM PROJECTS/ACTIVE/2024/IF24252.00 - TWIN FALLS COUNTY JAIL ELDRIDGE AVE/70 - CAD/DESIGN/TWFCO CIVIL PLAN 20240719.DWG



REUSE OF DRAWINGS
 THIS DOCUMENT, AND THE IDEAS AND DESIGNS INCORPORATED HEREIN, ARE THE PROPERTY OF CIVIL SCIENCE AND IS NOT TO BE USED, IN WHOLE OR PART, FOR ANY OTHER PROJECT WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF CIVIL SCIENCE.

NO.	DESCRIPTION	BY	DATE

UTILITY PLAN
CIVIL ENGINEERING DRAWINGS
 WRIGHT AVENUE JAIL
 WRIGHT AVENUE
 TWIN FALLS, IDAHO




FILE : TWFCO CIVIL PLAN 20240719
 CSI PROJ. # : IF-24252.00
 DRAWN BY: SRA
 DESIGN BY: SRA
 CHECKED BY: SRA
 ONE INCH
 AT FULL SIZE, IF NOT ONE INCH, SCALE ACCORDINGLY
 LAST UPDATED: 7/19/2024

PARCEL ID: RPT54650010050
 PARCEL SF SIZE: 180,643.11
 ADDRESS: 2515 WRIGHT AVE, TWIN FALLS, ID 83301
 ZONING DISTRICT: M-2

PHASE 1 PART A & B
 15 EMPLOYEES PER SHIFT
 15 + 15 AT SHIFT CHANGE = 30
 PLUS 7 ATTORNEY ROOMS
 PLUS 2 VISITATION MONITORS
 TOTAL REQ'D = 39

LANDSCAPING:
 2 SF PER LINERAR FOOT OF FRONTAGE
 447 X 2 = 894 SF
 15,874 SF PROVIDED

PROPERTY SET BACKS:
 15' ON OTHER STREETS FROM PROPERTY LINE




DATE _____

PHASE 1 PART A FOR:
 TWIN FALLS COUNTY - WRIGHT AVE JAIL
 2515 Wright Ave, Twin Falls, ID 83301
 PH 1 PART A REMODEL SITE PLAN

Laughlin Ricks Architecture
 architecture/planning
 134 3RD Ave East, * Twin Falls, Idaho 83301
 (208) 736-8050



DATE: 7.15.24
 KM Drawn RCR Checked
 #23029 PROJECT #

A1A-1.1



① PH 1 PART A - REMODEL SITE
 1" = 30'-0"

Plot Date: 7/19/2024 10:22 AM Plotted By: Stephen Andersen
 Date Created: 7/19/2024 11:40 AM Project: ACTIVE 2024 IF 24252.00 - TWIN FALLS COUNTY JAIL ELDRIDGE AVE/700 - CAD DESIGN/TWFCO CIVIL PLAN 20240719.DWG



REUSE OF DRAWINGS
 THIS DOCUMENT AND THE IDEAS AND DESIGNS INCORPORATED HEREIN ARE THE PROPERTY OF CIVIL SCIENCE AND IS NOT TO BE USED IN WHOLE OR PART FOR ANY OTHER PROJECT WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF CIVIL SCIENCE



NO.	REVISION	DESCRIPTION	BY	DATE

SITE PLAN
CIVIL ENGINEERING DRAWINGS
 WRIGHT AVENUE JAIL
 WRIGHT AVENUE
 TWIN FALLS, IDAHO

FILE: TWFCO CIVIL PLAN 20240719
 CSI PROJ. #: IF-24252.00
 DRAWN BY: SRA
 DESIGN BY: SRA
 CHECKED BY: SRA
 ONE INCH
 AT FULL SIZE, IF NOT ONE
 INCH, SCALE ACCORDINGLY
 LAST UPDATED: 7/19/2024



Plot Date: 7/19/2024 10:22 AM Plotted By: Stephen Andersen
 Date Created: 7/19/2024 1:10:40 PM PROJECTS/ACTIVE/2024/IF24252.00 - TWIN FALLS COUNTY JAIL ELDRIDGE AVE/70 - CAD/DESIGN/TWFCO CIVIL PLAN 20240719.DWG



STORMWATER CALCULATIONS

IT IS ASSUMED THAT THE DRIVE AISLE AND BUILDINGS HAVE A RUNOFF COEFFICIENT OF 0.95. THE VOID RATIO FOR THE DRAIN ROCK IS ASSUMED TO BE 0.40.

THE RUNOFF WATER FROM THE NEW ASPHALT LANE NORTH OF THE NORTH WALL OF THE NEW BUILDING WILL ALL BE RETAINED IN THE SUBSURFACE SEEPAGE BED.

THE RUNOFF WATER FROM THE NEW BUILDING ROOF AND THE ASPHALT SOUTH OF THE NORTH WALL OF THE NEW ADDITION NORTH WALL WILL ALL BE RETAINED IN THE RETENTION POND.

SUBSURFACE SEEPAGE BED CALCULATIONS
 AREA OF ASPHALT NORTH OF THE NORTH WALL OF THE NEW ADDITION = 11,291 S.F.
 TOTAL HARD SURFACE AREA TO BE RETAINED = 11,291 S.F.

VOLUME CALCULATION
 VOLUME REQUIRED = (11,291 S.F. X 1.9 IN /12 IN/FT) X 0.95 = 1,698 CUBIC FEET
 VOLUME PROVIDED = 27'X40'X4' X 0.40 = 1,728 CUBIC FEET
 VOLUME PROVIDED IS GREATER THAN VOLUME REQUIRED.

RETENTION POND CALCULATIONS
 AREA OF ASPHALT SOUTH OF THE NORTH WALL OF THE NEW ADDITION = 2,981 S.F.
 AREA OF NEW BUILDING ADDITION = 5,128 S.F.
 AREA OF LANDSCAPE ISLAND TO BE REMOVED AND PAVED AND NEW SIDEWALK = 658 S.F.
 TOTAL HARD SURFACE AREA TO BE RETAINED = 8,767 S.F.

VOLUME CALCULATION
 VOLUME REQUIRED = (8,767 S.F. X 1.9 IN /12 IN/FT) X 0.95 = 1,319 CUBIC FEET
 VOLUME PROVIDED = 1,486 CUBIC FEET
 VOLUME PROVIDED IS GREATER THAN VOLUME REQUIRED.

REUSE OF DRAWINGS
 THIS DOCUMENT, AND THE IDEAS AND DESIGNS INCORPORATED HEREIN, ARE THE PROPERTY OF CIVIL SCIENCE AND IS NOT TO BE USED IN WHOLE OR IN PART FOR ANY OTHER PROJECT WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF CIVIL SCIENCE.




NO.	REVISION	DESCRIPTION	BY	DATE



FILE : TWFCO CIVIL PLAN 20240719
 CSI PROJ. # : IF-24252.00
 DRAWN BY: SRA
 DESIGN BY: SRA
 CHECKED BY: SRA
 ONE INCH
 AT FULL SIZE, IF NOT ONE
 INCH, SCALE ACCORDINGLY
 LAST UPDATED: 7/19/2024

NOTES:


1. GEOTEXTILE FABRIC SHALL BE NONWOVEN TYPE III PER THE 2020 ISPC DIVISION 2000 TABLE 3 SECTION 203
2. FILL BETWEEN GEOTEXTILE FABRIC SHALL BE COMPACTED TO 90% MODIFIED PROCTOR TO PREVENT BLOCKS FROM OVERTURNING DURING COMPACTION PROCESS.
3. 3/4" CRUSHED ROCK BACKFILL SHALL BE EXTENDED TO THE BOTTOM OF THE ASPHALT LAYER ALONG THE BLOCK RETAINING WALL.
4. CONCRETE BLOCKS SHALL HAVE A MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 2,000 PSI.
5. GEOTEXTILE FABRIC SHALL EXTEND TO WITHIN 3" OF CREEKSIDE FACE OF THE RETAINING BLOCKS WHERE PLACED BETWEEN BLOCKS.
6. BLOCKS SHALL HAVE A MINIMUM DIMENSION OF 24"x24"x48".
7. TOP BLOCKS SHALL HAVE A FLAT LEVEL SURFACE.
8. BLOCKS SHALL HAVE INTERLOCKING SURFACES ON THE BOTTOM AND TOP OF EACH BLOCK EXCEPT FOR TOP LAYER OF BLOCKS WHICH SHALL HAVE A BOTTOM INTERLOCKING SLOT ONLY. (SUBMIT BLOCK DESIGN TO ENGINEER PRIOR TO PURCHASE OR INSTALLATION OF BLOCKS FOR ENGINEER'S APPROVAL)
9. FLOOD PLAIN ELEVATION AND LINEWORK WERE TAKEN FROM THE FEMA FIRM FLOOD INSURANCE RATE MAP PANEL 1391 OF 1650 (MAP NUMBER 16083C1391C) FLOOD MAP INFORMATION WAS OVERLAID USING GOOGLE EARTH IMAGERY AND LINING UP RAILROAD BRIDGES ADJACENT TO THE PROJECT SITE TO LOCATE MAP OVER EXISTING TOPOGRAPHY)



REUSE OF DRAWINGS
 THIS DOCUMENT AND THE IDEAS AND DESIGNS INCORPORATED HEREIN ARE THE PROPERTY OF CIVIL SCIENCE AND IS NOT TO BE USED IN WHOLE OR IN PART FOR ANY OTHER PROJECT WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF CIVIL SCIENCE



NO.	REVISION	DESCRIPTION	BY	DATE

DETAILS
CIVIL ENGINEERING DRAWINGS
 WRIGHT AVENUE JAIL
 WRIGHT AVENUE
 TWIN FALLS, IDAHO



Plot Date: 7/19/2024 10:27 AM Plotted By: Stephen Andersen
 Date Created: 7/19/2024 1:10:40 PM Project: ACTIVE 2024 IF 24252.00 - TWIN FALLS COUNTY JAIL ELDRIDGE AVENUE - CAD DESIGN TWFCO CIVIL PLAN 20240719.DWG

PLAT SHOWING ⁸⁷⁰⁵¹⁴
VALLEY INDUSTRIAL SUBDIVISION NO. 2
 A SUBDIVISION IN
 THE NW 1/4 SECTION 23, T.10 S., R.17 E., B.M.
 TWIN FALLS, TWIN FALLS COUNTY, IDAHO
 1984



VICINITY SKETCH
 SCALE IN FEET

CURVE DATA

CURVE	R	Δ	T	L	CH. L.	CH. BEARING
C-1	60.00'	141°19'04"	170.94'	147.99'	113.23'	S.71°09'11" W.
C-2	20.00'	51°19'04"	9.61'	17.91'	17.32'	N.63°50'49" W.
C-3	60.00'	141°19'04"	170.94'	147.99'	113.23'	N.70°09'53" W.
C-4	20.00'	51°19'04"	9.61'	17.91'	17.32'	S.64°50'07" W.




LEGEND

- ⊙ Brass Cap
- 3/4" x 30" Steel Rebar
- 5/8" x 30" Steel Rebar
- 1/2" x 24" Steel Rebar
- ⊙ Witness Corner (1/2" Steel Rebar)
- Public Utilities, Irrigation, and Drainage Easements As Noted.

NOTES

1. The South 20' Of The U.P.R.R. Spur Line Easement Is Reserved For A Spur Track And Not Designated For Utility Use.
2. There Is Herby Reserved Along All Lot Frontages, Adjacent To Streets, A 5' Wide Easement For Public Utilities.



UNPLATTED

UNPLATTED

Twin Falls County, Idaho
 Recorded For:
 JUB ENG
 09:00:00 am Nov. 01, 1984
 0000 - 870514

J-U-B ENGINEERS, INC.
 Engineers Surveyors Planners
 Twin Falls, Idaho


SHEET 1 OF 2

Valley Industrial
 #2
 Book 13 Page 15



REUSE OF DRAWINGS
 THIS DOCUMENT AND THE IDEAS AND DESIGNS INCORPORATED THEREIN ARE THE PROPERTY OF CIVIL SCIENCE AND IS NOT TO BE USED IN WHOLE OR IN PART FOR ANY OTHER PROJECT WITHOUT THE EXPRESS WRITTEN AUTHORIZATION OF CIVIL SCIENCE


NO.	REVISION	DESCRIPTION	BY	DATE



DEMO KEYNOTES	
Key Value	Keynote Text
301	REMOVE WALL IN ITS ENTIRETY AS SHOWN BY DASHED LINES
302	REMOVE DOOR SYSTEM IN ITS ENTIRETY
303	REMOVE WINDOW SYSTEM IN ITS ENTIRETY
304	REMOVE STUCCO SYSTEM IN ITS ENTIRETY
305	REMOVE PLUMBING FIXTURE
306	REMOVE CASEWORK IN ITS ENTIRETY
307	REMOVE WALL AS REQUIRED FOR NEW DOOR, RELOCATE ANYTHING ON WALL AS REQUIRED, MODIFY BASE AS REQUIRED
309	REMOVE DOWNSPOUT AS REQUIRED TO DRAIN ONTO NEW ROOF
310	REMOVE LOCKERS
311	REMOVE CONCRETE BENCH IN ITS ENTIRETY
312	REMOVE WOOD PANELING IN ITS ENTIRETY
313	REMOVE RAILING IN ITS ENTIRETY
314	REMOVE STAIR IN ITS ENTIRETY
315	REMOVE CARPET IN ITS ENTIRETY
316	REMOVE SHEET VINYL IN ITS ENTIRETY
317	REMOVE VCT IN ITS ENTIRETY
319	
406	REMOVE HATCH IN ITS ENTIRETY

- GENERAL DEMOLITION NOTES:**
- AT WALL REMOVAL, ALL ELECTRICAL MECH & PLUMBING SHALL BE CONSIDERED INCIDENTAL & SHALL BE REMOVED AS PART OF DEMOLITION. ALSO SEE ELEC., MECH., & PLUMBING PLANS FOR OTHER NOTES OR REQUIREMENTS.
 - CONTRACTOR SHALL NOTIFY THE COUNTY OF DEMOLITION WORK BEFORE PROCEEDING W/ PROJECT DEMOLITION.
 - ALL HOLES, EMPTY ELECTRICAL BOXES, & CUT OFF PIPING THROUGH EXISTING FIRE WALLS & CORRIDOR SHALL BE FILLED & FIRE SEALED. ALSO, SEE MECH. DRAWINGS FOR ADDITIONAL REQ'MENTS.
 - ALL WALLS OF PROJECT SHALL HAVE ALL SCREWS, FASTENERS, & MISC. REMOVED AND HOLES PATCHED & REPAIRED AS REQUIRED FOR NEW FINISHES.
 - ALL NEW & EXIST'G METAL DOORS & WINDOW FRAMES SHALL BE PAINTED. SEE PAINT & COATING SPECIFICATIONS.
 - ALL POINTS OF WORK OF REMODEL SHALL BE BLENDED TO MATCH EXIST'G SURFACES & FINISH. DUE TO DEMOLITION WORK AFFECTING NEARBY BUILDING TENANTS SPACES, THE CONTRACTOR WILL BE RESPONSIBLE TO SCHEDULE WEEKLY MEETINGS WITH HIS SUBCONTRACTORS & PROJECT COORDINATOR BOB BEER T.F. COUNTY TO COORDINATE WORK TO BE SCHEDULE THAT WEEK.
 - CONTRACTOR WILL BE RESPONSIBLE FOR ANY REQUIRED REMOVAL OF CEILING, GRID, ETC. NECESSARY TO ACCESS WORK AREAS AND REINSTALL SUCH REMOVAL. CONTRACTOR SHALL REPLACE ANY DAMAGED OR SOILED MATERIALS AT CONTRACTORS OWN EXPENSE.
 - ALL POINTS OF WORK OF REMODEL SHALL BE BLENDED TO MATCH EXIST'G SURFACES & FINISH.
- CONSTRUCTION WASTE:**
- BEFORE ANY CONSTRUCTION WASTE IS REMOVED FROM THE PROJECT ALL ROUTES BEGINNING FROM THE STAGING AREA TO THE TENANT IMPROVEMENT AREA SHALL BE PROTECTED IN PLACE.
 - ALL DEBRIS MATERIAL SHALL BE DISPOSED OF IN A LAWFUL MANNER.

① PH 1 PART A DEMO FLOOR PLAN
1/8" = 1'-0"




DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
PH 1 PART A DEMO FLOOR PLAN


Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Draw RCR Checked
#23029 PROJECT #


A1A-1.2




① PH 1 PART A DEMO NORTH
1/8" = 1'-0"




② PH 1 PART A DEMO EAST 3
1/8" = 1'-0"



③ PH 1 PART A DEMO SOUTH 2
1/8" = 1'-0"




④ PH 1 PART A DEMO NORTH 2
1/8" = 1'-0"



⑤ PH 1 PART A DEMO SOUTH 3
1/8" = 1'-0"

DEMO KEYNOTES	
Key Value	Keynote Text
302	REMOVE DOOR SYSTEM IN ITS ENTIRETY
303	REMOVE WINDOW SYSTEM IN ITS ENTIRETY
304	REMOVE STUCCO SYSTEM IN ITS ENTIRETY
309	REMOVE DOWNSPOUT AS REQUIRED TO DRAIN ONTO NEW ROOF
313	REMOVE RAILING IN ITS ENTIRETY
314	REMOVE STAIR IN ITS ENTIRETY




DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2615 Wright Ave, Twin Falls, ID 83301
PH 1 PART A DEMO ELEVATIONS

Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050


DATE: 7.15.24
KM Drawn RCR Checked
#23029 PROJECT #

A1A-1.3



DEMO KEYNOTES	
Key Value	Keynote Text
301	REMOVE WALL IN ITS ENTIRETY AS SHOWN BY DASHED LINES
306	REMOVE CASEWORK IN ITS ENTIRETY
401	REMOVE 2X4 ACT GRID IN ITS ENTIRETY
402	REMOVE GYP BD CEILING
404	REMOVE MECHANICAL FIXTURE - REFER TO MECHANICAL DRAWINGS
405	REMOVE LIGHT FIXTURE - REFER TO ELECTRICAL DRAWINGS
406	REMOVE HATCH IN ITS ENTIRETY

1 PH 1 PART A DEMO RCP
1/8" = 1'-0"



DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
PH 1 PART A DEMO CEILING PLAN



Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Draw #23029
RCR Checked

A1A-1.5


1. ANY LOCATION WHERE WOOD IS TOUCHING CONCRETE, MASONRY, CMU, OR STEEL SHALL BE PRESSURE TREATED.
2. ALL WOOD SHALL BE DOUGLAS FIR #2 OR BETTER.
3. ALL NEW INTERIOR WALLS SHALL BE 8X8X16 U.N.O.
4. SMOKE PARTITIONS SHALL BE FULL HEIGHT WALLS.

○ GENERAL NOTES
1/4" = 1'-0"



② DOUBLE CELL TYP. U.N.O.
1/2" = 1'-0"

① PH 1 PART A MAIN FLOOR
1/8" = 1'-0"




PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
PH 1 PART A FLOOR PLAN

Laughlin Ricks Architecture
architecture/planning
134 3rd Ave East, Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Draw RCR Checked
#23029 PROJECT #

A1A-2.0



PH 1 PART A ENLARGED FLOOR -
 MEDICAL & CONTROL
 1/4" = 1'-0"

7.15.24


DATE

PHASE 1 PART A FOR:
 TWIN FALLS COUNTY - WRIGHT AVE JAIL
 2615 Wright Ave, Twin Falls, ID 83301
 ENLARGED FLOOR PLANS

Laughlin Ricks Architecture
 architecture/planning
 134 3RD Ave East, * Twin Falls, Idaho 83301
 (208) 736-8050

DATE: 7.15.24
 KM RCR
 Drawn Checked
 #23029
 PROJECT #

A1A-2.1



① PH 1 PART A MAIN FLOOR - Callout 1
1/4" = 1'-0"

LICENSED ARCHITECT
R. COLBY RICKS
STATE OF IDAHO
7.15.24


DATE

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2615 Wright Ave, Twin Falls, ID 83301
ENLARGED FLOOR PLAN


Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Drawn RCR Checked
#23029
PROJECT #

A1A-2.3



1 PH 1 PART A MAIN FLOOR - Callout 3
1/4" = 1'-0"




DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
ENLARGED FLOOR PLAN


Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, # Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24	
KM Drawn	RCR Checked
#23029	PROJECT #


A1A-2.4



① PH 1 PART A REMODEL NORTH
1/8" = 1'-0"



② PH 1 PART A EAST
1/8" = 1'-0"



③ PH 1 PART A REMODEL SOUTH
1/8" = 1'-0"

LICENSED ARCHITECT
R. COLBY RICKS
STATE OF IDAHO
7.15.24


DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2615 Wright Ave, Twin Falls, ID 83301
PH 1 PART A EXTERIOR ELEVATIONS

Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Draw RCR Checked
#23029
PROJECT #

A1A-3.0



DATE _____


PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
 2815 Wright Ave, Twin Falls, ID 83301
PH 1 PART A ROOF PLAN

Laughlin Ricks Architecture
 architecture/planning
 134 3RD Ave East, * Twin Falls, Idaho 83301
 (208) 736-8050


DATE:	7.15.24
KM	RCR
Drawn	Checked
#23029	
PROJECT #	

A1A-4.0


ROOF TYPE 1
 60 MIL TPO ROOF MEMBRANE MECHANICALLY FASTENED
 COVERBOARD
 R-32 INSULATION
 5/8 BARRIER BOARD
 ROOF DECK
 STRUCTURE
 SPRAY APPLIED FIREPROOFING
 (1) HOUR RATED, CLASS "B"
 ROOF SYSTEM REQUIRED




① PH 1 PART A ROOF PLAN
 1/8" = 1'-0"




1 PH 1 PART A SECTION 1
1/4" = 1'-0"




2 PH 1 PART A SECTION 2
1/4" = 1'-0"




3 PH 1 PART A SECTION 3
1/4" = 1'-0"



① PH 1 PART A SECTION 4
 1/4" = 1'-0"




② PH 1 PART A SECTION 5
 1/4" = 1'-0"



- CEILING KEY**
- ① 2X2 SECURITY CEILING - ARMSTRONG METALWORKS SECURELOCK PRELUDE XL
NOTE COORDINATE ACCESS PANELS WITH ELECTRICAL AND PLUMBING
 - ①S 2X2 SECURITY CEILING - ARMSTRONG METALWORKS SECURELOCK PRELUDE XL
W/ FIBERGLASS INFILL PADS FOR SOUND CONTROL.
NOTE COORDINATE ACCESS PANELS WITH ELECTRICAL AND PLUMBING
 - ② EXISTING METAL CEILING
 - ③ NEW 2X4 ACT CEILING
 - ④ EXISTING 2X4 ACT CEILING
 - ⑤ EXISTING CONCRETE CEILING
 - ⑥ GYP BD. CEILING
 - ⑦ SECURITY GYP BD. CEILING
 - ⑧ TILE
 - ⑨ OPEN TO STRUCTURE W/ SPRAY APPLIED FIREPROOFING

① PH 1 PART A REMODEL RCP
1/8" = 1'-0"




DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
PH 1 PART A REMODEL CEILING PLAN


Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Draw RCR Checked
#23029
PROJECT #


A1A-7.0




1 CORR. 3 W
1/4" = 1'-0"




2 CORR. 3 E
1/4" = 1'-0"




3 CORR. 4 S.
1/4" = 1'-0"




4 CONTROL N
1/4" = 1'-0"




5 CONTROL E
1/4" = 1'-0"




6 CONTROL S.
1/4" = 1'-0"



7 CONTROL W
1/4" = 1'-0"



8 CORR. 7 W
1/4" = 1'-0"



9 CORR. 7 E.
1/4" = 1'-0"

LICENSED ARCHITECT
R. COLBY RICKS
STATE OF IDAHO
7.15.24


DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
INTERIOR ELEVATIONS

Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Draw RCR Checked
#23029
PROJECT #

A1A-8.0



DATE

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2615 Wright Ave., Twin Falls, ID 83301
FINISH SCHEDULE

Laughlin Ricks Architecture
architecture/planning
134 3rd Ave East, Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Draw RCR Checked
#23029
PROJECT #


A1A-9.0

PH 1 PART A - Room Finish Schedule


Table with columns: Number, Name, Base Finish, Floor Finish, Wall (Materials: North, East, South, West), Finishes (North, East, South, West), Ceiling (Material, Finish), Remarks. Rows include LOBBY, CORR. 1, OFFICE, CONFERENCE, CORR. 2, DAY ROOM, SHOWER, CELL, WAITING, ADA RR, COMPRESSOR, LAUNDRY, MED STORAGE, BOOKING, SHOWER, CELL, STORAGE, JANITOR, ATTORNEY, etc.

PH 1 PART A - Door Schedule



DOOR	ROOM	Phase Created	EL	Level	Width	Height	Thickness	DOOR				FRAME		UL RATING	Access Control	Comments	
								Material	Finish	Accessories	Door Latch	Material	Finish				DOOR GLASS
1	LOBBY	Existing	SFGL	Level 1	3'-0"	7'-0"	2"	(E) ALUMINUM STOREFRONT	FF	WEATHER-STRIP/ THRESHOLD / CLOSER / CONTINUOUS HINGES / PANIC HARDWARE	KEYED	(E) ALUMINUM	FF	(E)	--	Yes	INTERCOM AND ELETIC STRIKE CONTROLLED BY CONTROL
2	RR	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	-	PRIVACY	HM	PT	NONE		Yes	ELECTRIC STRIKE AND FOB
3	CORR. 1	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	CLOSER	STOREROOM	HM	PT	3/8" TEMPERED MIN		Yes	
4	OFFICE	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	-	CLASSROOM	(E) HM	PT	NONE			
5	CONFERENCE	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	-	CLASSROOM	(E) HM	PT	(E)			
6	RR	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	-	PRIVACY	HM	PT	NONE			
7	CORR. 2	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	CLOSER, HOLD OPEN	STOREROOM	HM	PT	3/8" TEMPERED MIN			
8	OFFICE	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	-	CLASSROOM	(E) HM	PT	NONE			
9	OFFICE	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	-	CLASSROOM	(E) HM	PT	NONE			
10	ELECT.	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	CLOSER	STOREROOM	(E) HM	PT	NONE			
11	CORR. 3	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	HM	PT	3/8" TEMPERED MIN		Yes	
12	IT	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	CLOSER	STOREROOM	(E) HM	PT	NONE			
14	DAY ROOM	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)	20 MIN	Yes	
15	SHOWER	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
16	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
17	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
18	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
19	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
20	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
21	DAY ROOM	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
22	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
23	DAY ROOM	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	WEATHERSTRIP, THRESHOLD, DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	NONE		Yes	
24	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
25	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
26	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
27	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
28	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
29	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
30	SHOWER	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
31	WAITING	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	HM	PT	3/8" TEMPERED MIN		Yes	
32	CONTROL	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	HM	PT	3/8" TEMPERED MIN		Yes	
33	RR	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	-	PRIVACY	HM	PT	NONE			
34	COMPRESSOR	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	CLOSER	STOREROOM	HM	PT	NONE			
34A	ADA RR	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	-	PRIVACY	HM	PT	NONE			
34B	LAUNDRY	PHASE 1 PART A		Level 1	3'-6"	7'-0"	1 3/4"	HM	PT	HOLD OPEN, SMOKE SEALS, CLOSER	PASSAGE	HM	PT	3/8" TEMPERED MIN			
35	FRR / MECH	Existing		Level 1	3'-8"	7'-0"	1 3/4"	(E) HM	PT	WEATHERSTRIP, THRESHOLD, CLOSER	STOREROOM	(E) HM	PT	NONE			
36	ELECT	Existing		Level 1	3'-8"	7'-0"	1 3/4"	(E) HM	PT	WEATHERSTRIP, THRESHOLD, CLOSER	STOREROOM	(E) HM	PT	NONE		No	
37	WAITING	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	WEATHERSTRIP, THRESHOLD, DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
38	CORR. 4	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	HM	PT	3/8" TEMPERED MIN		Yes	
39	EXAM A	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	-	PASSAGE	HM	PT	NONE			
40	EXAM B	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	-	PASSAGE	HM	PT	NONE			
41	STORAGE	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	CLOSER	STOREROOM	HM	PT	NONE			
42	MECH	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	CLOSER	STOREROOM	(E) HM	PT	NONE	20 MIN	No	
43	CORR. 5	Existing		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)	20 MIN	Yes	
44	MED STORAGE	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	CLOSER	STOREROOM	HM	PT	NONE		No	
45	OFFICE	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	CLOSER	STOREROOM	HM	PT	3/8" TEMPERED MIN		No	
46	CORR. 7	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	HM	PT	3/8" TEMPERED MIN		Yes	
47	BOOKING	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)	20 MIN	Yes	
48	SHOWER	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
49	SHOWER	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
50	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
51	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
52	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
53	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
54	BOOKING	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	HM	PT	3/8" TEMPERED MIN	20 MIN	Yes	
55	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
56	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
57	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
58	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
59	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
60	CELL	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
61	ADA RR	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	PRIVACY	HM	PT	NONE		No	
62	PAT DOWN	PHASE 1 PART A		Level 1	4'-0"	7'-4"	2"	HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	HM	PT	3/8" TEMPERED MIN		Yes	
63	SALLYPORT	PHASE 1 PART A		Level 1	12'-0"	12'-0"	3"	HM	PT	PER MANUFACTURER	PER MANUFACTURER	HM	PT	NONE		Yes	CONTROLLED BY CONTROL SECURITY GARAGE DOOR
63B	SALLYPORT	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	WEATHERSTRIP, THRESHOLD, DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	HM	PT	NONE			
64	PAT DOWN	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	HM	PT	3/8" TEMPERED MIN		Yes	
65	SALLYPORT	PHASE 1 PART A		Level 1	12'-0"	12'-0"	3"	HM	PT	PER MANUFACTURER	PER MANUFACTURER	HM	PT	NONE		Yes	CONTROLLED BY CONTROL SECURITY GARAGE DOOR
66	SALLYPORT	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	WEATHERSTRIP, THRESHOLD, DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	HM	PT	NONE		Yes	
67	ROOFTOP ACCESS	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	CLOSER	STOREROOM	HM	PT	NONE			
68	STORAGE	PHASE 1 PART A		Level 2	3'-0"	7'-0"	1 3/4"	HM	PT	CLOSER	STOREROOM	HM	PT	NONE			
69	STORAGE	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	-	STOREROOM	HM	PT	NONE			
70	STORAGE	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	-	STOREROOM	(E) HM	PT	(E)			
71	CORR. 8	PHASE 1 PART A		Level 1	3'-0"	7'-0"	1 3/4"	HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	HM	PT	3/8" TEMPERED MIN		Yes	
72	STORAGE	PHASE 1 PART A		Level 1	3'-6"	7'-0"	1 3/4"	HM	PT	-	STOREROOM	HM	PT	NONE			
73	CORR. 8	Existing		Level 1	3'-0"	7'-0"	1 3/4"	(E) HM	PT	DOOR POSITION SWITCH, BUTT HINGE & CLOSER	AIRTEQ 9500	(E) HM	PT	(E)		Yes	
74	CORR. 8	Existing		Level 1	3'-0"	7'-0"	1 3/4"										




① ACCESSIBLE PARKING STALLS
 1/8" = 1'-0"




② ACCESSIBLE PARKING SIGNS1
 3/4" = 1'-0"




③ SIGN POST DETAIL
 3/4" = 1'-0"




④ CONCRETE SIDEWALK TO BUILDING WALL DETAIL
 1 1/2" = 1'-0"




⑤ CONCRETE EXPANSION JOINT
 1 1/2" = 1'-0"




⑥ CONCRETE CONTROL JOINT
 1 1/2" = 1'-0"




⑦ PRE-CAST CONC. BUMPER DETAIL
 1/2" = 1'-0"




⑧ NEW CONCRETE TO EXISTING
 1 1/2" = 1'-0"




1 TRASH ENCLOSURE
1/2" = 1'-0"




3 TRASH ENCLOSURE SCREEN DETAIL
1 1/2" = 1'-0"



4 TRASH ENCLOSURE HINGE DETAIL
1 1/2" = 1'-0"



2 TRASH ENCLOSURE SECTION/ELEVATION
1/2" = 1'-0"



5 TRASH ENCLOSURE WALL SECTION
3/4" = 1'-0"

7.15.24

DATE


PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
DETAIL - TRASH ENCLOSURE

Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050


DATE: 7.15.24

KM RCR
Drawn Checked
#23029
PROJECT #


A1A-10.1




① HM DOOR HEAD DETAIL
3" = 1'-0"




④ HM DOOR HEAD DETAIL AT STUCCO
3" = 1'-0"




③ DOOR THRESHOLD DETAIL
1 1/2" = 1'-0"




② HM DOOR JAMB DETAIL
3" = 1'-0"



⑤ HM DOOR JAMB @ CMU
1 1/2" = 1'-0"



⑥ FIRE RATED CONTROL JOINT DETAIL,
TYP. @ EXTERIOR CMU
3" = 1'-0"



⑦ CONTROL JOINT DETAIL
N.T.S.

LICENSED ARCHITECT
R. COLBY RICKS
R. COLBY RICKS ARCHITECTURE/PLANNING
STATE OF IDAHO
7.15.24

DATE: _____



PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
DETAILS - MATERIALS, DOORS, & WINDOWS

Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050


DATE: 7.15.24
KM Drawn RCR Checked
#23029
PROJECT #

A1A-10.2


504.6 VISUAL CONTRAST. THE LEADING 1 TO 2 INCHES OF EVERY TREAD AND LANDING, MEASURED HORIZONTALLY FROM THE LEADING EDGE OF THE NOSING, SHALL CONSIST OF A SOLID SOL OR HAVING VISUAL CONTRAST OF DARK-ON-LIGHT OR LIGHT-ON-DARK FROM THE REMAINDER OF THE TREAD. THE CONTRASTING MARKING SHALL BE DURABLE AND SHALL EXTEND FROM ONE SIDE OF EACH TREAD TO THE OTHER SIDE OF EACH TREAD.




① STAIR CONTRAST
3/4" = 1'-0"



② HANDRAIL TO BUILDING DETAIL
3" = 1'-0"



③ STAIR EXTENSIONS
3/4" = 1'-0"




DATE	

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
DETAILS STAIR


Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, # Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24	
KM Draw	RCR Checked
#23029	PROJECT #


A1A-10.4



① LADDER DETAIL / ROOF HATCH
1" = 1'-0"



② ROOF ACCESS LADDER
1" = 1'-0"




DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
DETAILS MISC


Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Draw RCR Checked
#23029
PROJECT #


A1A-10.5




NOTE:
 1. HANGERS SHALL BE SADDLE-TIED AROUND MAIN RUNNERS.
 2. LOWER ENDS OF FLAT HANGERS SHALL BE BOLTED WITH 3/8\"/>



NOTE:
 AREAS SMALLER THAN 144 SQ. FT. AND WITH WALLS ON FOUR SIDES EXTENDING TO THE STRUCTURE NEED NOT BE BRACED. NOTE: BOUNDARY WALLS MUST BE BRACED TOP AND BOTTOM INDEPENDENT OF CEILING TO QUALIFY.




STRUT SIZE	MAXIMUM LENGTH
3/4\"/>	
1\"/>	
SINGLE 2 1/2\"/>	
BACK TO BACK 2 1/2\"/>	




1 CEILING DETAILS
 1\"/>

2 CEILING GRID DETAILS
 3\"/>



A. REFER TO MECHANICAL AND ELECTRICAL

3 SECURITY GYP BD CEILING
 3\"/>




DATE _____

PHASE 1 PART A FOR:
 TWIN FALLS COUNTY - WRIGHT AVE JAIL
 2815 Wright Ave, Twin Falls, ID 83301
 DETAILS CEILING


Laughlin Ricks Architecture
 architecture/planning
 134 3RD Ave East, * Twin Falls, Idaho 83301
 (208) 736-8050

DATE: 7.15.24
 KM Drawn RCR Checked
 #23029
 PROJECT #


A1A-10.6




1 SCUPPER W/ CONDUCTOR HEAD
3" = 1'-0"




2 SCUPPER ISO DETAIL
1 1/2" = 1'-0"




3 OVERFLOW SCUPPER
3" = 1'-0"




4 PARAPET WALL FLASHING
3" = 1'-0"




5 HIGH PARAPET WALL FLASHING
3" = 1'-0"




6 COUNTER FLASHING DETAIL
3" = 1'-0"



7 TYP. EQUIPMENT & VENT CURB
1 1/2" = 1'-0"




8 PREFABRICATED VENT PIPE FLASHING
3" = 1'-0"



9 COUNTERFLASHING DETAIL 1
3" = 1'-0"

NOTE:
1. DO NOT CUT PREFABRICATED BOOT. IT MUST BE PULLED OVER VENT PIPE.
2. PREFABRICATED BOOTS ARE AVAILABLE IN SMALL & LARGE SIZES, AND MUST BE USED WHENEVER POSSIBLE TO FLASH PIPES 1" TO 8" IN DIAMETER.




PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave., Twin Falls, ID 83301
DETAILS ROOF


Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, * Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Drawn RCR Checked
#23029 PROJECT #


A1A-10.7



① COATED METAL ROOF EDGE
3" = 1'-0"



② COVER TAPE AT GUTTER EDGE DETAIL
3" = 1'-0"




DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
ROOF DETAILS


Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, # Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24	
KM Draw	RCR Checked
#23029	PROJECT #


A1A-10.8




1 TYP. ATTORNEY CLIENT WINDOW (NON-ADA)
1" = 1'-0"




2 ADA ATTORNEY CLIENT WINDOW
1" = 1'-0"




3 STAINLESS STEEL SHELF SECTION
6" = 1'-0"




4 UPPER CASEWORK DETAIL 1
1" = 1'-0"




5 STAINLESS STEEL SHELF PLAN
1" = 1'-0"




6 CONTROL CASEWORK 1
1" = 1'-0"




7 CONTROL CASEWORK 1 DRAWER
1" = 1'-0"



8 CONTROL CASEWORK 3
1" = 1'-0"



9 CONTROL CASEWORK 3 DRAWER
1" = 1'-0"




PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
DETAILS CASEWORK

Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, # Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.24
KM Draw RCR Checked
#23029
PROJECT #


A1A-10.9



- KEYNOTES:**
1. SLOPED STUD WALL, NO BRIDGING ATTACHMENT
 2. STEEL DECK
 3. HORIZONTAL AND DIAGONAL BRIDGING IN LAST (B) BAYS ADJACENT TO STEEL STUD WALL
 4. BRIDGING PER MANUFACTURERS RECOMMENDATION
 5. STEEL JOIST


HORIZONTAL OR CROSS BRIDGING

T12 TYPICAL JOIST BRIDGING ADJACENT TO STEEL STUDWALL
SCALE: NTS



- KEYNOTES:**
1. STEEL DECK
 2. L4x4x1/4 x 12' LONG STEEL ANGLES AT 36" O.C. EACH SIDE OF MASONRY WALL
 3. MASONRY WALL
 4. STEEL JOIST


T8 TYPICAL INTERIOR MASONRY WALL PARALLEL W/ JOISTS (NON-BEARING)
SCALE: NTS



- KEYNOTES:**
1. SLOPED FINISH GRADE
 2. MINIMUM FOOTING DEPTH PER GSN (12" MINIMUM)
 3. DEEPEN FOOTING AS REQUIRED TO ACCOUNT FOR SLOPED GRADE
 4. CONCRETE FOOTING

NOTES:
A. FOR ADDITIONAL INFORMATION, SEE PLANS AND DETAILS


T4 TYPICAL DETAIL FOR FOUNDATION EMBEDMENT
SCALE: NTS



- KEYNOTES:**
1. FINISHED GRADE WHERE OCCURS
 2. DO NOT EXCAVATE A TRENCH CLOSER THAN 45° ANGLE TO BELOW BOTTOM FOOTING OR FOUNDATION
 3. BOTTOM OF CONCRETE FOOTING
 4. BOTTOM OF TRENCH

NOTES:
A. DO NOT UNDERCUT EXISTING FOOTINGS
B. NO PIPE OR OTHER UTILITIES SHALL PASS THRU WALL FOOTINGS OR UNDER COLUMN FOOTINGS


T1 TRENCH PARALLEL TO CONTINUOUS STRIP FOOTING
SCALE: NTS



- KEYNOTES:**
1. MASONRY WALL
 2. CONTROL JOINT
 3. CONTROL JOINT MATERIAL PER ARCHITECTURAL DRAWINGS AND SPECIFICATIONS
 4. A(1) VERTICAL BAR EACH SIDE IN SOLID GROUTED CELLS TO MATCH VERTICAL WALL REINFORCING
 5. #3 x 35' LONG (18" EACH LEG) HAIRPIN AT HORIZONTAL BAR SPACING
 6. TYPICAL HORIZONTAL BAR
 7. EXTERIOR GRADE SEALANT OVER BACKER ROD


NOTES:
A. BOND BEAM BARS AT FLOOR AND ROOF LINES SHALL RUN CONTINUOUS THROUGH CONTROL JOINT

T13 CONTROL JOINT IN MASONRY WALL
SCALE: NTS



- KEYNOTES:**
1. LAP - SEE GSN FOR MASONRY AND TYPICAL DETAIL FOR CONCRETE REQUIREMENTS
 2. MAXIMUM 1/5 LAP BUT NOT MORE THAN 6"
 3. WIRE TIES
 4. 1d (1" MINIMUM)
 5. RADIUS - 3d FOR BARS NOT OVER #6; 4d FOR #8, #10, AND #11 BARS; 5d FOR #14 AND #18 BARS; 5d FOR ALL GRADE 40 BARS WITH 180° HOOK
 6. 4D (4" MINIMUM)
 7. 12d (96" HOOK)
 8. 5d (4" MINIMUM)
 9. 135° BEND
 10. BEND AROUND 1 1/2" PIN FOR #3 BARS; BEND AROUND 2" PIN FOR #4 BARS; BEND AROUND 1 1/2" PIN FOR #5 BARS


T9 TYPICAL REINFORCING DETAIL
SCALE: NTS



- KEYNOTES:**
1. WALL AS OCCURS, SEE PLAN
 2. SIDEWALK, PAVEMENT, OR FINISH GRADE PER ARCH
 3. SLEEVE, # DIA MAX. PROVIDE 1/2" MINIMUM CLEARANCE AROUND PIPE/CONDUIT
 4. CONCRETE WALL, SEE PLAN
 5. CONCRETE FOOTING, SEE PLAN
 6. COMPACTED SUB-GRADE BELOW FOOTING, SEE PLAN
 7. PIPE OR CONDUIT

NOTES:
A. XNO PIPE SHALL PASS THROUGH FOOTINGS OR UNDER COLUMN FOOTINGS. FOR ADDITIONAL INFORMATION SEE PLANS AND DETAILS
B. MULTIPLE PIPES/CONDUIT SLEEVES ALLOWED PROVIDED SLEEVES ARE SPACED W/ MINIMUM OF 2x SLEEVE DIAMETER BETWEEN SLEEVES
C. SLEEVES SHALL NOT OCCUR WITHIN 12" OF POINT LOADS OR HOLD-DOWN ANCHORS


T5 TYPICAL PIPE THROUGH STEM WALL
SCALE: NTS



- KEYNOTES:**
1. CONCRETE FOOTING
 2. SLEEVE - PROVIDE 1/2" MINIMUM CLEARANCE AROUND PIPE OR CONDUIT
 3. PIPE OR CONDUIT
 4. CONCRETE FILL TO BE PLACED BEFORE FOOTING IS POURED - FORM SAME AS FOOTING AND POUR FULL WIDTH OF PIPE TRENCH
 5. STEM WALL

NOTES:
A. NO PIPE SHALL PASS THRU FOOTING OR UNDER COLUMN FOOTINGS. FOR TRENCHES GREATER THAN 3'-6" BELOW BOTTOM OF FOOTING, SEE PIPE PASSING BELOW WALL FOOTING DETAIL.

T2 PIPE PASSING UNDER WALL FOOTING IN SHALLOW TRENCH
SCALE: NTS




- KEYNOTES:**
1. MASONRY WALL
 2. BOND BEAM REINFORCING
 3. CORNER BARS SAME SIZE AND SPACING AS HORIZONTAL REINFORCING - MINIMUM LAP PER GSN
 4. END #4 x 36" LONG (18" EACH LEG) HAIRPIN AT SAME SPACING AS HORIZONTAL REINFORCING

T14 PLAN - CORNER AND END REINFORCING IN MASONRY WALLS
SCALE: NTS

T9 TYPICAL REINFORCING DETAIL
SCALE: NTS


BAR SIZE	CLASS B TENSION SPLICE LENGTHS					
	f _c = 3,000 PSI		f _c = 4,000 PSI		f _c = 5,000 PSI	
	HORIZONTAL BARS W/ > 12" OF CONC. BELOW	VERTICAL AND BOTTOM HORIZONTAL BARS	HORIZONTAL BARS W/ > 12" OF CONC. BELOW	VERTICAL AND BOTTOM HORIZONTAL BARS	HORIZONTAL BARS W/ > 12" OF CONC. BELOW	VERTICAL AND BOTTOM HORIZONTAL BARS
#3	12"	12"	12"	12"	12"	12"
#4	19"	15"	17"	13"	15"	12"
#5	29"	23"	26"	20"	23"	18"
#6	32"	25"	28"	21"	25"	19"
#7	54"	41"	47"	36"	42"	32"
#8	70"	54"	61"	47"	54"	42"
#9	89"	68"	77"	59"	69"	53"
#10	112"	87"	97"	75"	87"	67"

NOTES:
1. TOP BARS ARE ANY HORIZONTAL BARS PLACED SO THAT MORE THAN 12" OF FRESH CONCRETE IS CAST IN THE MEMBER BELOW THE REINFORCEMENT.
2. UNLESS NOTED OTHERWISE, LAP SPLICES IN CONCRETE BEAMS, SLABS AND WALLS SHALL BE CLASS "B" TENSION LAP SPLICES.



- KEYNOTES:**
1. CORNER DOWELS TO MATCH HORIZONTAL REINFORCEMENT
 2. CONCRETE WALL WITH REINFORCEMENT
 3. LAP SPLICE PER TYPICAL STEEL REINFORCING LAP SPLICES IN CONCRETE DETAIL


T6 TYPICAL CONCRETE CORNER
SCALE: NTS



- KEYNOTES:**
1. STEM WALL
 2. CONCRETE FOOTING
 3. 1'-6" MAXIMUM (WHERE TRENCH EXCEEDS 1'-6" NOTIFY STRUCTURAL ENGINEER PRIOR TO PLACEMENT OF FOOTINGS)
 4. BACKFILL AND RECOMPACT TRENCH PER SOILS REPORT AND SPECIFICATIONS
 5. BOTTOM OF TRENCH


NOTES:
A. DO NOT UNDERCUT EXISTING FOOTINGS
B. NO PIPES OR OTHER UTILITIES SHALL PASS THRU WALL FOOTINGS OR UNDER COLUMN FOOTINGS

T3 PIPE PASSING BELOW FOOTING IN DEEP TRENCH
SCALE: NTS




- KEYNOTES:**
1. MASONRY WALL
 2. 1/2" DIA x 8" LONG SMOOTH DOWEL AT 48" O.C.
 3. 1/2" VERTICAL BAR AT GROUTED CELLS AT END AND AT INTERSECTION OF WALLS
 4. MASONRY PARTITION WALL (NON-BEARING) WHICH ABUTS CONTINUOUS MASONRY WALL AND IS NOT TOOTHED INTO IT

T15 PLAN - MASONRY PARTITION WALL AT MASONRY WALL
SCALE: NTS



- KEYNOTES:**
1. STEEL BEAM
 2. BRIDGING PER MANUFACTURERS RECOMMENDATIONS
 3. STEEL JOIST


T11 TYPICAL JOIST BRIDGING DETAIL AT STEEL BEAM
SCALE: NTS



- KEYNOTES:**
1. CONCRETE SLAB ON GRADE
 2. CONTINUOUS KEVED JOINT
 3. SAWCUT 1/8" WIDE x 1/4 SLAB THICKNESS IN DEPTH - CUT SHALL BE MADE SOON ENOUGH TO PREVENT SHRINKAGE CRACKING, BUT NOT SO SOON AS TO CAUSE SPALLING OF THE CONCRETE WHILE SAWING. WORK MUST BE COMPLETE WITHIN 16 HOURS OF CONCRETE PLACEMENT.

NOTES:
A. KEVED JOINTS NEED ONLY OCCUR AT EXPOSED EDGES DURING PLACEMENT UNLESS SPECIFICALLY NOTED ON THE PLANS
B. "TOOL WET JOINT" - "ZIP STRIP" - ETC SHALL MATCH SAWCUT REQUIREMENTS

T7 CONTROL JOINTS IN CONCRETE SLAB ON GRADE
SCALE: NTS



PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
TYPICAL DETAILS

Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.2024
PERMIT SET: KBB
Checked: #23029
PROJECT #


S1.2

Ridge Structural Engineering
1152 Bond Avenue, Suite B Rexburg, ID 83440
phone: 208.569.5694
contact@ridgestructural.com

DATE: 7.15.2024
PERMIT SET: KBB
Checked: #23029
PROJECT #


JOB NO.: 24.145 PROJECT MANAGER: JJ CAD OPERATOR: GTC

This drawing is the property of Ridge Structural Engineering, Inc. Legally, this drawing can NOT be copied in whole or in part. It is only to be used for the project and site specifically identified herein and is to be used for any other project. Construction shall conform to all applicable codes, standards, and specifications. The contractor assumes full liability for deviations from the plans of these items.




T24 PLAN - TYPICAL OPENING IN ROOF FRAMING
SCALE: NTS

- KEYNOTES:**
1. SURCHARGE OR DRIFT SNOW LOAD AREA, SEE PLAN
 2. BALANCED ROOF SNOW LOAD, SEE GSN
 3. REQUIRED LOAD INCREASE, SEE PLAN
 4. EXTENT OF SURCHARGE OR DRIFT LOAD, SEE PLAN




T25 TYPICAL ROOF SNOW SURCHARGE / DRIFT LOAD
SCALE: NTS

- KEYNOTES:**
1. EXISTING ROOF FRAMING
 2. 2x6 KICKER SPACED AT 6'-0" O.C. (MAX) W/ (4) 16d NAILS INTO BLOCK AND (1) A35 CLIP AT PT PLATE
 3. CONTINUOUS 2x PT PLATE W/ 5/8" DIA ANCHOR BOLTS AT 32" O.C. W/ 5" MINIMUM EMBEDMENT
 4. MASONRY WALL
 5. 2x6 BLOCK AT EACH KICKER, ATTACH TO UNDERSIDE OF EXISTING ROOF SHEATHING W/ (1) A35 CLIP, CLIP INSTALLED USING 1/2" LONG SCREWS
 6. 2x6 KICKER SPACED AT 6'-0" O.C. (MAX) W/ (4) 16d NAILS INTO EXISTING JOISTS AND (1) A35 CLIP AT PT PLATE




T26 TYPICAL INTERIOR MASONRY WALL (NON-BEARING)
SCALE: NTS



T19 TYPICAL MASONRY WALL REINFORCING AROUND OPENINGS - ELEVATION
SCALE: NTS


- KEYNOTES:**
1. STEEL DECK
 2. ANGLE SUPPORT L2x2x1/8 BELOW DECK, ANGLE MAY BE PLACED ON TOP OF DECK W/ PRIOR APPROVAL OF ARCHITECT
 3. WELD 2" AT EACH RIB, TYPICAL



- NOTES:**
- AN OPENING WHICH CUTS ONE WEB (4" MAX DIMENSION PERPENDICULAR TO RIBS), MAY BE CUT IN DECK WITHOUT AND SPECIAL REINFORCING
 - AN OPENING WHICH CUTS TWO WEBS (8" MAX DIMENSION PERPENDICULAR TO RIBS), WILL REQUIRE ANGLE SUPPORT SHOWN ABOVE
 - ANY OPENING WHICH CUTS MORE THAN TWO WEBS, FRAME OPENING W/ TYPICAL ANGLE SUPPORT FRAME, SEE TYPICAL OPENING IN STEEL DECK DETAIL

T22 TYPICAL SMALL OPENING IN STEEL DECK
SCALE: NTS

- KEYNOTES:**
1. PIPE SLEEVE
 2. 18 GA PLATE W/ #10 SHEET METAL SCREWS AT 6" O.C. EACH WAY
 3. METAL ROOF DECK




T23 TYPICAL PIPE SLEEVE THROUGH ROOF DECK
SCALE: NTS

- KEYNOTES:**
1. 8" DEEP BOND BEAM W/ (1) #5 CONTINUOUS AT TOP OF PARAPET
 2. ROOF LINE
 3. 16" DEEP BOND BEAM W/ (2) #5 CONTINUOUS AT ROOF AND FLOOR LINES
 4. PROVIDE 90° STANDARD HOOK WHERE LINTEL REINFORCING EXTENDS LESS THAN 24" BEYOND OPENING
 5. TYPICAL CORNER OR JAMB VERTICAL BARS
 6. PROVIDE (1) #5 HORIZONTAL BAR BELOW OPENINGS
 7. TYPICAL WALL REINFORCING, SEE PLAN
 8. FOUNDATION VERTICAL DOWEL, MATCH ALL VERTICAL WALL REINFORCING
 9. LINTEL REINFORCING, SEE PLAN
 10. FULL HEIGHT VERTICAL JAMB REINFORCING, SEE PLAN
 11. SEE TYPICAL MASONRY LINTEL DETAIL
 12. SEE TYPICAL MASONRY JAMB DETAIL

- NOTES:**
- GROUT ALL CELLS CONTAINING REINFORCING, SEE PLAN FOR LOCATION OF WALLS REQUIRING FULL GROUTING
 - SPECIAL INSPECTION REQUIRED, SEE GSN
 - SEE PLAN AND CORRESPONDING DETAILS FOR LINTEL AND JAMB REINFORCING REQUIREMENTS


T20 TYPICAL STEEL JOIST ATTACHMENT
SCALE: NTS

- KEYNOTES:**
1. STEEL DECK
 2. BOUNDARY ATTACHMENT
 3. L4x4x1/4 STEEL ANGLES BETWEEN JOISTS EACH SIDE OF MASONRY WALL
 4. MASONRY WALL
 5. STEEL JOIST




T21 TYPICAL INTERIOR MASONRY WALL PERPENDICULAR W/ JOISTS (NON-BEARING)
SCALE: NTS

- NOTES:**
- ALL OTHER FRAMING NOT SHOWN FOR CLARITY



T16 TYPICAL MASONRY LINTEL
SCALE: NTS


- KEYNOTES:**
1. VERTICAL BAR
 2. #3 x 36" LONG (18" EACH LEG) HAIRPIN AT HORIZONTAL BAR SPACING
 3. TYPICAL HORIZONTAL BAR
 4. JAMB LENGTH PER PLAN, SOLID GROUT
 5. (2) #4 HORIZONTAL BARS AT 48" O.C. W/ HOOKS EACH END



- NOTES:**
- PROVIDE FOUNDATION VERTICAL DOWEL TO MATCH AND LAP W/ VERTICAL JAMB REINFORCING


T17 PLAN - TYPICAL MASONRY JAMB
SCALE: NTS

- KEYNOTES:**
1. MASONRY WALL
 2. ANCHOR INSTALLATION NOT ALLOWED IN HATCHED AREAS, TYPICAL




T18 POST-INSTALLED ANCHORS IN MASONRY WALLS
SCALE: NTS

- KEYNOTES:**
1. STEEL DECK
 2. BOUNDARY ATTACHMENT
 3. L4x4x1/4 STEEL ANGLES BETWEEN JOISTS EACH SIDE OF MASONRY WALL
 4. MASONRY WALL
 5. STEEL JOIST



- NOTES:**
- ALL OTHER FRAMING NOT SHOWN FOR CLARITY



PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
TYPICAL DETAILS



Laughlin Ricks Architecture
architecture/planning
134 3rd Ave East, Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.2024
PERMIT SET: KBB
PROJECT #

Ridge Structural Engineering
1152 Bond Avenue, Suite B
Rexburg, ID 83440
phone: 208.569.5694
contact@ridgestructural.com

S1.3

- KEYNOTES:
1. COMPACTED SUB-GRADE BELOW FOOTING. SEE PLAN.
 2. 8" THICK CONCRETE WALL W/ #4 AT 18" O.C. VERTICAL AND #4 AT 12" O.C. HORIZONTAL.
 3. SIDEWALK PAVEMENT, OR FINISH GRADE PER CIVIL.
 4. MINIMUM FOOTING DEPTH: 24"
 5. 36" WIDE x 12" THICK FOOTING W/ (5) #4 CONT AND #4 AT 18" O.C. TRANSVERSE, TOP AND BOTTOM.
 6. HOOKED DOWEL TO MATCH WALL VERTICAL REINFORCING.
 7. 2" DIA WEEP HOLES AT 6'-0" O.C. MAX SPACING.



T27 TYPICAL SITE RETAINING WALL 4'-0"
SCALE: NTS

DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
TYPICAL DETAILS

Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, # Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.2024
PERMIT SET: KBB
Checked: #23029
PROJECT #

S1.4

This drawing is the property of Ridge Structural Engineering, Inc. Legally, this drawing can NOT be copied in whole or in part. It is only to be used for the project and site specifically described herein and is not to be used on any other project. Contractor shall verify all dimensions, details, and conditions and report at once any error, inconsistency or omission discovered before construction. The contractor assumes full liability for deviations from the intent of these plans.

JOB NO.: 24.145	PROJECT MANAGER: JJ	CAD OPERATOR: GTC
Ridge Structural Engineering		
1152 Bond Avenue, Suite B Rexburg, ID 83440	phone: 208.569.5694	contact@ridgestructural.com



WALL (W) SCHEDULE					
TYPE	MATERIAL	THICKNESS	VERTICAL REINFORCING	HORIZONTAL REINFORCING	REMARKS
W1	CONCRETE	8"	#4 AT 18" O.C.	#4 AT 12" O.C.	---
W2	MASONRY	8"	#5 AT 32" O.C.	(2) #4 AT 48" O.C.	SOLID GROUTED
W3	MASONRY	6"	#5 AT 32" O.C.	#5 AT 48" O.C.	SOLID GROUTED

FOOTING SCHEDULE					
MARK	LENGTH	WIDTH	THICKNESS	REINFORCING	REMARKS
F36	36"	36"	10"	(4) #4 EACH WAY BOTTOM	---
F42	42"	42"	10"	(5) #4 EACH WAY BOTTOM	---
F48	48"	48"	10"	(4) #4 EACH WAY BOTTOM	---
WF24	CONT	24"	12"	(2) #4 CONT BOTTOM	STRIP FOOTING

MASONRY JAMB (MJ) SCHEDULE					
SEE TYPICAL JAMB DETAIL FOR ADDITIONAL INFORMATION					
MARK	REBAR AND QUANTITIES	TYPE	LENGTH	REMARKS	
MJ1	(2) #5	A	16"	REBAR CENTERED	
MJ2	(8) #5	C	24"	REBAR EACH FACE	
MJ3	(4) #5	B	16"	REBAR EACH FACE	

- FOUNDATION PLAN NOTES**
- VERIFY ALL DIMENSIONS WITH ALL ARCHITECTURAL DRAWINGS.
 - ALL SCHEDULED MARK DESIGNATIONS MAY NOT NECESSARILY BE FOUND ON THIS PLAN. SCHEDULES ARE TYPICAL TO THIS PROJECT.
 - THE DEPTH OF FOOTING DIMENSION INDICATED IN THE G.S.N. IS A MINIMUM. FOUNDATION CONTRACTOR SHALL COORDINATE WITH THE SOILS REPORT AND OTHER TRADES TO INSURE THAT THESE MINIMUMS ARE SUFFICIENT FOR THE WORK. SEE TYPICAL DETAILS FOR ADDITIONAL REQUIREMENTS.
 - W1, W2, ETC. - AS SHOWN ON PLAN INDICATES CONCRETE OR MASONRY WALLS. SEE WALL SCHEDULE FOR ADDITIONAL INFORMATION.
 - WF18, WF24, ETC. - AS SHOWN ON PLAN INDICATES A CONTINUOUS WALL FOOTING. SEE FOOTING SCHEDULE FOR ADDITIONAL INFORMATION.
 - F36, F48, ETC. - AS SHOWN ON PLAN INDICATES A CONCRETE FOOTING. SEE FOOTING SCHEDULE FOR ADDITIONAL INFORMATION.
 - MJ1, MJ2, ETC. - AS SHOWN ON PLAN INDICATES A MASONRY JAMB. SEE JAMB SCHEDULE FOR ADDITIONAL INFORMATION.
 - FOR SIDEWALK AND LANDING LOCATIONS, SEE ARCHITECTURAL DRAWINGS.
 - TYPICAL TOP OF CONCRETE WALL = 100'-0"
 - TYPICAL TOP OF EXTERIOR FOOTING = 98'-0"
 - TYPICAL TOP OF INTERIOR FOOTING = 99'-4"


- KEYNOTES**
- DRILL AND EPOXY REBAR INTO EXISTING FOUNDATION W/ 4" MINIMUM EMBEDMENT
 - CONTRACTOR TO VERIFY MINIMUM EXISTING FOOTING SIZE OF 24" WIDE. CONTACT STRUCTURAL ENGINEER IF FOOTING IS SMALLER



CONCRETE SLAB ON GRADE
4" CONCRETE SLAB ON GRADE W/ #3 AT 18" O.C. EACH WAY CENTERED IN SLAB THICKNESS OVER COMPACTED FILL. (SEE GSN)
PROVIDE SLAB JOINTS PER TYPICAL DETAIL WITHIN 16 HOURS OF BATCH TIME
FINISHED FLOOR = 100'-0"

CONCRETE SLAB ON GRADE
5" CONCRETE SLAB ON GRADE W/ #4 AT 24" O.C. EACH WAY CENTERED IN SLAB THICKNESS OVER COMPACTED FILL. (SEE GSN)
PROVIDE SLAB JOINTS PER TYPICAL DETAIL WITHIN 16 HOURS OF BATCH TIME
SLOPE PER ARCH DRAWINGS

PHASE 1 FOUNDATION PLAN
SCALE: 1/8" = 1'-0"



This drawing is the property of Ridge Structural Engineering, Inc. Legally, this drawing can NOT be copied in whole or in part. It is only to be used for the project and site specifically identified herein and is to be used for any other project. Contractor shall verify all dimensions, details, and conditions and report at once any error, inconsistency or omission discovered before construction. The contractor assumes full liability for deviations from the plan of these plans.

JOB NO.: 24-145 PROJECT MANAGER: JJ CAD OPERATOR: GTC


Ridge Structural Engineering
1152 Bond Avenue, Suite B phone: 208.569.5694
Rexburg, ID 83440 contact@ridgestructural.com

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
FOUNDATION PLAN

Laughlin Ricks Architecture
architecture/planning
134, 3rd Ave East, # Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.2024
PERMIT SET: KBB
Checked: #23029
PROJECT #

S2.0



WALL (W) SCHEDULE					
TYPE	MATERIAL	THICKNESS	VERTICAL REINFORCING	HORIZONTAL REINFORCING	REMARKS
W1	CONCRETE	8"	#4 AT 18" O.C.	#4 AT 12" O.C.	
W2	MASONRY	8"	#5 AT 32" O.C.	(2) #4 AT 48" O.C.	SOLID GROUTED
W3	MASONRY	6"	#5 AT 32" O.C.	#5 AT 48" O.C.	SOLID GROUTED

STEEL JOIST (SJ) SCHEDULE			
MARK	STEEL JOIST	JOIST SPACING (O.C.)	
SJ1	18K 270/150	6'-0"	
SJ2	30K 270/150	6'-0"	
SJ3	18K 270/150	6'-0"	

- ROOF FRAMING PLAN NOTES**
- VERIFY ALL DIMENSIONS WITH ALL ARCHITECTURAL DRAWINGS.
 - ALL SCHEDULED MARK DESIGNATIONS MAY NOT NECESSARILY BE FOUND ON THIS PLAN. SCHEDULES ARE TYPICAL TO THIS PROJECT.
 - B1, B2, ETC. - AS SHOWN ON PLAN INDICATES A BEAM OR HEADER. SEE BEAM SCHEDULE FOR ADDITIONAL INFORMATION.
 - P1, P2, ETC. AS SHOWN ON PLAN INDICATES A WOOD POST. SEE POST SCHEDULE FOR MORE INFORMATION.
 - W1, W2, ETC. - AS SHOWN ON PLAN INDICATES CONCRETE OR MASONRY WALLS. SEE WALL SCHEDULE FOR ADDITIONAL INFORMATION.
 - ML1, ML2, ETC. - AS SHOWN ON PLAN INDICATES A MASONRY LINTEL. SEE LINTEL SCHEDULE FOR ADDITIONAL INFORMATION.
 - MJ1, MJ2, ETC. - AS SHOWN ON PLAN INDICATES A MASONRY JAMB. SEE JAMB SCHEDULE FOR MORE INFORMATION.
 - SJ1, SJ2, ETC. - AS SHOWN ON PLAN INDICATES A STEEL JOIST. SEE STEEL JOIST SCHEDULE FOR ADDITIONAL INFORMATION.
 - CJ AS SHOWN ON PLAN INDICATES A CONTROL JOINT IN A CONCRETE OR MASONRY WALL. SEE GSN AND TYPICAL DETAIL. JOINTS MAY BE SHOWN, BUT NOT NOTED ON THIS PLAN. SEE FOUNDATION PLAN FOR NOTED LOCATIONS.
 - FOR CLARITY, DETAILS MAY SHOW ONLY ONE SIDE OF FRAMING CONDITION.
 - FOR CLARITY, ALL ROOF OPENINGS MAY NOT BE SHOWN ON THE ROOF FRAMING PLAN. FOR EXACT SIZE, NUMBER AND LOCATION OF OPENINGS, SEE ARCHITECTURAL, MECHANICAL, PLUMBING, AND ELECTRICAL DRAWINGS. FOR FRAMING AT OPENINGS, SEE TYPICAL DETAILS.
 - VERIFY EXACT SIZE AND WEIGHT OF EQUIPMENT ON ROOF WITH MECHANICAL DRAWINGS.
 - ALL "C" TYPE JOISTS SHALL HAVE A SHOE DEPTH OF 2 1/2". THE JOIST MANUFACTURER SHALL DESIGN ALL JOISTS AND THE SHOES FOR AN AXIAL TENSION (T) OR COMPRESSION (C) LOAD OF 1500# (ASD) DUE TO OUT-OF-PLANE LOADS, UNLESS LARGER LOAD IS INDICATED ON PLANS.
 - THE JOIST MANUFACTURER SHALL DESIGN ALL JOISTS AND SUPPLY ADDITIONAL BRIDGING AS REQUIRED FOR THE NET UPLIFT WIND LOAD USING THE FOLLOWING UNFACTORED LOADS: DL = 20 PSF; WIND (s = 5.6 FT); ZONE 1 = 29.5 PSF, ZONE 2 = 39.3 PSF, ZONE 3 = 39.3 PSF
 - RME: INDICATES HVAC EQUIPMENT ON ROOF. SEE TYPICAL DETAILS FOR FRAMING INFORMATION.


- KEYNOTES**
- NEW OPENING IN EXISTING WALL
 - BRACE TOPS OF NON-BEARING MASONRY WALL PER TYPICAL DETAIL (TYPICAL)
 - MASONRY INFILL IN EXISTING OPENING. WALL REINFORCING TO BE #4 AT 32" O.C. VERTICAL AND #4 AT 48" O.C. HORIZONTAL. EPOXY NEW REBAR INTO EXISTING WALLS W/ 4" EMBEDMENT. SOLID GROUT WALL
 - DRILL AND EPOXY NEW WALL HORIZONTAL REINFORCEMENT INTO EXISTING W/ 5" EMBEDMENT
 - ATTACH BEAM TO BEAM W/ HUS.25/12 FACE-MOUNT HANGER
 - BEAMS ATTACH TO POST W/ SIMPSON PC4Z/EPC4Z POST CAP. ATTACH POST TO WALL BELOW W/ ABU44Z POST BASE INSTALLED W/ (1) 5/8" DIA. x 5" SCREW ANCHOR.
 - ATTACH BEAM TO WALL W/ HUS.25/12 HANGER INSTALLED USING (2) 1/4" DIA. x 2 3/4" TITEN TURBO SCREWS
 - BEAMS ATTACH TO POST W/ SIMPSON PC6Z POST CAP. ATTACH POST TO WALL BELOW W/ ABU66Z POST BASE INSTALLED W/ (1) 5/8" DIA. x 5" SCREW ANCHOR.
 - BEAM ATTACHED TO WALL W/ HUS.25/12 HANGER ATTACHED TO WALL W/ (8) 5/8" DIA. x 5" TITEN HD ANCHORS.
 - BEAMS ATTACH TO POST W/ SIMPSON EPC6Z POST CAP. ATTACH POST TO WALL BELOW W/ ABU66Z POST BASE INSTALLED W/ (1) 5/8" DIA. x 5" SCREW ANCHOR.
 - HANG EXISTING BEAM FROM NEW BEAM W/ MGU.5/SDS FACE-MOUNT HANGER
 - ATTACH BEAM TO TOP OF EXISTING WALL W/ SIMPSON ABU88Z POST BASE INSTALLED USING (2) 5/8" DIA. x 5" SCREW ANCHORS
 - JOIST MANUFACTURER TO DESIGN JOISTS FOR DRIFTING SNOW LOAD FOR LENGTH AND MAGNITUDE SHOWN. SEE TYPICAL DETAIL
 - NEW ROOF ACCESS HATCH - SEE ARCH
 - BLOCKOUT AT TOP OF NEW MASONRY WALL FOR DUCT PASSAGE. COORDINATE REQUIRED SIZE W/ MECHANICAL DRAWINGS
 - PROVIDE ANGLE FRAME BELOW RTU. SEE TYPICAL DETAIL. EXACT LOCATION OF UNIT TO BE COORDINATED BY CONTRACTOR

POST (P) SCHEDULE			
MARK	SIZE	SPECIES AND GRADE	CONNECTION
P1	6x6	DOUG FIR NO. 2	SEE KEYNOTES
P2	4x4	DOUG FIR NO. 2	SEE KEYNOTES


BEAM (B) SCHEDULE	
MARK	SIZE
B1	3 1/8x12 GLB
B2	5 1/8x16 1/2 GLB
B3	6 3/4x16 1/2 GLB

MASONRY LINTEL (ML) SCHEDULE			
MARK	SIZE	LONGITUDINAL REINFORCING	VERTICAL TIES
ML1	16" DEEP	(2) #5 BARS TOP AND BOTTOM	MATCH WALL REINFORCING
ML2	16" DEEP	(1) #5 BARS TOP AND BOTTOM	MATCH WALL REINFORCING
ML3	30" DEEP	(2) #5 BARS TOP AND BOTTOM	MATCH WALL REINFORCING
ML4	48" DEEP	(2) #6 BARS TOP AND BOTTOM	#5 AT 8" O.C.

MASONRY JAMB (MJ) SCHEDULE				
SEE TYPICAL JAMB DETAIL FOR ADDITIONAL INFORMATION				
MARK	REBAR AND QUANTITIES	TYPE	LENGTH	REMARKS
MJ1	(2) #5	A	16"	REBAR CENTERED
MJ2	(8) #5	C	24"	REBAR EACH FACE
MJ3	(4) #5	B	16"	REBAR EACH FACE



PHASE 1 ROOF FRAMING PLAN
SCALE: 1/8" = 1'-0"



PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
ROOF FRAMING PLAN


Laughlin Ricks Architecture
architecture/planning
134 3rd Ave East, Twin Falls, Idaho 83301
(208) 736-8050

Ridge Structural Engineering
1152 Bond Avenue, Suite B
Rexburg, ID 83440
phone: 208.569.5694
contact@ridgestructural.com

DATE: 7.15.2024
PERMIT SET: KBB
#23029
PROJECT #


JOB NO.: 24.145 PROJECT MANAGER: JJ CAD OPERATOR: GTC

S2.1




- KEYNOTES:**
1. WALL BEYOND, SEE PLAN
 2. #4 BENT DOWEL AT 18" O.C.
 3. CONCRETE SLAB ON GRADE, SEE PLAN
 4. CONCRETE WALL, SEE PLAN
 5. CONCRETE FOOTING, SEE PLAN
 6. COMPACTED SUB-GRADE BELOW FOOTING, SEE PLAN
 7. MINIMUM FOOTING DEPTH, SEE GSN
 8. SIDEWALK, PAVEMENT, OR FINISH GRADE PER ARCH
 9. RIGID INSULATION PER ARCH

103 CONCRETE SLAB AT FOUNDATION
SCALE: NTS




- KEYNOTES:**
1. MASONRY WALL, SEE PLAN
 2. #5 DOWEL DRILLED AND EPOXIED INTO EXISTING SLAB W/ 3" MIN EMBEDMENT
 3. EXISTING CONCRETE SLAB ON GRADE

104 MASONRY WALL AT EXISTING SLAB ON GRADE
SCALE: NTS




- KEYNOTES:**
1. MASONRY WALL, SEE PLAN
 2. DOWEL TO MATCH VERTICAL MASONRY WALL REINFORCING SIZE AND SPACING
 3. CONCRETE SLAB ON GRADE, SEE PLAN
 4. CONCRETE WALL, SEE PLAN
 5. CONCRETE FOOTING, SEE PLAN
 6. COMPACTED SUB-GRADE BELOW FOOTING, SEE PLAN
 7. MINIMUM FOOTING DEPTH, SEE GSN
 8. SIDEWALK, PAVEMENT, OR FINISH GRADE PER ARCH
 9. RIGID INSULATION PER ARCH

101 MASONRY WALL AT FOUNDATION
SCALE: NTS




- KEYNOTES:**
1. CONCRETE FOOTING, SEE PLAN
 2. COMPACTED SUB-GRADE BELOW FOOTING, SEE PLAN
 3. CONCRETE SLAB ON GRADE, SEE PLAN

105 CONCRETE SLAB AT FOUNDATION
SCALE: NTS




- KEYNOTES:**
1. MASONRY WALL, SEE PLAN
 2. COMPACTED SUB-GRADE BELOW FOOTING, SEE PLAN
 3. CONCRETE SLAB ON GRADE, SEE PLAN
 4. CONCRETE FOOTING, SEE PLAN
 5. DOWEL TO MATCH VERTICAL MASONRY WALL REINFORCING SIZE AND SPACING, EPOXY DOWEL AT FOOTING W/ 6" MIN EMBEDMENT INTO FOOTING, SEE PLAN

102 MASONRY WALL AT FOUNDATION
SCALE: NTS



- KEYNOTES:**
1. #5 BENT DOWEL AT 18" O.C.
 2. TRENCH DRAIN, SEE ARCHITECTURAL DRAWINGS
 3. CONCRETE SLAB ON GRADE, SEE PLAN
 4. #4 HORIZONTAL BARS BELOW TRENCH DRAIN

106 TRENCH DRAIN IN CONCRETE SLAB
SCALE: NTS



PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
FOUNDATION DETAILS

Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, # Twin Falls, Idaho 83301
(208) 736-8050


DATE: 7.15.2024
PERMIT SET: KBB
#23029
PROJECT #

S3.0


This drawing is the property of Ridge Structural Engineering, Inc. Legally, this drawing can NOT be copied in whole or in part. It is only to be used for the project and site specifically identified herein and is not to be used on any other project. Contractors shall verify all dimensions, details, and conditions and report at once any error, inconsistency or omission discovered before construction. The contractor assumes full liability for deviations from the final of these plans.

JOB NO.: 24.145 PROJECT MANAGER: JJ CAD OPERATOR: GTC

Ridge Structural Engineering
1152 Bond Avenue, Suite B phone: 208.569.5694
Rexburg, ID 83440 contact@ridgestructural.com




- KEYNOTES:**
- EXISTING MASONRY WALL
 - L4x4x1/4 EACH SIDE W/ 5/8" DIA THROUGH BOLTS AND WASHERS AT 24" O.C.
 - PROVIDE CONT #4 BAR AND SOLID GROUT WHERE BLOCK CORE IS HOLLOW
 - EXISTING CONCRETE WALL STRUCTURE




- KEYNOTES:**
- CONTINUOUS L2 1/2x2 1/2x1/4 BETWEEN EACH JOIST
 - BOUNDARY ATTACHMENT, SEE PLAN
 - STEEL DECK, SEE PLAN
 - STEEL JOIST, SEE PLAN
 - MASONRY WALL, SEE PLAN
 - CONT L3x3x1/4 LEDGER ANGLE W/ 3/4" DIA x 6" TITEN HD MASONRY ANCHORS AT 16" O.C.
 - EXISTING MASONRY WALL
 - EXISTING ROOF FRAMING



NOTES:
A. SCREW ANCHORS MUST BE INSTALLED INTO GROUTED MASONRY, CONTACT ENGINEER IF THIS CANNOT BE ACCOMPLISHED FOR FURTHER INSTRUCTION



- KEYNOTES:**
- MASONRY WALL, SEE PLAN
 - 1/2" x 6" x 0-8" STEEL EMBED PLATE W/ (4) 3/8" x 6" LONG HEADED STUDS
 - STEEL BEAM, SEE PLAN



- KEYNOTES:**
- CONTINUOUS L4x4x1/4 STEEL ANGLE W/ 5/8" DIA CONCRETE ANCHOR AT 32" O.C. W/ 5" MINIMUM EMBEDMENT
 - BOUNDARY ATTACHMENT, SEE PLAN
 - STEEL DECK, SEE PLAN
 - STEEL JOIST, SEE PLAN
 - MASONRY WALL, SEE PLAN
 - 16" DEEP BOND BEAM W/ (2) #5 BARS CONTINUOUS
 - 1/2" x 6" x 1-0" BEARING PLATE W/ (2) 5/8" DIA x 8" LONG HEADED STUDS ON ±1 1/2" NON SHRINK GROUT



208 STEEL JOIST AT EXISTING MASONRY WALL
SCALE: NTS


204 STEEL BEAM AT MASONRY WALL
SCALE: NTS

201 STEEL JOIST AT MASONRY WALL
SCALE: NTS

209 STEEL JOIST AT EXISTING MASONRY WALL
SCALE: NTS

205 STEEL JOIST AT MASONRY WALL
SCALE: NTS

202 STEEL JOIST AT MASONRY WALL
SCALE: NTS



- KEYNOTES:**
- CONTINUOUS L4x4x1/4 STEEL ANGLE W/ 5/8" DIA CONCRETE ANCHOR AT 32" O.C. W/ 5" MINIMUM EMBEDMENT
 - BOUNDARY ATTACHMENT, SEE PLAN
 - STEEL DECK, SEE PLAN
 - STEEL JOIST, SEE PLAN
 - MASONRY WALL, SEE PLAN
 - 16" DEEP BOND BEAM W/ (2) #5 BARS CONTINUOUS
 - 1/2" x 6" x 1-0" BEARING PLATE W/ (2) 5/8" DIA x 8" LONG HEADED STUDS ON ±1 1/2" NON SHRINK GROUT


- 8. EXISTING MASONRY WALL**
9. DRILL AND EPOXY NEW WALL VERTICAL REBAR INTO EXISTING WALL
10. EXISTING ROOF FRAMING

NOTES:
A. SCREW ANCHORS MUST BE INSTALLED INTO GROUTED MASONRY, CONTACT ENGINEER IF THIS CANNOT BE ACCOMPLISHED FOR FURTHER INSTRUCTION

210 EXISTING ROOF JOIST AT WOOD BEAM
SCALE: NTS

206 STEEL JOIST AT MASONRY WALL
SCALE: NTS


203 STEEL JOIST AT STEEL BEAM
SCALE: NTS



- KEYNOTES:**
- EXISTING ROOF FRAMING
 - WOOD BEAM, SEE PLAN
 - HANG EXISTING JOIST TO NEW WOOD BEAM W/ IUS2 3/16" FACE MOUNT HANGER, CONTRACTOR TO VERIFY JOIST DIMENSION
 - HANG EXISTING WOOD JOIST TO NEW WOOD BEAM W/ IUS10 HANGER

- KEYNOTES:**
- CONTINUOUS L2 1/2x2 1/2x1/4 BETWEEN EACH JOIST
 - BOUNDARY ATTACHMENT, SEE PLAN
 - STEEL DECK, SEE PLAN
 - STEEL JOIST, SEE PLAN
 - MASONRY WALL, SEE PLAN
 - 1/2" x 6" x 1-0" BEARING PLATE W/ (2) 5/8" DIA x 8" LONG HEADED STUDS

- KEYNOTES:**
- STEEL BEAM, SEE PLAN
 - STEEL JOIST, SEE PLAN
 - STEEL DECK, SEE PLAN
 - MASONRY WALL, SEE PLAN
 - #5 x 48" LONG WELDABLE REBAR AT 32" O.C.
 - CONTINUOUS L4x4x1/4 STEEL ANGLE W/ 5/8" DIA CONCRETE ANCHOR AT 32" O.C. W/ 5" MINIMUM EMBEDMENT
 - BOUNDARY ATTACHMENT, SEE PLAN



- KEYNOTES:**
- CONTINUOUS L3x3x1/4 STEEL ANGLE W/ 3/4" DIA x 6" SCREW ANCHOR AT 32" O.C.
 - BOUNDARY ATTACHMENT, SEE PLAN
 - STEEL DECK, SEE PLAN
 - STEEL JOIST, SEE PLAN
 - MASONRY WALL, SEE PLAN
 - EXISTING MASONRY WALL
 - DRILL AND EPOXY NEW WALL VERTICAL REBAR INTO EXISTING WALL, NEW VERTICAL BAR MUST BE INSTALLED IN SAME CELL AS EXISTING WALL VERTICAL BAR


NOTES:
A. SCREW ANCHORS MUST BE INSTALLED INTO GROUTED MASONRY, CONTACT ENGINEER IF THIS CANNOT BE ACCOMPLISHED FOR FURTHER INSTRUCTION

211 WOOD JOIST AT WOOD BEAM
SCALE: NTS

207 STEEL DECK AT MASONRY WALL
SCALE: NTS



- KEYNOTES:**
- BOUNDARY ATTACHMENT, SEE PLAN
 - STEEL DECK, SEE PLAN
 - CONT 16" DEEP MINV SOLID GROUTED BOND BEAM W/ #5 BARS CONTINUOUS
 - MASONRY WALL, SEE PLAN
 - CONTINUOUS 1/2" x 7" WIDE EMBED PLATE W/ 5/8" DIA x 6" LONG HEADED STUDS AT 32" O.C.



- KEYNOTES:**
- EXISTING MASONRY WALL
 - L4x4x1/4 EACH SIDE W/ 5/8" DIA THROUGH BOLTS AND WASHERS AT 24" O.C.
 - PROVIDE CONT #4 BAR AND SOLID GROUT WHERE BLOCK CORE IS HOLLOW
 - EXISTING CONCRETE WALL STRUCTURE

NOTES:
A. SCREW ANCHORS MUST BE INSTALLED INTO GROUTED MASONRY, CONTACT ENGINEER IF THIS CANNOT BE ACCOMPLISHED FOR FURTHER INSTRUCTION

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
FRAMING DETAILS


Laughlin Ricks Architecture
architecture/planning
134 3rd Ave East, Twin Falls, Idaho 83301
(208) 736-8050

DATE: 7.15.2024
PERMIT SET: KBB
#23029
PROJECT #


JOB NO.: 24.145 PROJECT MANAGER: JJ CAD OPERATOR: GTC

Ridge Structural Engineering
1152 Bond Avenue, Suite B phone: 208.569.5694
Rexburg, ID 83440 contact@ridgestructural.com


S4.0



- KEYNOTES:**
1. MASONRY WALL, SEE PLAN
 2. 2" THICK CONCRETE THREADS
 3. 1/2" GAUGE STEEL RISER PLATE AND TREAD PLATE
 4. L3x3x1/8 ANGLE W/ (2) 3/8" DIA x 3" SCREW ANCHORS




218 STAIR TREAD AT MASONRY WALL
SCALE: NTS




- KEYNOTES:**
1. BOUNDARY ATTACHMENT, SEE PLAN
 2. STEEL DECK, SEE PLAN
 3. CONT 1/2" DEEP MINI SOLID GROUTED BOND BEAM W/ #5 BARS CONTINUOUS
 4. MASONRY WALL, SEE PLAN
 5. CONTINUOUS 1/2" x 7" WIDE EMBED PLATE W/ 5/8" DIA x 6" LONG HEADED STUDS AT 32" O.C.

215 STEEL DECK AT MASONRY WALL
SCALE: NTS




- KEYNOTES:**
1. MASONRY WALL, SEE PLAN
 2. 4" THICK CONCRETE SLAB REINFORCED W/ #3 BARS AT 12" O.C. EACH WAY, CENTERED IN SLAB THICKNESS
 3. 3/8" THICK STEEL PLATE
 4. CONTINUOUS L3x3x1/4 STEEL LEDGER ANGLE W/ 3/4" DIA x 6" LONG TITEN MASONRY ANCHORS AT 8" O.C.




- KEYNOTES:**
1. CONTINUOUS L3x3x1/4 STEEL ANGLE W/ 3/4" DIA x 6" SCREW ANCHOR AT 32" O.C.
 2. BOUNDARY ATTACHMENT, SEE PLAN
 3. STEEL DECK, SEE PLAN
 4. STEEL JOIST, SEE PLAN
 5. EXISTING MASONRY WALL
 6. EXISTING ROOF FRAMING

219 STAIR LANDING AT MASONRY WALL
SCALE: NTS

216 STEEL JOIST AT EXISTING MASONRY WALL
SCALE: NTS




- KEYNOTES:**
1. EXISTING ROOF FRAMING
 2. WOOD BEAM, SEE PLAN
 3. HANG EXISTING JOIST TO NEW WOOD BEAM W/ US2-3716 FACE MOUNT HANGER, CONTRACTOR TO VERIFY JOIST DIMENSION



- KEYNOTES:**
1. NEW FULL HEIGHT (SL) BLOCKING BETWEEN EACH EXISTING JOIST W/ ASS CLIP TOP AND BOTTOM, TOP CLIP ATTACHED TO UNDERSIDE OF EXISTING ROOF SHEATHING USING 1/2" LONG SCREWS
 2. (2) 10# NAILS AT EACH JOIST
 3. EXISTING ROOF FRAMING
 4. CONT 2x PT PLATE W/ 5/8" DIA ANCHOR BOLTS AT 32" O.C. W/ 5" MIN EMBEDMENT
 5. MASONRY WALL, SEE PLAN


220 EXISTING ROOF JOIST AT WOOD BEAM
SCALE: NTS

217 EXISTING WOOD JOIST AT NEW MASONRY SHEARWALL
SCALE: NTS



- KEYNOTES:**
1. STEEL BEAM, SEE PLAN
 2. STEEL JOIST, SEE PLAN
 3. STEEL DECK, SEE PLAN
 4. MASONRY WALL, SEE PLAN
 5. #5 x 48" LONG WELDABLE REBAR AT 32" O.C.
 6. CONTINUOUS L4x4x1/4 STEEL ANGLE W/ 5/8" DIA CONCRETE ANCHOR AT 32" O.C. W/ 5" MINIMUM EMBEDMENT
 7. BOUNDARY ATTACHMENT, SEE PLAN

221 MASONRY WALL AT STEEL BEAM
SCALE: NTS



DATE _____

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
FRAMING DETAILS

Laughlin Ricks Architecture
architecture/planning
134 3RD Ave East, # Twin Falls, Idaho 83301
(208) 736-8050


DATE: 7.15.2024
PERMIT SET: KBB
Checked: #23029
PROJECT #

S4.1

This drawing is the property of Ridge Structural Engineering, Inc. Legally, this drawing can NOT be copied in whole or in part. It is only to be used for the project and site specifically described herein and is to be used on any other project. Contractor shall certify review of dimensions, details, and conditions and report at once any error, inconsistency or omission discovered before construction. The contractor assumes full liability for deviations from the final of these plans.

JOB NO.: 24.145 PROJECT MANAGER: JJ CAD OPERATOR: GTC

Ridge Structural Engineering
1152 Bond Avenue, Suite B phone: 208.569.5694
Rexburg, ID 83440 contact@ridgestructural.com



PH 1 PART A DEMO MECHANICAL FLOOR PLAN
 SCALE: 1/8" = 1'-0"

- PLAN NOTES:**
- 1 EXISTING DIFFUSER TO REMAIN. PROTECT DURING CONSTRUCTION.
 - 2 EXISTING RETURN GRILLE TO REMAIN. PROTECT DURING CONSTRUCTION.
 - 3 EXISTING EXHAUST GRILLE TO REMAIN. PROTECT DURING CONSTRUCTION.
 - 4 EXISTING DIFFUSER TO BE REMOVED AND DISPOSED OF IN ITS ENTIRETY. REMOVE, DISPOSE OF, AND CAP CORRESPONDING BRANCH DUCTWORK AND CAP AT MAIN IF BRANCH DUCTWORK IS NOT BEING RE-USED. SEE SHEET M1A-1.1 FOR BRANCH DUCTWORK BEING RE-USED.
 - 5 EXISTING RETURN/RELIEF GRILLE TO BE REMOVED AND DISPOSED OF IN ITS ENTIRETY ALONG WITH CORRESPONDING SOUND BOOT.
 - 6 EXISTING EXHAUST GRILLE TO BE REMOVED IN ITS ENTIRETY. REMOVE, DISPOSE OF, AND CAP CORRESPONDING BRANCH DUCTWORK CAP AT MAIN.
 - 7 EXISTING IN-LINE EXHAUST FAN TO BE REMOVED IN ITS ENTIRETY. REMOVE ALL DUCT AND CAP DUCT AT ROOF CAP.
 - 8 EXISTING CEILING EXHAUST FAN TO BE REMOVED IN ITS ENTIRETY. REMOVE ALL DUCT AND CAP DUCT AT ROOF CAP.
 - 9 EXISTING IN-LINE EXHAUST FAN TO REMAIN. MODIFY DUCTWORK AS REQUIRED FOR NEW EXHAUST GRILLE LOCATION.
 - 10 EXISTING DRYER TO BE REMOVED BY THE GENERAL CONTRACTOR PRIOR TO CONSTRUCTION. REMOVE AND DISPOSE OF CORRESPONDING DUCTWORK AND WALL CAP IN ITS ENTIRETY. COORDINATE WITH THE GENERAL CONTRACTOR FOR THE REQUIRED PATCH & REPAIR AFTER THE WORK IS COMPLETE. COORDINATE WITH DIVISION 22 FOR GAS LINE REMOVAL.
 - 11 EXISTING THERMOSTAT TO REMAIN. PROTECT DURING CONSTRUCTION.
 - 12 REMOVE AND RE-LOCATE EXISTING THERMOSTAT. MODIFY WIRING AS REQUIRED. SEE SHEET M1A-1.1 FOR NEW LOCATION.
 - 13 EXISTING CEILING ACCESS SECURITY PANEL.
 - 14 EXISTING INTAKE/COMBUSTION AIR LOUVER AND CORRESPONDING DUCTWORK TO REMAIN.
 - 15 EXISTING UNIT HEATER TO REMAIN. PROTECT DURING CONSTRUCTION.
 - 16 EXISTING ROOF ACCESS.

MECHANICAL LEGEND

SYMBOL	DESCRIPTION
	ELECTRONIC THERMOSTAT
	ELECTRONIC SENSOR
	EQUIPMENT SYMBOL
(E) FC-1*	EXISTING EQUIPMENT TAG MARKINGS
(E) FC-1	EXISTING EQUIPMENT DRAWING MARKINGS
	SMOKE DETECTOR
	CARBON DIOXIDE DETECTOR
(E)	EXISTING
(R)	RELOCATED
	HAND DAMPER
	CONCEALED HAND DAMPER
	ROUND BRANCH DUCT WITH HAND DAMPER
	INSULATED FLEXIBLE DUCT
	RETURN AIR OR EXHAUST GRILLE
	CEILING DIFFUSER
	ROOF MOUNTED UPBLAST EXHAUST FAN
---	EXISTING TO BE DEMOLISHED
---	EXISTING TO REMAIN (E)
---	NEW EQUIPMENT
	CONNECTION/DISCONNECTION

- GENERAL NOTES:**
- A- THE CONTRACTOR SHALL CHECK AND VERIFY ALL DIMENSIONS AND CONNECTIONS ON THE JOB SITE. ALL WORK SHALL BE EXECUTED FROM MEASUREMENTS TAKEN AT THE SITE.
 - B- THE MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE TO INSURE PROPER CODE CLEARANCES FOR ELECTRICAL AND MECHANICAL ACCESS WHEN INSTALLING ANY EQUIPMENT SUPPLIED BY THE MECHANICAL CONTRACTOR.
 - C- IT IS CRITICAL THAT THIS CONTRACTOR COORDINATE EQUIPMENT LOCATIONS WITH PIPING, DUCTWORK, ELECTRICAL CONDUIT AND BUILDING STRUCTURE TO INSURE CODE COMPLIANCE.
 - D- DUCT DIMENSIONS CALLED OUT ON DRAWINGS ARE INSIDE FREE AREA DIMENSIONS. ACOUSTICAL DUCT LINER ARE TO BE ADDED TO OVERALL MEASUREMENTS.
 - E- ALL DUCTWORK AND PIPING WHICH PASSES THRU FIRE RATED WALLS TO BE FIRE STOPPED WITH APPROVED FOAM OR SEALANT. REFER TO SPECIFICATIONS FOR APPROVED MANUFACTURERS.
 - F- PIPING FROM WATER HEATER TO TERMINATION OF HEATED WATER FIXTURE SUPPLY PIPE SHALL HAVE 1-INCH INSULATION WITH AMINIMUM CONDUCTIVITY OF 0.21 BTU x IN/(HxFT²xF) AS REQUIRED BY IECC C404.4. INSULATION SHALL BE CONTINUOUS EXCEPT WHERE THE PIPE PASSES THROUGH A FRAMING MEMBER OR AT LOCATIONS WHERE A VERTICAL SUPPORT OF THE PIPING IS INSTALLED.
 - G- SEE ARCHITECTURAL PLANS FOR ROOM NAMES AND NUMBERS.

MECHANICAL LEGEND

SYMBOL	DESCRIPTION
	ELECTRONIC THERMOSTAT
	ELECTRONIC SENSOR
	EQUIPMENT SYMBOL
(E) FC-1*	EXISTING EQUIPMENT TAG MARKINGS
(E) FC-1	EXISTING EQUIPMENT DRAWING MARKINGS
	SMOKE DETECTOR
	CARBON DIOXIDE DETECTOR
(E)	EXISTING
(R)	RELOCATED
	HAND DAMPER
	CONCEALED HAND DAMPER
	ROUND BRANCH DUCT WITH HAND DAMPER
	INSULATED FLEXIBLE DUCT
	RETURN AIR OR EXHAUST GRILLE
	CEILING DIFFUSER
	ROOF MOUNTED UPBLAST EXHAUST FAN
---	EXISTING TO BE DEMOLISHED
---	EXISTING TO REMAIN (E)
---	NEW EQUIPMENT
	CONNECTION/DISCONNECTION


Engineered Systems Associates
 1355 EAST CENTER
 POCATELLO, IDAHO 83201
 PHONE: (208) 233-0501
 FAX: (208) 233-0529
 EMAIL: esa@engsystems.com
 ESA JOB NUMBER: 24048

Professional Engineer
 David L. Hansen
 18184
 STATE OF IDAHO
 JUL 12, 2024


DATE: 07/12/2024
 DRAWN: [] CHECKED: []
 ISSUE FOR PERMIT: []
 AN ADDITION FOR:
 TWIN FALLS COUNTY JAIL
 2815 Wright Ave., Twin Falls, ID 83301
 PH 1 PART A DEMO MECH. FLOOR PLAN

Laughlin Ricks Architecture
 architecture/planning
 134 3RD AVE. E. * Twin Falls, Idaho 83301
 (208) 736-8050 Fax: (208) 733-0950

M1A-1.0



PH 1 PART A MECHANICAL FLOOR PLAN
 SCALE: 1/8" = 1'-0"



- PLAN NOTES:**
- 1 EXISTING DIFFUSER TO REMAIN. BALANCE TO CFM INDICATED ON PLANS.
 - 2 EXISTING RETURN/RELIEF GRILLE TO REMAIN. PROTECT DURING CONSTRUCTION.
 - 3 EXISTING EXHAUST GRILLE TO REMAIN. BALANCE TO CFM INDICATED ON PLANS.
 - 4 EXISTING TRANSFER DUCT IN CEILING SPACE WITH FIRE DAMPER TO REMAIN. PROTECT DURING CONSTRUCTION.
 - 5 EXISTING CEILING ACCESS SECURITY PANEL.
 - 6 ROUTE MAIN DUCTWORK AS HIGH AS POSSIBLE. SUPPLY DIFFUSERS TO BE INSTALLED HORIZONTALLY AND COME IN 45° DOWNWARD DEFLECTION TO MINIMIZE AIR VELOCITY TO OCCUPANTS BELOW. EXHAUST GRILLES TO BE INSTALLED ON BOTTOM OF DUCT. EXPOSED DUCTWORK TO BE PRE-PRIMED WITH PAINTLOK.
 - 7 RETURN GRILLE TO CONTAIN MIN QTY (2) 90° ELBOWS/TURNS FOR SOUND ISOLATION. TERMINATE DUCT UPWARDS AND COVER WITH 1/4" GALVANIZED MESH WIRING.
 - 8 TYPICAL CO / NO2 SENSOR FOR GARAGE EXHAUST SYSTEM. MOUNTING HEIGHT AS PER MANUFACTURER INSTRUCTIONS. SEE SPECIFICATIONS.
 - 9 RETURN GRILLE TO CONTAIN MIN QTY (2) 90° ELBOWS/TURNS FOR SOUND ISOLATION. COVER OPENING WITH 1/4" GALVANIZED MESH WIRING.
 - 10 EXISTING THERMOSTAT TO REMAIN. PROTECT DURING CONSTRUCTION.
 - 11 RE-LOCATE EXISTING THERMOSTAT. MODIFY WIRING AS REQUIRED.
 - 12 TIE NEW BRANCH DUCTWORK TO NEAREST EXISTING MAIN. FIELD VERIFY EXISTING CONDITIONS PRIOR TO CONSTRUCTION.
 - 13 EXISTING INTAKE/COMBUSTION AIR LOUVER AND CORRESPONDING DUCTWORK TO REMAIN.
 - 14 EXISTING UNIT HEATER TO REMAIN. PROTECT DURING CONSTRUCTION.
 - 15 EXISTING ROOF ACCESS.
 - 16 CONTROLS TO COME WITH OCCUPANCY SENSOR.
 - 17 INSTALL MOTORIZED DAMPER IN CEILING SPACE. COORDINATE WITH ELECTRICAL FOR INTERLOCK WITH THE OPERATION OF ANY DRYER.
 - 18 INSTALL WALL ELECTRIC HEATER 12" BELOW CEILING AND DIRECTLY BELOW RELIEF/COMBUSTION AIR INTAKE.
 - 19 ADJUST FAN COIL INSTALL LOCATION AS DIRECTED BY OWNER. SEE INSTALL DETAIL ON SHEET M1A-2.2.

07.12.24

DATE: JUL 12 2024
 ISSUE FOR PERMIT

AN ADDITION FOR:
TWIN FALLS COUNTY JAIL
 2815 Wright Ave. * Twin Falls, Idaho 83301
PH 1 PART A DEMO MECH. FLOOR PLAN

Laughlin Ricks Architecture
 architecture/planning
 134 3RD AVE. E. * Twin Falls, Idaho 83301
 (208) 756-8050 Fax: (208) 753-0950

Engineered Systems Associates
 1355 EAST CENTER
 POCATELLO, IDAHO 83201
 PHONE: (208) 233-0501
 FAX: (208) 233-0529
 EMAIL: esa@engsystems.com
 ESA JOB NUMBER: 24048

DATE: 07/12/2024
 1/1 Drawn 0/11 Checked
M1A-1.1

PLAN NOTES:

- 1 EXISTING ROOF CAP TO REMAIN. PROTECT DURING CONSTRUCTION.
- 2 EXISTING FLUE THRU ROOF TO REMAIN. PROTECT DURING CONSTRUCTION.
- 3 REMOVE AND REPLACE EXISTING ROOF EXHAUST FAN WITH NEW.
- 4 REMOVE AND DISPOSE OF EXISTING EXHAUST FAN IN ITS ENTIRETY ALONG WITH CORRESPONDING DUCTWORK AND GRILLES. CAP OPENING WITH 18 GAUGE GALVANIZED STEEL COVERING.
- 5 REMOVE, DISPOSE OF, AND REPLACE EXISTING ROOF TOP UNIT WITH NEW. FIELD VERIFY EXISTING CONDITIONS PRIOR TO SUBMITTALS AND CONSTRUCTIONS. PROVIDE AND INSTALL ROOF TOP UNITS WITH ADAPT-A-CURB OR SIMILAR IF REQUIRED. COORDINATE WITH DIVISION 22 FOR GAS PIPING DISCONNECTION AND RECONNECTION.

DATE: 07.12.24


DATE: JUL 12 2024
ISSUE FOR PERMIT

AN ADDITION FOR:
TWIN FALLS COUNTY JAIL
2815 Wright Ave, Twin Falls, ID 83301
PH 1 PART A MECH. ROOF PLAN


Laughlin Ricks Architecture
architecture/planning
134 3RD AVE. E. * Twin Falls, Idaho 83301
(208) 736-8050 Fax: (208) 733-0950

DATE: 07/12/2024
BY: [Signature] DMH
CHECKED: [Signature] DMH

M1A-1.2



Engineered Systems Associates
1355 EAST CENTER
POCATELLO, IDAHO 83201
PHONE: (208) 233-0501
FAX: (208) 233-0529
EMAIL: esa@engsystems.com
ESA JOB NUMBER: 24048



PH 1 PART A MECHANICAL ROOF PLAN
SCALE: 1/8" = 1'-0"



EXHAUST FAN SCHEDULE											
SYM.	TYPE	C.F.M.	S.P.E.	HP	CHAR.	FLA	R.P.M.	CONTROL	REMARKS		
EF-1	ROOF MOUNTED	455	0.38	1/4	120/60"1	5.8	1725	24/7 CONTINUOUS	PENNBARREY MODEL DX110GP		
EF-2	IN-LINE	-	-	-	-	-	-	-	EXISTING TO BE REMOVED		
EF-3	ROOF MOUNTED	1450	0.38	1/2	120/60"1	9.8	1230	24/7 CONTINUOUS	PENNBARREY MODEL DX16Q1GP		
EF-4	IN-LINE	75	0.25	1/20	120/60"1	X	1050	WITH LIGHTS (SEE ELECTRICAL)	EXISTING TO REMAIN.		
EF-5	IN-LINE	-	-	-	-	-	-	-	EXISTING TO BE REMOVED		
EF-6	CEILING MOUNTED	-	-	-	-	-	-	-	EXISTING TO BE REMOVED		
EF-7	IN-LINE	-	-	-	-	-	-	-	EXISTING TO BE REMOVED		
EF-8	IN-LINE	-	-	-	-	-	-	-	EXISTING TO BE REMOVED		
EF-9	ROOF MOUNTED	1500	0.25	1/2	120/60"1	9.8	1155	(E) COOLING THERMOSTAT	PENNBARREY MODEL DX16Q1GP		
EF-10	ROOF MOUNTED	900	0.5	1/3	120/60"1	-	1595	24/7 CONTINUOUS	PENNBARREY MODEL DX130GP		
EF-11	IN-LINE	-	-	-	-	-	-	-	EXISTING TO BE REMOVED		
EF-12	ROOF MOUNTED	2200	0.5	3/4	120/60"1	13.8	1725	CARBON MONOXIDE	PENNBARREY MODEL DX16Q2GP		
EF-13	WALL MOUNTED	MIN 160	0.125	-	120/60"1	1.7	868	24/7 CONTINUOUS	PENNBARREY MODEL Z8-GPE		

ELECTRIC HEATER SCHEDULE						
SYM.	TYPE	BTUH	KW	CHAR.	CONTROL	REMARKS
EH-1	SURFACE MOUNT	6,824	2.0	208/60"1	INTEGRAL	QMARK MODEL 4408F WITH SURFACE MOUNTED FRAME
EH-2	SURFACE MOUNT	16,378	4.8	208/60"3	INTEGRAL	QMARK MODEL AWH45083F ARCHITECTURAL HEAVY-DUTY WITH SURFACE MOUNTED FRAME

*INSTALL UNIT ON WALL 12" A.F.F. TO BOTTOM OF FRAME OR UNLESS STATED ON PLANS

ELECTRIC HEATER SCHEDULE						
SYM.	TYPE	BTU	KW	CHAR.	CONTROL	REMARKS
EH-1	SEMI-RECESSED WALL MTD	13,650	4.0	277/60"1	INTEGRAL	QMARK MODEL AWH4407F WITH SEMI-RECESSED MOUNT FRAME
EH-2	SEMI-RECESSED WALL MTD	16,378	4.8	277/60"1	INTEGRAL	QMARK MODEL AWH4507F WITH SURFACE MOUNT FRAME

* INSTALL ALL UNITS ON WALL 12" A.F.F. TO BOTTOM OF FRAME

CONDENSING UNIT SCHEDULE										
SYM.	COOLING	HEATING	EAT	CHAR.	MCA	MOCP	WEIGHT	REFRIGERANT PIPING*		REMARKS
								LIQUID	SUCTION	
CU-1	33,200 BTUH	N/A	95°F	208-10	14	25	130#	1/4"	5/8"	DAIWA ELECTRIC MODEL MSY-GS36NA2 CONDENSING UNIT WITH LOW AMBIENT START KIT. 18.5 SEER2.

*ADJUST REFRIGERANT SIZE BASED ON FIELD MEASUREMENTS, QUANTITY OF FITTINGS, AND MANUFACTURER RECOMMENDED SIZING CHARTS.

FAN COIL SCHEDULE								
SYM.	CFM	CHAR.	FAN WATTS	FLA	WEIGHT	COOLING CAPACITY	CONDENSATE DRAIN	REMARKS
FC-1	MEDIUM	FROM HP-1	60	1.0	40#	33,200 BTU	3/4"	MITSUBISHI ELECTRIC MODEL MSY-GS36NA2 WITH CONDENSATE PUMP AND WIRED THERMOSTAT.

ROOF TOP HEATING & AIR CONDITIONING UNIT SCHEDULE																		
SYM.	CFM	OA	SP _i	BLOWER H.P.	CHAR.	MCA	MOCP	WEIGHT	GAS CONN.	HEATING				COOLING			REMARKS*	
										BTUH IN	BTUH OUT	EAT	LAT	MBH	EAT	LAT		
RTU-1	1200	200	0.7	0.5	208/60"3	20	30	700 LB	3/4"	110,000	73,000	44.5	107.7	32	95	57.9	CARRIER MODEL 48FCEA04 WITH COIL GUARDS, INTEGRATED DISCONNECT. 13.4 SEER2.	
RTU-2	4000	1450	0.5	2.0	208/60"3	45	60	1200 LB	3/4"	250,000	200,000	29.9	74.1	125	99	55	CARRIER MODEL 48FCTM12 WITH 2-STAGE COOLING, STAINLESS STEEL HEAT EXCHANGER, ECONOMIZER, BAROMETRIC RELIEF DAMPER, SMOKE DETECTOR, COIL GUARDS, INTEGRATED DISCONNECT AND CONVENIENCE OUTLET. 15 IEER	
RTU-3	1200	230	0.65	0.33	208/60"1	26	30	700 LB	3/4"	110,000	73,000	44.5	107.7	32	95	57.9	CARRIER MODEL 48FCEA04 WITH COIL GUARDS, INTEGRATED DISCONNECT. 13.4 SEER2.	
RTU-4	1200	180	0.65	0.5	208/60"3	20	30	700 LB	3/4"	110,000	73,000	44.5	107.7	32	95	57.9	CARRIER MODEL 48FCEA04 WITH COIL GUARDS, INTEGRATED DISCONNECT. 13.4 SEER2.	
RTU-5	1200	200	0.7	0.5	208/60"3	20	30	700 LB	3/4"	110,000	73,000	44.5	107.7	32	95	57.9	CARRIER MODEL 48FCEA04 WITH COIL GUARDS, INTEGRATED DISCONNECT. 13.4 SEER2.	
RTU-6	3000	400	1.0	1.0	208/60"3	40	50	960 LB	3/4"	224,000	181,000	44.5	X	86	95	X	CARRIER MODEL 48FCFM08 WITH 2-STAGE COOLING, SMOKE DETECTOR, ECONOMIZER, COIL GUARDS, INTEGRATED DISCONNECT. 15 IEER.	
RTU-7	3000	900	1.0	1.0	208/60"3	40	50	960 LB	3/4"	224,000	181,000	44.5	X	86	95	X	CARRIER MODEL 48FCFM08 WITH 2-STAGE COOLING, SMOKE DETECTOR, ECONOMIZER, COIL GUARDS, INTEGRATED DISCONNECT. 15 IEER.	
RTU-8	1800	300	0.7	1.0	208/60"3	26	30	750 LB	3/4"	130,000	106,000	44.5	99.0	44	95	57.3	CARRIER MODEL 48FCEA05 WITH ECONOMIZER, BAROMETRIC RELIEF DAMPER, COIL GUARDS, INTEGRATED DISCONNECT. 13.4 SEER2.	
RTU-9	4000	250	0.5	2.0	208/60"3	45	60	1200 LB	3/4"	250,000	200,000	29.9	74.1	125	99	55	CARRIER MODEL 48FCTM12 WITH 2-STAGE COOLING, STAINLESS STEEL HEAT EXCHANGER, ECONOMIZER, BAROMETRIC RELIEF DAMPER, SMOKE DETECTOR, COIL GUARDS, INTEGRATED DISCONNECT AND CONVENIENCE OUTLET. 15 IEER	

*UNITS TO COME WITH ADAPT-A-CURB OR SIMILAR IF REQUIRED FOR NEW INSTALL. CONTRACTOR TO FIELD VERIFY EXISTING CONDITIONS AND TAKE MEASUREMENTS PRIOR TO PURCHASE.

GRILLE AND REGISTER SCHEDULE										
SYM.	TYPE	SIZE	CFM RANGE	THROW PATTERN	CONSTR.	FINISH	BRANCH DUCT	BALANCING DAMPER	MAX NC RATING	REMARKS
CD-1 CFM	SECURITY CEILING	24x24"	40-100	◀▶	STEEL	BY ARCH	8"0	NO	25	PRICE MODEL MSD IN 24x24" SECURITY CEILING
CD-2 CFM	SECURITY CEILING	24x24"	110-225	◀▶	STEEL	BY ARCH	8"0	NO	25	PRICE MODEL MSD IN 24x24" SECURITY CEILING
CD-3 CFM	SECURITY CEILING	24x24"	230-380	◀▶	STEEL	BY ARCH	10"0	NO	25	PRICE MODEL MSD IN 24x24" SECURITY CEILING
CD-4 CFM	SECURITY CEILING	12x12"	110-225	◀▶	STEEL	BY ARCH	8"0	NO	25	PRICE MODEL MSD
CD-5 CFM	CEILING	24x24"	40-100	◀▶	STEEL	BY ARCH	8"0	NO	25	PRICE MODEL SMD IN 24x24" LAY-IN CEILING
CD-6 CFM	CEILING	24x24"	110-225	◀▶	STEEL	BY ARCH	8"0	NO	25	PRICE MODEL SMD IN 24x24" LAY-IN CEILING
CD-7 CFM	CEILING	24x24"	230-380	◀▶	STEEL	BY ARCH	10"0	NO	25	PRICE MODEL SMD IN 24x24" LAY-IN CEILING
CD-8 CFM	CEILING	8x8"	40-100	◀▶	STEEL	BY ARCH	8"0	NO	30	PRICE MODEL SMD
DR-20 CFM	DUCT REGISTER	18x6"	330-370	45° DEFLECTION	STEEL	BY ARCH	20"0	YES	30	PRICE MODEL SDG SPIRAL DUCT GRILLE
BEG-16 CFM	DUCT REGISTER	26x6"	500	0°	STEEL	BY ARCH	16"0	YES	30	PRICE MODEL SDGR SPIRAL DUCT GRILLE
EG-1 CFM	CEILING	8x8"	50-100	N/A	STEEL	WHITE	8"0	YES	30	PRICE MODEL 10
EG-2 CFM	CEILING	8x8"	50-100	N/A	STEEL	WHITE	8x6"	YES	30	PRICE MODEL MSRRP
PH-1	PENTHOUSE	22x22"	2400	N/A	ALUM	BY ARCH	22x22"	MOTORIZED DAMPER	N/A	GREENHECK WIH-22-22 INTAKE VENTILATOR
RG-1	SECURITY CEILING	24x24"	125-450	N/A	STEEL	BY ARCH	10x10" SOUND BOOT	NO	25	PRICE MODEL MSRRP IN 24x24" SECURITY CEILING
RG-2	CEILING	12x24"	125-450	N/A	STEEL	WHITE	10x10" SOUND BOOT	NO	25	PRICE MODEL 10 IN 24x24" LAY-IN CEILING
RG-3	SECURITY CEILING	24x24"	455-1000	N/A	STEEL	BY ARCH	14x14" SOUND BOOT	NO	25	PRICE MODEL MSRRP IN 24x24" SECURITY CEILING
SD-1 CFM	SIDEWALL	14x14"	200-230	N/A	STEEL	BY ARCH	8"0	YES	30	PRICE MODEL MSBL SECURITY SIDEWALL DIFFUSER
SD-1 CFM	SIDEWALL	16x16"	600-800	N/A	STEEL	BY ARCH	16x16"	YES	30	PRICE MODEL MSRRP
WC-1	WALL CAP	8"0	N/A	N/A	STEEL	BY ARCH	8"0	NO	N/A	

(1) DIFFUSER TO BE MOUNTED 12 AWAY FROM FLOOR.

Professional Engineer

David L. Hansen
 18184
 JUL 12, 2024

Engineered Systems Associates
 1355 EAST CENTER
 POCAHELLO, IDAHO 83201
 PHONE: (208) 233-0501
 FAX: (208) 233-0529
 EMAIL: esa@engsystems.com
 ESA JOB NUMBER: 24048


07.12.24

DATE: JUL 12, 2024
 ISSUE FOR PERMIT


AN ADDITION FOR:
 TWIN FALLS COUNTY JAIL
 2815 Wright Ave., Twin Falls, ID 83301
 MECHANICAL SCHEDULES

Laughlin Ricks Architecture
 architecture/planning
 134 3RD AVE. E. * Twin Falls, Idaho 83301
 (208) 736-8050 Fax: (208) 733-0950


DATE: 07/12/2024
 DRAWN: [Signature] CHECKED: [Signature]
M1A-2.1




CEILING DIFFUSER DETAIL WITH FLEXIBLE DUCT
NO SCALE




TYPICAL ROOFTOP MOUNTING DETAIL
NO SCALE




ROOF TOP HVAC UNIT DETAIL
NO SCALE



REGISTER INSTALLATION DETAIL
NO SCALE



ROOF TOP EXHAUST FAN DETAIL
NO SCALE



FLEXIBLE DUCT SUPPORT DETAIL
NO SCALE

DIMENSION OF LONGEST SIDE, INCHES	SHEET METAL GAGE (ALL FOUR SIDES)	TRANSVERSE REINFORCING (1)	
		MINIMUM REINFORCING ANGLE SIZE AND MAXIMUM LONGITUDINAL SPACING BETWEEN TRANSVERSE JOINTS & OR INTERMEDIATE REINFORCING	AT JOINTS
UP THRU 12	26	NONE REQUIRED	26 26
13 - 18	24	NONE REQUIRED	24 24
19 - 30	24	1"x1"x18" @ 60 IN	- 24

(1) TRANSVERSE REINFORCING SIZE IS DETERMINED BY DIMENSION OF SIDE TO WHICH ANGLE IS APPLIED.

METAL FASTENERS - O MARK INSULPINS, DURO DYNE FASTENERS OR GRIPNAILS.

GRIP NAILS SHALL BE INSTALLED BY GRIPNAIL AIR HAMMER OR BY AUTOMATIC FASTENER EQUIP.

ENDS OF LINER SHALL BE BUTTED FIRMLY TOGETHER

NOT MORE THAN 2" FROM EDGE OF LINER

12" OC MAX.

SHEET METAL DUCT

TOP AND BOTTOM SECTION OF LINER SHALL OVERLAP THE SIDES

1" THICK DUCT LINER

ALL ENDS OF LINER TO BE COATED WITH ADHESIVE. SEE SPECIFICATIONS.

LINER TO BE ADHERED TO DUCT W/ 100% ADHESIVE. SEE SPECIFICATIONS.

NO POP RIVETS ALLOWED


SELF-TAPPING CADMIUM PLATED HEX HEAD SHEET METAL SCREW

HANGER STRAPS


HANG DUCTS UP TO 30" WIDTH WITH 1"x18 GAGE STRAPS AT 10'-0" MAXIMUM SPACING.

STRAPS TO BE TIGHT AGAINST DUCTWORK


DUCT CONSTRUCTION AND HANGER DETAIL
NO SCALE




PENTHOUSE DETAIL
NO SCALE



DRYER VENT THRU WALL
NO SCALE



SOUND BOOT DETAIL
NO SCALE



FAN COIL & REFRIGERANT PIPING DETAIL
NO SCALE

07.12.24

DATE: JUL 12, 2024 ISSUE FOR PERMIT

AN ADDITION FOR:
TWIN FALLS COUNTY JAIL
2815 Wright Ave. * Twin Falls, ID 83301
MECHANICAL DETAILS

Laughlin Ricks Architecture
architecture/planning
134 3RD AVE. E. * Twin Falls, Idaho 83301
(208) 736-8050 Fax: (208) 733-0950

Engineered Systems Associates
1355 EAST CENTER
POCATELLO, IDAHO 83201
PHONE: (208) 233-0501
FAX: (208) 233-0529
EMAIL: esa@engsystems.com
ESA JOB NUMBER: 24048


PROFESSIONAL ENGINEER
DAVID L. HANSEN
18184
STATE OF IDAHO
JUL 12, 2024

DATE: 07/12/2024

DESIGNED BY: [Signature]

CHECKED BY: [Signature]

M1A-2.2



PH 1 PART A DEMO PLUMBING FLOOR PLAN
 SCALE: 1/8" = 1'-0"



- PLAN NOTES:**
- 1 SEE SITE PLAN FOR CONTINUATION.
 - 2 EXISTING FIXTURE TO REMAIN. PROTECT DURING CONSTRUCTION. CONTRACTOR SHALL REPLACE ALL GASKETS/SEALS FOR ALL FIXTURES.
 - 3 EXISTING CLEAN OUT TO REMAIN. PROTECT DURING CONSTRUCTION.
 - 4 EXISTING WATER SOFTENER TO REMAIN. PROTECT DURING CONSTRUCTION.
 - 5 EXISTING AIR COMPRESSOR SYSTEM TO REMAIN. PROTECT DURING CONSTRUCTION.
 - 6 REMOVE AND DISPOSE OF EXISTING FIXTURE IN ITS ENTIRETY. CAP WASTE BELOW GRADE AND ABANDON. REMOVE AND DISPOSE OF BRANCH WATER AND VENT BACK TO MAIN AND ABANDON IF APPLICABLE.
 - 7 PROVIDE AND INSTALL NEW WATER HEATER IN PLACE OF OLD. INSTALL WITH NEW BALL VALVE, FLEX PIPING, AND GAS CONNECTIONS. SECURE NEW WATER HEATER EXISTING WALL WITH ANCHOR STRAPS. SEE TYPICAL INSTALL DETAIL. CORRESPONDING TEMPER STATION TO REMAIN.
 - 8 COORDINATE WITH LOCAL GAS COMPANY TO ACCOMMODATE 1,833,000 BTU/H AT 2 PSI OPERATING PRESSURE. REMOVE REGULATOR WITHIN MECHANICAL ROOM FOR 2PSI OPERATING PRESSURE THROUGHOUT THE BUILDING. FIELD VERIFY EXISTING CONDITIONS.
 - 9 ALL EXISTING SPRINKLER HEADS WITHIN BUILDING TO BE REMOVED AND REPLACED WITH NEW TYCO / RAVEN INSTITUTIONAL HEADS. FIELD VERIFY EXISTING CONDITIONS.
 - 10 RELOCATE EXISTING FIRE SPRINKLER HEAD LOCATIONS AS REQUIRED BY NFPA 13 REQUIREMENT FOR REMODELED AREA. ALL RELOCATED FIRE SPRINKLER HEADS TO BE NEW TYCO / RAVEN INSTITUTIONAL TYPE.
 - 11 EXISTING DRYER TO BE REMOVED BY THE GENERAL CONTRACTOR PRIOR TO CONSTRUCTION. REMOVE, DISPOSE OF, AND CAP CORRESPONDING BRANCH GAS PIPING BACK TO MAIN. FIELD VERIFY EXISTING CONDITIONS DURING CONSTRUCTION.
 - 12 ROOF TOP UNIT REPLACEMENT BY DIVISION 23. DISCONNECT GAS PIPING PRIOR TO REMOVAL. PROVIDE AND INSTALL NEW GAS CONNECTION AS PER DETAIL ON SHEET P1A-2.1.
 - 13 NEW ROOF TOP UNIT BY DIVISION 23. PROVIDE AND INSTALL NEW GAS CONNECTION AS PER DETAIL ON SHEET P1A-2.1.
 - 14 EXISTING CEILING ACCESS SECURITY PANEL.
 - 15 EXISTING 140°F HOT WATER LOOP TO BE REMOVED AND DISPOSED OF. CAP AND ABANDON PIPING BACK TO MECHANICAL ROOM AND ABANDON.
 - 16 EXISTING ROOF ACCESS.

- GENERAL NOTES:**
- A. THE CONTRACTOR SHALL CHECK AND VERIFY ALL DIMENSIONS AND CONNECTIONS ON THE JOB SITE. ALL WORK SHALL BE EXECUTED FROM MEASUREMENTS TAKEN AT THE SITE.
 - B. THE PLUMBING CONTRACTOR SHALL BE RESPONSIBLE TO INSURE PROPER CODE CLEARANCES FOR ELECTRICAL AND MECHANICAL ACCESS WHEN INSTALLING ANY EQUIPMENT SUPPLIED BY THE PLUMBING CONTRACTOR.
 - C. IT IS CRITICAL THAT THIS CONTRACTOR COORDINATE EQUIPMENT LOCATIONS WITH PIPING, DUCTWORK, ELECTRICAL CONDUIT AND BUILDING STRUCTURE TO INSURE CODE COMPLIANCE.
 - D. PIPING FROM WATER HEATER TO TERMINATION OF HEATED WATER FIXTURE SUPPLY PIPE SHALL HAVE 1-INCH INSULATION WITH AMINIMUM CONDUCTIVITY OF 0.21 BTU x IN/(HxFT²xF) AS REQUIRED BY IECC C404.4. INSULATION SHALL BE CONTINUOUS EXCEPT WHERE THE PIPE PASSES THROUGH A FRAMING MEMBER OR AT LOCATIONS WHERE A VERTICAL SUPPORT OF THE PIPING IS INSTALLED.
 - E. SEE ARCHITECTURAL PLANS FOR ROOM NAMES AND NUMBERS.

PLUMBING LEGEND	
SYMBOL	DESCRIPTION
V	VENT
VTR	VENT THRU ROOF
CO	CLEANOUT
WCO	WALL CLEANOUT
COTG	CLEANOUT TO GRADE
—	PIPE DROP
—	PIPE RISE
—	BALL TYPE ISOLATION VALVE
—	SOIL OR WASTE PIPING
—	VENT LINE PIPING
—	HARD COLD WATER PIPING
—	DOMESTIC HOT WATER PIPING
—	DOMESTIC HW RECIRC. PIPING
—	DOMESTIC 140°F HW PIPING
—	CONDENSATE DRAIN LINE
—	NATURAL GAS PIPING
—	NATURAL GAS REGULATOR
—	GREASE WASTE
—	PRESSURE REDUCING STATION
—	CONNECTION/DISCONNECTION POINT

Engineered Systems Associates
 1355 EAST CENTER
 POCATELLO, IDAHO 83201
 PHONE: (208) 233-0501
 FAX: (208) 233-0529
 EMAIL: esa@engsystems.com
 ESA JOB NUMBER: 24048


DATE: 07/12/2024
 DRAWN: [Signature] CHECKED: [Signature]

AN ADDITION FOR:
TWIN FALLS COUNTY JAIL
 2815 Wright Ave., Twin Falls, ID 83301
PH 1 PART A DEMO PLUMB. FLOOR PLAN


DATE: 07.12.24
 ISSUE FOR PERMIT

Laughlin Ricks Architecture
 architecture/planning
 134 3RD AVE. E. * Twin Falls, Idaho 83301
 (208) 736-8050 Fax: (208) 733-0950

P1A-1.0



PH 1 PART A PLUMBING FLOOR PLAN
 SCALE: 1/8" = 1'-0"



- PLAN NOTES:**
- SEE SITE PLAN FOR CONTINUATION.
 - EXISTING FIXTURE TO REMAIN. PROTECT DURING CONSTRUCTION. CONTRACTOR SHALL REPLACE ALL GASKETS/SEALS FOR ALL FIXTURES.
 - EXISTING CLEAN OUT TO REMAIN. PROTECT DURING CONSTRUCTION.
 - EXISTING WATER SOFTENER TO REMAIN. PROTECT DURING CONSTRUCTION.
 - EXISTING AIR COMPRESSOR SYSTEM TO REMAIN. PROTECT DURING CONSTRUCTION.
 - SEE LARGE SCALE PLANS ON SHEET P1A-1.2 FOR CONTINUATION.
 - PROVIDE AND INSTALL NEW WATER HEATER IN PLACE OF OLD. INSTALL WITH NEW BALL VALVE, FLEX PIPING, AND GAS CONNECTIONS. SECURE NEW WATER HEATER EXISTING WALL WITH ANCHOR STRAPS. SEE TYPICAL INSTALL DETAIL. CORRESPONDING TEMPER STATION TO REMAIN.
 - COORDINATE WITH LOCAL GAS COMPANY TO ACCOMMODATE 1,833,000 BTU/H AT 2 PSI OPERATING PRESSURE. REMOVE REGULATOR WITHIN MECHANICAL ROOM FOR 2PSI OPERATING PRESSURE THROUGHOUT THE BUILDING. FIELD VERIFY EXISTING CONDITIONS.
 - ALL EXISTING SPRINKLER HEADS WITHIN BUILDING TO BE REMOVED AND REPLACED WITH NEW TYCO / RAVEN INSTITUTIONAL HEADS. FIELD VERIFY EXISTING CONDITIONS.
 - RELOCATE EXISTING FIRE SPRINKLER HEAD LOCATIONS AS REQUIRED BY NFPA 13 REQUIREMENT FOR REMODELED AREA. ALL RELOCATED FIRE SPRINKLER HEADS TO BE NEW TYCO / RAVEN INSTITUTIONAL TYPE.
 - FIRE SPRINKLER PLANS FOR NEW ADDITION VIA DIFFERED SUBMITTAL.
 - ROOF TOP UNIT REPLACEMENT BY DIVISION 23. DISCONNECT GAS PIPING PRIOR TO REMOVAL. PROVIDE AND INSTALL NEW GAS CONNECTION AS PER DETAIL ON SHEET P1A-2.1.
 - NEW ROOF TOP UNIT BY DIVISION 23. PROVIDE AND INSTALL NEW GAS CONNECTION AS PER DETAIL ON SHEET P1A-2.1.
 - EXISTING CEILING ACCESS.
 - CONTRACTOR REQUIRED TO SCOPE EXISTING WASTE LINES PRIOR TO CONSTRUCTION FOR BEST POSSIBLE SAW CUT FOR NEW WASTE LINE. COORDINATE WITH THE GENERAL CONTRACTOR FOR REQUIRED SAW CUT AND REPAIR.
 - ROUTE VENT LINE TO NEAREST EXISTING EQUIVALENT OR LARGER.

DATE: 07.12.24
 ISSUE FOR PERMIT

**AN ADDITION FOR:
 TWIN FALLS COUNTY JAIL
 2815 Wright Ave., Twin Falls, ID 83301
 PH 1 PART A PLUMBING FLOOR PLAN**

GAS LOAD CALCS


RTU 1	110,000 BTU/H
RTU 2	130,000 BTU/H
RTU 3	110,000 BTU/H
RTU 4	110,000 BTU/H
RTU 5	110,000 BTU/H
RTU 6	224,000 BTU/H
RTU 7	130,000 BTU/H
RTU 8	130,000 BTU/H
RTU 9	250,000 BTU/H
WH-1	199,000 BTU/H
DRYERS	330,000 BTU/H
TOTAL GAS LOAD	1,833,000 BTU/H
TOTAL DESIGN LOAD	2,362,000 BTU/H
DESIGNED LENGTH	250 FEET
DISCHARGE PRESSURE	(E) 2 PSI
MAIN GAS PIPE SIZE	(E) 1-1/2"

Laughlin Ricks Architecture
 architecture/planning
 134 3RD AVE. E. * Twin Falls, Idaho 83301
 (208) 736-8050 Fax: (208) 733-0950


Engineered Systems Associates
 1355 EAST CENTER
 POCA TELLO, IDAHO 83201
 PHONE: (208) 233-0501
 FAX: (208) 233-0529
 EMAIL: esa@engsystems.com
 Jul 12, 2024
 ESA JOB NUMBER: 24048

DATE: 07/12/2024
 Drawn: [Signature] Checked: [Signature]


P1A-1.1




**LARGE SCALE RR-32
WASTE & VENT FLOOR PLAN**
SCALE: 1/4" = 1'-0" North




**LARGE SCALE RR-32
WATER FLOOR PLAN**
SCALE: 1/4" = 1'-0" North




LARGE SCALE MEDICAL WASTE & VENT FLOOR PLAN
SCALE: 1/4" = 1'-0" North




LARGE SCALE MEDICAL WATER FLOOR PLAN
SCALE: 1/8" = 1'-0" North




**LARGE SCALE LAUNDRY
WASTE & VENT FLOOR PLAN**
SCALE: 1/4" = 1'-0" North



**LARGE SCALE LAUNDRY
WATER FLOOR PLAN**
SCALE: 1/4" = 1'-0" North



LARGE SCALE RR-2 & 7 WASTE & VENT FLOOR PLAN
SCALE: 1/4" = 1'-0" North



LARGE SCALE RR-2 & 7 WATER FLOOR PLAN
SCALE: 1/4" = 1'-0" North

- PLAN NOTES:**
- SEE SHEET P1A-1.2 FOR CONTINUATION.
 - EXISTING FIXTURE TO REMAIN. PROTECT DURING CONSTRUCTION.
 - EXISTING CLEAN OUT TO REMAIN. PROTECT DURING CONSTRUCTION.
 - ALL EXISTING SPRINKLER HEADS WITHIN BUILDING TO BE REMOVED AND REPLACED WITH NEW TYCO / RAVEN INSTITUTIONAL HEADS. FIELD VERIFY EXISTING CONDITIONS.
 - RELOCATE EXISTING FIRE SPRINKLER HEAD LOCATIONS AS REQUIRED BY NFPA 13 REQUIREMENT FOR REMODELED AREA. ALL RELOCATED FIRE SPRINKLER HEADS TO BE NEW TYCO / RAVEN INSTITUTIONAL TYPE.
 - PIPE 3/4" COPPER COLD WATER LINE DOWN ALONG WALL AND CONNECTED TO WASHER WITH BALL VALVE, UNION, AND FLEX HOSE. FOLLOW WASHER MANUFACTURER RECOMMENDED INSTALL AND MODIFY INSTALL AS REQUIRED.

DATE: JUL 12 2024
ISSUE FOR PERMIT

AN ADDITION FOR:
TWIN FALLS COUNTY JAIL
2815 Wright Ave, Twin Falls, ID 83301
PH 1 PART A PLUMBING FLOOR PLAN


Laughlin Ricks Architecture
—architecture/planning—
134 3RD AVE. E. * Twin Falls, Idaho 83301
(208) 736-8050 Fax: (208) 733-0950

Engineered Systems Associates
1355 EAST CENTER
POCATELLO, IDAHO 83201
PHONE: (208) 233-0501
FAX: (208) 233-0529
EMAIL: esa@engsystems.com
ESA JOB NUMBER: 24048


PROFESSIONAL ENGINEER
DAVID L. HANSEN
18184
STATE OF IDAHO

DATE: 07/12/2024
TJ Drawn
DLH Checked

P1A-1.1




ROOF TOP GAS PRESSURE REGULATOR DETAIL
NO SCALE




CLEAN OUT DETAILS
NO SCALE

FIXTURE SCHEDULE					
SYM.	DESCRIPTION	HOT	COLD	WASTE	VENT
CB-1	CATCH BASIN - SEE DETAIL ON THIS SHEET.	--	--	4"	--
DF-1	BILEVEL ADA DRINKING FOUNTAIN - ELKAY MODEL LZSTL8WSLK WITH BOTTLE FILLER STATION & FILTER FRONT PUSH BAR OPERATORS, 1/2" STOP, 1-1/2" P-TRAP AND FLEX-GUARD SAFETY BUBBLER VALVE.	--	1/2"	1-1/2"	1-1/2"
FD-1	2" FLOOR DRAIN - ZURN Z-415B WITH 5"Ø CHROME-PLATED BRONZE STRAINER, 2" DEEP SEAL P-TRAP, AND TRAP SEAL.	--	--	2"	2"
FD-2	2" FLOOR DRAIN - ZURN Z-415B WITH 5"Ø CHROME-PLATED BRONZE STRAINER.	--	--	2"	2"
FS-1	FLOOR SINK - ZURN Z-1900-KC WITH WHITE ENAMEL FINISH, DOME STRAINER AND 4" DEEP SEAL P-TRAP. PROVIDE 1/2" GRATE OVER SINK.	--	--	3"	2"
HB-1	HOSE BIBB - ZURN MODEL Z1305 "ECOLOTROL" ENCASED & LOCKABLE NON-FREEZE HOSE BIBB. LENGTH TO SUIT WALL THICKNESS.	--	3/4"	--	--
HB-2	HOSE BIBB - SEE DETAIL ON THIS SHEET.	3/4"	3/4"	--	--
L-1	ADA COUNTERTOP LAVATORY - KOHLER MODEL K-2905-4 SELF-RIMMING "FARMINGTON" WITH MOEN L4601 LEVER FAUCET, K-7715 OPEN GRID STRAINER, 1/2" BALL STOPS AND 1-1/2" P-TRAP. INSULATE HOT WATER SUPPLY AND TRAP WITH JACKET.	1/2"	1/2"	1-1/2"	1-1/2"
S-1	SINGLE COMPARTMENT SINK - ELKAY MODEL HDS1516PDK WITH 18 GA TYPE 304 STAINLESS STEEL CONSTRUCTION, 2-HOLE FAUCET DRILLINGS, ELKAY LK2477CR FAUCET, LK-99 STRAINER, 1-1/2" P-TRAP AND 1/2" BALL TYPE STOP VALVES.	1/2"	1/2"	2"	1-1/2"
TD-1	TRENCH DRAIN - ZURN 886-HD 6-3/4" WIDE HEAVY DUTY TRENCH DRAIN SYSTEM WITH 4" END OUTLET, END CAP AND DUCTILE IRON SLOTTED GRATE, LENGTH AS PER FLOOR PLAN.	--	--	4"	--
WC-1	ADA FLUSH VALVE WATER CLOSET - KOHLER K-4368 "HIGHCLIFF" WITH ELONGATED BOWL, K-4670C WHITE OPEN FRONT SEAT, SLOAN REGAL FLUSH VALVE AND BOLT CAPS.	--	1"	4"	2"
WH-1	100 GALLON GAS FIRED WATER HEATER - A.O.SMITH MODEL BTR-199 ATMOSPHERIC WATER HEATER WITH 100 GALLON CAPACITY, 199,000 BTUH, (120/60/1), 1-1/2" SUPPLIES AND T&P RELIEF VALVE.	1-1/2"	1-1/2"	--	--


1 LAVATORYS TO HAVE 2" VENT IF USED AS BATHROOM GROUP WET VENT.



TYPICAL WATER HEATER PIPING DIAGRAM
NO SCALE




INTERIOR HOSE BIBB DETAIL
NO SCALE




GAS LINE CONNECTION DETAIL
NO SCALE

TRENCH SECTIONS		
TRENCH NO. *	SHALLOW INVERT 'A'	DEEP INV. 'B'
40'-0" TRENCH		
8604	5.30'	5.90'
8605	5.90'	6.50'
8606	6.50'	7.10'
8607	7.10'	7.70'
8608	7.70'	8.30'
8609	8.30'	8.90'
54'-4" TRENCH		
8604	5.30'	5.90'
8605	5.90'	6.50'
8606	6.50'	7.10'
8607	7.10'	7.70'
8608	7.70'	8.30'
8609	8.30'	8.90'
8610	8.90'	9.50'
86011	9.50'	10.10'
80'-0" TRENCH		
8604	5.30'	5.90'
8605	5.90'	6.50'
8606	6.50'	7.10'
8607	7.10'	7.70'
8608	7.70'	8.30'
8609	8.30'	8.90'
8610	8.90'	9.50'
86011	9.50'	10.10'
8612	10.10'	10.70'
8613	10.70'	11.30'
8614	11.30'	11.90'
8615	11.90'	12.50'

* TRENCH SECTIONS ARE 80" LONG. DO NOT USE NEUTRAL SECTIONS.




NOTE: ACTUAL CHANNEL LENGTH IS 81-1/4" TO ALLOW FOR OVERLAP.




TRENCH DRAIN INSTALLATION DETAILS
NO SCALE


PLUMBING CONTRACTOR IS RESPONSIBLE FOR CONCRETE ENCASEMENT AND REINFORCING. EXTEND 4" WASTE LINE FROM END OF TRENCH AND CONNECT TO SAND AND GREASE TRAP AS SHOWN ON PLANS. PROVIDE FLOOR CLEAN OUT ON WASTE LINE.




TRAP SEAL INSTALLATION DETAIL
NO SCALE



UNINSULATED PIPE SUPPORT DETAIL
NO SCALE



CATCH BASIN PIPING DETAIL
NO SCALE



EXTERIOR HOSE BIBB DETAIL
NO SCALE

07.12.24

DATE: JUL 12 2024
ISSUE FOR PERMIT

AN ADDITION FOR:
TWIN FALLS COUNTY JAIL
2815 Wright Ave., Twin Falls, ID 83301
PLUMBING SCHEDULES AND DETAILS

Laughlin Ricks Architecture
architecture/planning
134 3RD AVE. E. * Twin Falls, Idaho 83301
(208) 736-8050 Fax: (208) 733-0950

DATE: 07/12/2024
T.D. Drawn: DAH
Checked: [Signature]

Engineered Systems Associates
1355 EAST CENTER
POCATELLO, IDAHO 83201
PHONE: (208) 233-0501
FAX: (208) 233-0529
EMAIL: esa@engsystems.com
ESA JOB NUMBER: 24048

PROFESSIONAL ENGINEER
DAVID L. HANSEN
18184
STATE OF IDAHO
JUL 12 2024

P1A-2.1

LIGHTING SYMBOL SCHEDULE	
NOTE: ALL SYMBOLS MAY NOT BE USED	
SYMBOL	DESCRIPTION
F1	LIGHT FIXTURE TYPE DESIGNATION
	PARKING AREA POLE LIGHT, SINGLE OR DOUBLE HEAD AS INDICATED ON DRAWINGS. REFER TO LIGHT POLE DETAIL FOR POLE INFORMATION.
	EXTERIOR WALL MOUNTED FIXTURE
	2X4 FLUORESCENT OR LED FIXTURE
	2X2 FLUORESCENT OR LED FIXTURE
	SURFACE MOUNTED FLUORESCENT OR LED FIXTURE
	STRIP FLUORESCENT OR LED FIXTURE
	WALL MOUNTED FLUORESCENT OR LED FIXTURE
	ROUND RECESSED FIXTURE
	SURFACE OR PENDANT FIXTURE
	EXIT SIGN, WALL OR CEILING MOUNTING AS REQUIRED (SINGLE OR DOUBLE FACE) DIRECTIONAL CHEVRONS AS INDICATED; CONNECT TO EMERGENCY GENERATOR CIRCUIT.
	WALL OR CEILING MOUNTED EMERGENCY LIGHTING UNIT W/BATTERY PACK CONNECT TO UNSWITCHED LEG OF LIGHTING CIRCUIT THAT IS IN THE SAME AREA AS THE EMERGENCY LIGHT.
	SHADED FIXTURE INDICATES AN EMERGENCY FIXTURE. PROVIDE WITH EMERG. BATTERY PACK OR CONNECT TO EMERGENCY POWER SYSTEM (WHERE APPLICABLE). CONNECT BATTERY PACK TO UNSWITCHED LEG OF LIGHTING CIRCUIT THAT SERVES THE SAME AREA AS THE EMERGENCY FIXTURE. PROVIDE WITH TEST LIGHT AND SWITCH.
	CEILING MOUNTED OCCUPANCY SENSOR. REFER TO OCCUPANCY SENSOR/SWITCH SCHEDULE FOR SENSOR TYPE AND ADDITIONAL INFORMATION.
	SWITCH MOUNTED OCCUPANCY SENSOR, LOW VOLTAGE SWITCHPOD OR DIMMER SWITCH. REFER TO OCCUPANCY SENSOR/SWITCH SCHEDULE FOR TYPE AND ADDITIONAL INFORMATION.
	SINGLE-POLE SWITCH (SEE SUB-SCRIPTS BELOW FOR ADDITIONAL INFORMATION)

LIGHT FIXTURE SUBSCRIPTS	
NL NIGHT-LIGHT(CONNECT TO UNSWITCHED LEG OF CIRCUIT)	
SWITCH SUBSCRIPTS	
3 3-WAY SWITCH	LV LOW-VOLTAGE SWITCH (PER DWGS)
4 4-WAY SWITCH	T THERMAL-OVERLOAD SWITCH
D DIMMER SWITCH (COMPATIBLE W/ LOAD & LTG TYPES)	M SWITCH SUPPLIED WITH EQUIPMENT, INSTALLED BY E.C.
F 7-DAY PROGRAMMABLE TIMER SWITCH (INTERMATIC MODEL E1500WC SERIES)	WP WEATHERPROOF
P PILOT LIGHTED SWITCH	2P DOUBLE POLE, SINGLE THROW SWITCH

CIRCUITING & GENERAL SYMBOL SCHEDULE	
NOTE: ALL SYMBOLS MAY NOT BE USED	
SYMBOL	DESCRIPTION
	KEYED NOTE REFERENCE
1 / ES101	DETAIL # / SHEET REFERENCE
	BRANCH CIRCUIT HOME-RUN TO PANEL INDICATED
	QTY & SIZE OF EQUIPMENT GROUND CONDUCTOR
	QTY & SIZE OF NEUTRAL AND PHASE CONDUCTOR(S)
	SIZE OF CONDUIT
	TICK MARKS
	EQUIPMENT GROUNDING CONDUCTOR
	NEUTRAL CONDUCTOR(S)
	PHASE AND/OR SWITCH-LEG CONDUCTOR(S)
	CALCULATED AVAILABLE FAULT CURRENT AT EQUIPMENT(SEE POWER RISER)
	BRANCH CIRCUIT/FEEDER CONCEALED IN CEILING OR WALL
	BRANCH CIRCUIT/FEEDER CONCEALED UNDERGROUND OR FLOOR
	NEW EQUIPMENT, DEVICES, ETC.
	EXISTING EQUIPMENT, DEVICES, ETC.
	DEMOLITION EQUIPMENT, DEVICES, ETC.

UTILITY LIGHTING REBATES & INCENTIVES:	
IT SHALL BE THE RESPONSIBILITY OF THE ELECTRICAL CONTRACTOR TO PREPARE ALL REQUIRED APPLICATIONS AND INFORMATION REQUIRED TO PROVIDE THE OWNER WITH THE MAXIMUM AMOUNT OF REBATE DOLLARS FROM THE LOCAL UTILITY COMPANY. THE ELECTRICAL CONTRACTOR SHALL SUBMIT VERIFICATION OF THE UTILITY COMPANY PRE-APPLICATION APPROVAL PRIOR TO ORDERING ANY MATERIALS.	
VISIT THE FOLLOWING UTILITY CO. WEBSITES FOR INFORMATION:	
IDAHO POWER CO. WWW.IDAHOPOWER.COM CONTACT: SHELLEY MARTIN (208) 388-5872 OR DAN KUHIL (503) 308-0233 dan.kuhil@evergreen-efficiency.com	ROCKY MOUNTAIN POWER CO. WWW.ROCKYMOUNTAINPOWER.NET CONTACT: DAN KUHIL (503) 308-0233 dan.kuhil@evergreen-efficiency.com

POWER SYMBOL SCHEDULE	
NOTE: ALL SYMBOLS MAY NOT BE USED	
SYMBOL	DESCRIPTION
	ELECTRICAL SWITCHBOARD EQUIPMENT. (SEE POWER RISER AND PANEL SCHEDULES FOR ADDITIONAL INFORMATION)
	DRY-TYPE TRANSFORMER. (SEE POWER RISER FOR ADDITIONAL INFORMATION)
	ELECTRICAL PANELBOARD. (SEE POWER RISER AND PANEL SCHEDULES FOR ADDITIONAL INFORMATION)
	DISCONNECT SWITCH, SIZE/POLES/TYPE AS INDICATED TYPES: 1-NEMA 1, 3R-NEMA 3R, 4X-NEMA 4X
	FUSED DISCONNECT SWITCH, SIZE/POLES/TYPE AS INDICATED TYPES: 1-NEMA 1, 3R-NEMA 3R, 4X-NEMA 4X
	COMBINATION STARTER & FUSED DISCONNECT SWITCH, SIZE/POLES/TYPE AS INDICATED. TYPES: 1-NEMA 1, 3R-NEMA 3R, 4X-NEMA 4X
	JUNCTION BOX CR = CORD REEL; SEE DRAWINGS FOR INFORMATION CD = CORD DROP; SEE DRAWINGS FOR INFORMATION
	EQUIPMENT CONNECTION; COORDINATE CONNECTION WITH EQUIPMENT PRIOR TO ROUGH-IN
	MOTOR CONNECTION
	EXHAUST FAN CONNECTION
	POWER AND/OR DATA SERVICE POLE
	FLOORBOX (SEE FLOORBOX SCHEDULE FOR ADDITIONAL INFORMATION)
	PUSHBUTTON STATION
	SPECIAL RECEPTACLE (COORDINATE NEMA TYPE WITH EQUIP.) (REFER TO PANEL SCHEDULES FOR AMPS)
	CEILING MOUNTED DUPLEX RECEPTACLE (COORDINATE PLACEMENT WITH CEILING EQUIPMENT PRIOR TO ROUGH-IN)
	DUPLEX RECEPTACLE, UL TAMPER-RESISTANT WHERE MOUNTED BELOW 5FT
	GFCI-TYPE DUPLEX RECEPTACLE, UL TAMPER-RESISTANT WHERE MOUNTED BELOW 5FT
	SPLIT-WIRED RECEPTACLE, HALF OF RECEPT. SHALL BE SWITCHED OTHER HALF SHALL HAVE CONSTANT POWER.
	DOUBLE-DUPLEX RECEPTACLE, UL TAMPER-RESISTANT WHERE MOUNTED BELOW 5FT
	GFCI-TYPE DOUBLE DUPLEX RECEPTACLE, UL TAMPER-RESISTANT WHERE MOUNTED BELOW 5FT.

RECEPTACLE AND EQUIPMENT SUBSCRIPTS	
AC ABOVE COUNTER	E "RED" RECEPTACLE CONNECTED TO EMERG. POWER SYSTEM
WP WEATHERPROOF (UL LISTED WEATHER-RESISTANT)	D CLOTHES DRYER (NEMA 14-30R)
42" MOUNTING HEIGHT AFF OR AFG	R ELECTRIC RANGE (NEMA 14-50R)
REF REFRIGERATOR	W WELDER RECEPTACLE
M MICROWAVE	208/240V - NEMA 6-50R
M/R MICROWAVE RANGE HOOD (LOCATE ABOVE RANGE)	
USB DUPLEX REPT. WITH (2) USB CHARGING PORTS	
DW DISHWASHER, INSTALL PER NEC 422.16(B)(2)	
D/W DISPOSAL/DISHWASHER, INSTALL PER NEC 422.16(B)(2)	
TV RECEPT. DEDICATED TO TV	
FIELD VERIFY HEIGHT W/ TV PRIOR TO ROUGH-IN.	
EW/C ELECTRIC WATER COOLER	
PROVIDE GFCI PROTECTION PER NEC 422.5(A)	

PROJECT GENERAL NOTES:	
A.	E.C. SHALL REFER TO THE MECHANICAL DRAWINGS FOR EXACT LOCATIONS OF ALL MECHANICAL EQUIPMENT AND ELECTRICAL CONNECTIONS.
B.	E.C. SHALL PROVIDE MINIMUM WORKING CLEARANCE AS PER NEC BEFORE INSTALLING ANY ELECTRICAL PANELS OR CABINETS. SEE ELECTRICAL EQUIPMENT CLEARANCE DETAIL.
C.	INSTALL ALL LIGHT FIXTURES IN MECHANICAL ROOM AFTER THE MECHANICAL EQUIPMENT IS IN PLACE. ADJUST AS NECESSARY. PROVIDE CHAIN SUSPENSION KITS AS REQUIRED.
D.	REFER TO ARCHITECTURAL REFLECTED CEILING PLANS (R) FOR EXACT FIXTURE LOCATIONS, CEILING TYPES, ETC.
E.	E.C. SHALL PROVIDE ALL CONCRETE PADS AS REQUIRED FOR ALL ELECTRICAL EQUIPMENT.
F.	CONFIRM EXACT LOCATIONS OF ALL TELEPHONE/DATA OUTLETS WITH OWNER PRIOR TO ROUGH-IN.
G.	LOCATE SWITCHES, OUTLETS, ETC., SHOWN AT ROOM ENTRY DOORWAYS, AS CLOSE TO DOOR FRAME AS POSSIBLE, SO AS NOT TO INTERFERE WITH ROOM CABINETS, ETC.
H.	SUPPORT ALL LIGHT FIXTURES INDEPENDENT OF CEILING.
I.	ELECTRICAL CONTRACTOR SHALL OBTAIN ALL APPLICABLE PERMITS FOR WORK AND PAY ASSOCIATED FEES.
J.	MAINTAIN 24" MIN. CLEARANCE FROM ALL COMMUNICATIONS CABLING AND ELECTRONIC BALLASTS. UNLESS SPECIFICALLY INDICATED OTHERWISE, E.C. SHALL COORDINATE WITH ANY SPECIAL SYSTEMS SUPPLIER/SHOP DRAWINGS; DENTAL, MEDICAL, KITCHEN, SPECIALIZED EQUIPMENT, ETC. FOR THE EXACT ROUGH-IN REQUIREMENTS FOR THEIR EQUIPMENT. ALSO UNLESS INDICATED OTHERWISE, THE E.C. TO BE RESPONSIBLE FOR FINAL ELECTRICAL CONNECTIONS TO ALL SPECIAL EQUIPMENT.
L.	ALL CONDUIT/RACEWAY/CABLES TO BE CONCEALED IN WALLS OR ABOVE CEILINGS. IF ANY SURFACE WORK IS NECESSARY, IT SHALL BE APPROVED BY THE ARCHITECT/ENGINEER PRIOR TO INSTALLATION.
M.	ELECTRICAL CONTRACTOR SHALL VISIT THE SITE PRIOR TO BID AND THOROUGHLY INVESTIGATE THE EXISTING CONDITIONS, AS THEY RELATE TO THE SCOPE OF WORK DESCRIBED. MAKE NECESSARY PROVISIONS IN THE BASE BID TO ADEQUATELY ACCOMMODATE THESE CONDITIONS.
N.	DATA CABLING SYSTEM PRE-INSTALLATION CONFERENCE: 1. E.C. SHALL SCHEDULE A MEETING A MINIMUM OF FIVE CALENDAR DAYS PRIOR TO BEGINNING DATA CABLING INSTALLATION. ATTENDEES SHOULD INCLUDE OWNER'S REP., ENGINEER, GC, EC AND CABLING SUB. REFER TO SECTION 26 2812(1.4)(E) FOR ADDITIONAL INFORMATION.


SPECIAL SYSTEMS SYMBOL SCHEDULE	
NOTE: ALL SYMBOLS MAY NOT BE USED	
SYMBOL	DESCRIPTION
	DATA OUTLET; = # OF DATA CABLES, X=CONDUIT SIZE (SEE NOTES 1,2,3 BELOW)
	CEILING MOUNTED DATA OUTLET; = # OF DATA CABLES, X=CONDUIT SIZE (SEE NOTES 1,2,3 BELOW)
	TELEPHONE OUTLET; = # OF TELEPHONE CABLES, X=CONDUIT SIZE (SEE NOTES 1,2,3 BELOW)
	TELEPHONE/DATA OUTLET; = # OF TELEPHONE/DATA CABLES, X=CONDUIT SIZE (SEE NOTES 1,2,3 BELOW)
	ELECTRICAL FLOORBOX REFER TO "ELECTRICAL FLOORBOX SCHEDULE" FOR INFORMATION. = # OF DATA CABLES, X=CONDUIT SIZE (SEE NOTES 1,2,3 BELOW)
	TV AND/OR AV BOX; WITH POWER, DATA AND/OR AV CONNECTIVITY ### = BOX ID; REFER TO "ELECTRICAL AV/TV BOX SCHEDULE" FOR INFORMATION. = # OF DATA CABLES, X=CONDUIT SIZE (SEE NOTE #2 BELOW) INSTALL CONDUIT (SIZE AS INDICATED) FROM BOX TO NEAREST ACCESSIBLE CEILING SPACE W/ DATA CABLING/TERMINATIONS AS INDICATED ON DRAWINGS.
	WALL FLOOR ELECTRICAL PATHWAY SLEEVE; INSTALL THROUGH WALL OR FLOOR AS INDICATED. SLEEVES SHALL BE ABOVE ACCESSIBLE CEILINGS IN ACCESSIBLE LOCATION. FIELD VERIFY EXACT LOCATION TO AVOID CONFLICT WITH OTHER TRADES AND UTILITIES. IF WALL/FLOOR IS NOT FIRE RATED E.C. MAY UTILIZED EMT CONDUIT SLEEVES OF EQUAL SIZE. REFER TO ARCHITECTURAL DRAWINGS FOR FIRE RATINGS. (qty) = QUANTITY OF SLEEVES AT LOCATION EP2 = 2" HILTI SPEED SLEEVE CP-653-BA EP4 = 4" HILTI SPEED SLEEVE CP-653-BA

SPECIAL SYSTEMS NOTES:	
1.	UTILIZE 4 1 1/16" DEEP BOX WITH REQUIRED MUDRING AND CONDUIT TO ABOVE NEAREST ACCESSIBLE CEILING OR DATA RACK, TERMINATE WITH INSULATED THROAT BUSHING. PROVIDE QTY OF CABLES INDICATED FROM OUTLET TO NEAREST TELE/DATA ROOM. SEE DWGS FOR ADDITIONAL INFORMATION. UTILIZE J-HOOKS 3FT ON CENTER FOR SUPPORT OF CABLING WHERE CABLE TRAY IS NOT INSTALLED/SPECIFIED.
2.	CONDUIT SIZE (X FROM ABOVE); 2=1/2", 3=3/4", 4=1", 5=1-1/4", 6=1-1/2"
3.	BLANK (NO LABEL) = 4 1 1/16" DEEP BOX WITH REQUIRED MUDRING AND 1" CONDUIT TO ABOVE NEAREST ACCESSIBLE CEILING/CABLE TRAY. TERMINATE WITH INSULATED THROAT BUSHING, PROVIDE PULL STRING. (UNLESS OTHERWISE NOTED)


GENERAL SPECIAL SYSTEM NOTES:	
A.	COMMUNICATIONS CABLES SHALL HAVE BENDS NO GREATER THAN 90 DEG.
B.	CONDUITS FOR COMMUNICATIONS CABLING SHALL HAVE A MAXIMUM BEND RADIUS NOT MORE THAN 10X THE DIAMETER OF THE CONDUIT.
C.	ALL COMMUNICATIONS CONDUITS SHALL BE TERMINATED WITH AN INSULATED NON-METALLIC BUSHING AT BOTH ENDS.
D.	COMMUNICATIONS CONDUITS SHALL HAVE NO MORE THAN (2) 90'S WITHOUT A PULLBOX. PULL BOXES SHALL BE LOCATED IN ACCESSIBLE LOCATIONS AND SHALL BE SIZED AT LEAST 12X THE LARGEST CONDUIT DIAMETER IN LENGTH AND MIN. 4" DEEP AND 8" WIDE.
E.	IT SHALL BE THE RESPONSIBILITY OF THE E.C. TO INSURE THAT THE PATHWAY FOR THE DATA CABLING DOES NOT CREATE CABLE LENGTHS THAT EXCEEDS THE LENGTH OF 295FT FROM OUTLET TO PATCH PANEL. THIS INCLUDES SERVICE LOOPS AND PATCH CORDS.
F.	WHERE CABLE TRAY IS UTILIZED IN THE PROJECT, COMMUNICATION CONDUITS ENDING AT THE CABLE TRAY SHALL EXTEND 1" OVER THE SIDE INTO THE TRAY.

FIRE ALARM SYMBOL SCHEDULE	
NOTE: ALL SYMBOLS MAY NOT BE USED	
SYMBOL	DESCRIPTION
	FIRE ALARM CONTROL PANEL (WALL MOUNTED, TOP AT 6'-0" AFF)
	NOTIFICATION DEVICE EXTENDER PANEL. PROVIDE QTY AS REQUIRED BASED ON DEVICE VOLTAGE DROP CALC'S PER NFPA 72 REQUIREMENTS. (WALL MOUNTED, TOP AT 5'-0" AFF)
	REMOTE ANNUCIATOR PANEL (FLUSH MOUNTED IN WALL AT 5'-0" AFF)
	MANUAL PULL STATION (MOUNTING HEIGHT PER ADA & NFPA 72)
	MAGNETIC DOOR HOLD OPEN
	ADDRESSABLE CONTROL/RELAY MODULE
	ADDRESSABLE MONITORING MODULE
	FIRE ALARM FLOW SWITCH
	FIRE ALARM TAMPER SWITCH
	FIRE ALARM SMOKE DAMPER
	ADDRESSABLE DETECTOR WITH BASE
DETECTOR SUBSCRIPTS	
P PHOTOELECTRIC SMOKE DETECTOR	D DUCT SMOKE DETECTOR
I IN-DUCT SMOKE DETECTOR	H HEAT DETECTOR
M MULTI-STATION SMOKE DETECTOR (120V W/BATTERY BACKUP)	
MS MULTI-STATION SMOKE DETECTOR W/VISIBLE STROBE (120V W/BATTERY BACKUP)	
MC MULTI-STATION SMOKE/ CARBON MONOXIDE DETECTOR (120V W/BATTERY BACKUP)	
	FIRE/SMOKE DAMPER; COORDINATE LOCATIONS WITH MECH. DRAWINGS
	EXTERIOR 120V FIRE BELL, INSTALL NEXT TO FDC.
	WALL OR CEILING MOUNTED FIRE ALARM HORN ONLY
	WALL MOUNTED FIRE ALARM STROBE OR HORN/STROBE PROVIDE CANDELA RATING AS REQUIRED BY NFPA 72
	CEILING MOUNTED FIRE ALARM STROBE OR HORN/STROBE PROVIDE CANDELA RATING AS REQUIRED BY NFPA 72

GENERAL FIRE ALARM SYSTEM NOTES:	
A.	DO NOT INSTALL MORE THAN (10) NOTIFICATION APPLIANCES ON ANY SINGLE CLASS "A" SIGNAL CIRCUIT. DO NOT EXCEED 400 FT. OF NO. 14 WIRE IN THE TOTAL LOOP.
B.	NFPA ALLOWS NOTIFICATION APPLIANCES TO BE MOUNTED AT A HEIGHT RANGE BETWEEN 80" TO 96" ABOVE FINISH FLOOR. THE PREFERRED HEIGHT IS 80" IF THIS CONFLICTS WITH OTHER TRADES OR ROOM FURNISHINGS, LOCATE AS CLOSE TO 80" AS POSSIBLE. NOT EXCEEDING 96". ALL NOTIFICATION APPLIANCES IN A COMMON ROOM OR LINE OF SIGHT SHALL BE LOCATED AT A COMMON HEIGHT.
C.	MOUNT PULL STATIONS AT 48-48" A.F.F. TO THE OPERATING HANDLE TO MEET ADA REQUIREMENTS.
D.	DO NOT CONNECT THE FIRE ALARM SYSTEM TO ANY DEVICE WHICH HAS A POWER HELD CONTACTS (FLOW, TAMPER, HOOD SYSTEM, DUCT DETECTOR, ETC. FALSE ALARM WILL OCCUR.
E.	ELECTRICAL CONTRACTOR SHALL SUPPLY AND INSTALL CONDUCTOR QUANTITIES PER FIRE ALARM SYSTEM SUPPLIER, AND AS PER NFPA AND NEC REQUIREMENTS.
F.	DO NOT INSTALL ANY SMOKE OR HEAT DETECTORS WITHIN 3 FEET OF ANY AIR DIFFUSER.
G.	DO NOT EXCEED 2500 FEET ON ANY ADDRESSABLE DEVICE RUN. DO NOT EXCEED 120 DEVICES ON ANY ONE ADDRESSABLE DEVICE RUN.
H.	ALL AIR HANDLING EQUIPMENT 2000 CFM OR MORE MUST BE SHUT DOWN UPON FIRE ALARM AS PER LIFE SAFETY CODES.
I.	ALL CLASS "B" INITIATING CIRCUITS WITH ADDRESSABLE DEVICES NEED EOLR (END OF LINE RESISTORS).
J.	IN CORRIDORS, NOTIFICATION APPLIANCES MUST BE LOCATED WITHIN 15' FROM ENDS OF CORRIDORS AND A MAXIMUM OF 100' SPACING.
K.	NOTIFICATION APPLIANCES TO BE SYNCHRONIZED TO PROVIDE A 3-3-3 TEMPORAL PATTERN.
L.	ALL WIRING AND CONDUIT ROUTING TO BE AS DESCRIBED ON SUPPLIED SHOP DRAWINGS. FIRE ALARM PLAN IS SHOWN FOR GENERAL LOCATION AND LAYOUT ONLY.
M.	THE FIRE ALARM SYSTEM TO BE IN COMPLIANCE WITH ALL APPLICABLE LOCAL, STATE AND ADA REQUIREMENTS.
N.	ELECT. CONTR. TO CONNECT SPRINKLER SYSTEM TAMPER SWITCHES AND FLOW VALVES TO FIRE ALARM SYSTEM AS REQUIRED. SEE FIRE SPRINKLER SYSTEM DRAWINGS FOR EXACT LOCATIONS AND QUANTITIES.



ABBREVIATIONS			
P	SINGLE POLE	V	KILOVOLT
1PH	SINGLE-PHASE	KVA	KILOVOLT AMPERE
2C	TWO-CONDUCTOR	KW	KILOWATT
3C	THREE-CONDUCTOR	KWh	KILOWATT HOUR
3P	THREE POLE	LED	LIGHT EMITTING DIODE
3PH	THREE-PHASE	LFMC	LIQUID TIGHT FLEXIBLE METAL CONDUIT
3W	THREE-WIRE	LFNC	LIQUID TIGHT FLEXIBLE NONMETALLIC CONDUIT
4W	FOUR-WIRE	LTG	LIGHTING
AC	ABOVE COUNTER	LV	LOW VOLTAGE
ADA	AMERICANS WITH DISABILITIES ACT	MAX	MAXIMUM
AFF	ABOVE FINISHED FLOOR	M.C.	MECH. CONTRACTOR
AFG	ABOVE FINISHED GRADE	MCA	MINIMUM CIRCUIT AMPS
AIC	AMPERE INTERRUPTING CAPACITY	MCB	MAIN CIRCUIT BREAKER
AL	ALUMINUM	MCC	MOTOR CONTROL CENTER
A or AMP	AMPERE	MDP	MAIN DISTRIBUTION PANEL
ANN	ANNUNCIATOR	MH	MANHOLE
ANN	ACCESS POINT (WIRELESS DATA)	MIN	MINIMUM
ATS	AUTOMATIC TRANSFER SWITCH	ML	MAIN LUGS ONLY
AV	AUDIO VISUAL	MOC	MAXIMUM OVERCURRENT PROTECTION
AWG	AMERICAN WIRE GAGE	NA	NOT APPLICABLE
BFG	BELOW FINISHED GRADE	NC	NORMALLY CLOSED
C	CEILING MOUNTED	NEC	NATIONAL ELECTRICAL CODE
CATV	CABLE TELEVISION	NEMA	NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION
CB	CIRCUIT BREAKER	NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
CCTV	CLOSED CIRCUIT TELEVISION	NIC	NOT IN CONTRACT
CKT	CIRCUIT	NL	NIGHT LIGHT
C	CONDUIT	NO	NORMALLY OPEN
CP	CONTROL PANEL	NTS	NOT TO SCALE
CT	CURRENT TRANSFORMER	OC	ON CENTER
CU	COPPER	OC	ON CENTER
DS	DISCONNECT SWITCH	OL	OVERLOAD
EA	EACH	OP	OVERCURRENT PROTECTION SIZE
E.C.	ELECTRICAL CONTRACTOR	OL	OVERLOAD
EM	EMERGENCY	PB	PUSHBUTTON
EMT	ELECTRICAL METALLIC TUBING	P	PHASE
ENT	ELECTRICAL NONMETALLIC TUBING	PNL	PANEL
EPO	EMERGENCY POWER OFF EQUIPMENT	PT	POTENTIAL TRANSFORMER
EQUIP	EQUIPMENT	PTZ	PAN/TILT/ZOOM
EX	EXISTING	QTY	QUANTITY
FA	FIRE ALARM	RCP	REFLECTED CEILING PLAN
FACP	FIRE ALARM CONTROL PANEL	RMC	RIGID METAL CONDUIT
FLA	FULL LOAD AMPS	RNC	RIGID NONMETALLIC CONDUIT
FMC	FLEXIBLE METAL CONDUIT	SCA	SHORT CIRCUIT AMPS
GND	GROUND	SCBA	STANDARD COLOR BY ARCHITECT
G.C.	GENERAL CONTRACTOR	SF	SQUARE FOOT (FEET)
GEN	GENERATOR	SP	SURGE PROTECTION DEVICE
GFI	GROUND FAULT CIRCUIT INTERRUPTER	SPEC	SPECIFICATION
GFP	GROUND FAULT PROTECTION	SWBD	SWITCHBOARD
HD	HEAVY DUTY	SWG	SWITCHGEAR
HID	HIGH INTENSITY DISCHARGE	TL	TWIST LOCK
HOA	HAND-OFF-AUTOMATIC	TP	TWISTED PAIR
HP	HORSE POWER	TTB	TELEPHONE TERMINAL BOARD
HPS	HIGH PRESSURE SODIUM	TV	TELEVISION
HV	HIGH VOLTAGE	TYP	TYPICAL
HZ	HERTZ	UG	UNDERGROUND
IG	ISOLATED GROUND	UPS	UNINTERRUPTIBLE POWER SUPPLY
IMC	INTERMEDIATE METAL CONDUIT	V	VOLTS
J-BOX	JUNCTION BOX	VA	VOLT AMPERE
		V.I.F.	VERIFY IN FIELD
		VFD	VARIABLE FREQUENCY DRIVE
		WAP	WIRELESS ACCESS POINT
		W/	WITH
		W/O	WITHOUT
		WP	WEATHERPROOF
		XFMR	TRANSFORMER




GENERAL NOTES:	
A.	ALL WORKING SPACE CLEARANCES ARE FROM THE FACE OF THE EQUIPMENT.


NOTES:	
1.	THE MINIMUM HEADROOM OF WORKING SPACE SHALL BE 6 1/2FT.
2.	THE WIDTH OF THE WORKING SPACE SHALL BE THE WIDTH OF THE EQUIPMENT OR 30", WHICHEVER IS GREATER. THE PANEL DOOR SHALL OPEN AT LEAST 90 DEGREES.
3.	ALL CIRCUIT BREAKERS, WHEN IN THEIR HIGHEST POSITION, SHALL NOT BE MORE THAN 6FT 7 IN. ABOVE THE FINISHED FLOOR.
4.	3FT CLEARANCE IF 0-150V TO GROUND, 3.5FT CLEARANCE IF 151-600V TO GROUND, 4FT IF EXPOSED LIVE PARTS ON BOTH SIDES OF THE WORKING SPACE.

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2915 Wright Ave., Twin Falls, ID 83401
ELECTRICAL SYMBOLS & DETAILS



Laughlin Ricks Architecture
architecture/planning
134 3RD AVE. E. # Twin Falls, Idaho 83301
PHONE: (208) 756-8050

DATE: 7.12.24	
SAM Drawn	TEP Checked
#23029	PROJECT #
E1A-0.0	






1 EXISTING - ELECTRICAL SITE PLAN
SCALE: 1" = 20'-0"



2 NEW - ELECTRICAL SITE PLAN
SCALE: 1" = 20'-0"



GENERAL NOTES:


A. REFER TO SYMBOL SCHEDULE SHEET FOR PROJECT GENERAL NOTES AND GENERAL NOTES ASSOCIATED WITH THE INSTALLATION OF EACH SYSTEM, INCLUDING BUT NOT LIMITED TO: LIGHTING, POWER, FIRE ALARM, SPECIAL SYSTEMS, ETC.

KEY NOTES:

- 1 E.C. SHALL DISCONNECT AND REMOVE EXISTING POLE LIGHT HEAD AND REPLACE WITH NEW AS INDICATED ON NEW DRAWING. FIELD VERIFY NEW HEAD IS COMPATIBLE WITH EXISTING POLE PRIOR TO ORDERING.
- 2 EXISTING POLE LIGHT AND BASE TO BE DISCONNECTED AND REMOVED IN ITS ENTIRETY. EXISTING LIGHTING CIRCUIT SHALL BE MAINTAINED FOR CONNECTION TO NEW LIGHTING AS INDICATED ON NEW DRAWINGS. INSTALL IN-GRADE J-BOXES AS REQUIRED FOR SPLICING AND EXTENDING EXISTING CIRCUIT TO NEW POLE LIGHT LOCATIONS.
- 3 EXISTING MOTORIZED GATE TO BE DISCONNECTED AND REMOVED IN ITS ENTIRETY. E.C. SHALL MAINTAIN EXISTING UNDERGROUND CONDUITS FOR FUTURE USE AND STUB INTO NEW IN-GRADE, FIBERGLASS J-BOX WITH LID LABELED "ELECTRICAL". INSTALL LID FLUSH WITH FINISH. LOCATE BOX IN LANDSCAPE AREA THAT IS NOT IN CONFLICT WITH NEW CONSTRUCTION. COORDINATE WITH OWNER.
- 4 EXISTING SECURITY INTERCOM PEDESTAL TO BE DISCONNECTED AND REMOVED IN ITS ENTIRETY. E.C. SHALL MAINTAIN EXISTING UNDERGROUND CONDUITS FOR FUTURE USE AND STUB INTO NEW IN-GRADE, FIBERGLASS J-BOX WITH LID LABELED "ELECTRICAL". INSTALL LID FLUSH WITH FINISHED GRADE AND PROVIDE CRUSHED GRAVEL IN BOTTOM FOR DRAINAGE.
- 5 INSTALL NEW HEAD ON EXISTING POLE; CONNECT TO EXISTING CIRCUIT AND CONTROLS. FIELD VERIFY COMPATIBILITY OF HEAD AND EXISTING POLE PRIOR TO ORDERING FIXTURE.

PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
ELECTRICAL SITE PLAN


Laughlin Ricks Architecture
—
architecture/planning
134 3RD AVE. E. # Twin Falls, Idaho 83301
PHONE: (208) 756-8050




PROJECT #: 2496
IPAYNE
Engineering Inc.
1823 E. Center
Pocatello, Idaho 83201
tel (208) 232-4439
www.payneengineeringinc.com

DATE: 7.12.24
SAM Drawn
TEP Checked
#23029
PROJECT #

E1A-0.1



1 EXISTING LIGHTING PLAN
SCALE: 1/8" = 1'-0"



GENERAL NOTES:

- A. ALL EXISTING ELECTRICAL MAY NOT APPEAR ON THESE PLANS, HOWEVER THE ABOVE INFORMATION APPLIES.
- B. PROVIDE AND INSTALL BLANK COVERS ON ALL UNUSED SWITCH/OUTLET/J-BOXES WHERE REQUIRED.
- C. ALL WALL DEVICES THAT ARE EXISTING TO REMAIN, SHALL BE ADAPTED TO NEW WALL COVERINGS. REFER TO ARCHITECTURAL DRAWINGS FOR EXACT WALL LOCATIONS, THICKNESS, ETC.
- D. PRIOR TO THE START OF ANY DEMOLITION WORK, DISCONNECTING ANY POWER AND OR TELE/DATA SYSTEMS, THE CONTRACTOR SHALL COORDINATE DOWN-TIME WITH THE OWNER.
- E. REFER TO ARCHITECTURAL PLANS FOR EXTENT OF DEMOLITION, DETAILS, ETC.
- F. REMOVE OR RELOCATE ELECTRICAL AS NECESSARY FOR NEW WORK.
- G. WHERE EXISTING CIRCUITS ARE TO BE RE-USED, EXTEND AS NECESSARY. MAINTAIN ELECTRICAL CONTINUITY TO DOWNSTREAM EQUIPMENT TO REMAIN.
- H. EXISTING SHOWN TO REMAIN, MAY NEED TO BE REMOVED AND RE-INSTALLED ONLY AS NECESSARY FOR EXTENDING OR MODIFICATION OF EXISTING CIRCUITS OR WIRING.
- I. REFER TO MECHANICAL PLANS FOR EXTENT OF MECHANICAL EQUIPMENT TO BE REMOVED OR RELOCATED.
- J. REMOVE ALL UNUSED EQUIPMENT WIRING, CONDUIT AND BOXES IN ALL AREAS. ABANDON ONLY IN CONCEALED AREAS.
- K. CONTRACTOR MY UTILIZE ANY EXISTING CONDUIT WHERE COMPATIBLE WITH NEW DESIGN, AND IF IN GOOD CONDITION AND COMPLIES WITH SPECIFICATIONS.
- L. WHEN ANY MODIFICATIONS ARE MADE TO ANY EXISTING ELECTRICAL PANEL TO REMAIN, CONTRACTOR TO PROVIDE NEW TYPE WRITTEN INDEX TO REFLECT ALL NEW AND EXISTING LOADS.
- M. REMOVE ALL EQUIPMENT, RACEWAYS, CABLES, ETC. NOT USED IN FINISHED AREAS.

KEY NOTES:

- 1 EXISTING LIGHTING FIXTURES IN THIS AREA SHALL BE DISCONNECTED/REMOVED AND REPLACED WITH NEW. EXISTING CIRCUIT/CONTROLS SHALL BE MAINTAINED FOR CONNECTION TO NEW LIGHT FIXTURE. E.C. SHALL REMOVE AN EXISTING FIXTURE AND FIELD INVESTIGATE EXISTING ELECTRICAL ROUGH-IN CONDITIONS AND VERIFY NEW FIXTURE IS COMPATIBLE PRIOR TO ORDERING ANY NEW FIXTURES.
- 2 EXISTING LIGHTING FIXTURES AND CONTROLS IN THIS AREA SHALL BE DISCONNECTED/REMOVED AND REPLACED WITH NEW AS INDICATED ON NEW LIGHTING PLAN. LOCATE AND MAINTAIN EXISTING LIGHTING CIRCUIT(S) IN AREA FOR USE FOR NEW LIGHTING.
- 3 EXISTING EXTERIOR LIGHTING FIXTURE SHALL BE DISCONNECTED/REMOVED AND REPLACED WITH NEW. EXISTING CIRCUIT/CONTROLS SHALL BE MAINTAINED FOR CONNECTION TO NEW LIGHT FIXTURE. E.C. SHALL REMOVE AN EXISTING FIXTURE AND FIELD INVESTIGATE EXISTING ELECTRICAL ROUGH-IN CONDITIONS AND VERIFY NEW FIXTURE IS COMPATIBLE PRIOR TO ORDERING ANY NEW FIXTURES.
- 4 EXISTING EXTERIOR LIGHTING FIXTURE SHALL BE DISCONNECTED/REMOVED TO ACCOMMODATE NEW CONSTRUCTION. E.C. SHALL RE-ESTABLISH/MAINTAIN CONTINUITY TO ALL DOWNSTREAM LIGHTING THAT IS TO REMAIN.


DATE _____

DATE _____


PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
EXISTING LIGHTING PLAN

Laughlin Ricks Architecture
architecture/planning
134 3RD AVE. E. # Twin Falls, Idaho 83301
PHONE: (208) 756-8050

DATE: 7.12.24
SAM Drawn TEP Checked
#23029 PROJECT #
E1A-0.2



PROJECT #: 2496
IPAYNE
Engineering Inc.
1823 E. Center
Pocatello, Idaho 83201
tel (208) 232-4439
www.payneengineeringinc.com



GENERAL NOTES:

- A. ALL EXISTING ELECTRICAL MAY NOT APPEAR ON THESE PLANS, HOWEVER THE ABOVE INFORMATION APPLIES.
- B. PROVIDE AND INSTALL BLANK COVERS ON ALL UNUSED SWITCH/OUTLET/J-BOXES WHERE REQUIRED.
- C. ALL WALL DEVICES THAT ARE EXISTING TO REMAIN, SHALL BE ADAPTED TO NEW WALL COVERINGS, REFER TO ARCHITECTURAL DRAWINGS FOR EXACT WALL LOCATIONS, THICKNESS, ETC.
- D. PRIOR TO THE START OF ANY DEMOLITION WORK, DISCONNECTING ANY POWER AND OR TELE/DATA SYSTEMS, THE CONTRACTOR SHALL COORDINATE DOWN-TIME WITH THE OWNER.
- E. REFER TO ARCHITECTURAL PLANS FOR EXTENT OF DEMOLITION, DETAILS, ETC.
- F. REMOVE OR RELOCATE ELECTRICAL AS NECESSARY FOR NEW WORK.
- G. WHERE EXISTING CIRCUITS ARE TO BE RE-USED, EXTEND AS NECESSARY, MAINTAIN ELECTRICAL CONTINUITY TO DOWNSTREAM EQUIPMENT TO REMAIN.
- H. EXISTING SHOWN TO REMAIN, MAY NEED TO BE REMOVED AND RE-INSTALLED ONLY AS NECESSARY FOR EXTENDING OR MODIFICATION OF EXISTING CIRCUITS OR WIRING.
- I. REFER TO MECHANICAL PLANS FOR EXTENT OF MECHANICAL EQUIPMENT TO BE REMOVED OR RELOCATED.
- J. REMOVE ALL UNUSED EQUIPMENT WIRING, CONDUIT AND BOXES IN ALL AREAS. ABANDON ONLY IN CONCEALED AREAS.
- K. CONTRACTOR MY UTILIZE ANY EXISTING CONDUIT WHERE COMPATIBLE WITH NEW DESIGN, AND IF IN GOOD CONDITION AND COMPLIES WITH SPECIFICATIONS.
- L. WHEN ANY MODIFICATIONS ARE MADE TO ANY EXISTING ELECTRICAL PANEL TO REMAIN, CONTRACTOR TO PROVIDE NEW TYPE WRITTEN INDEX TO REFLECT ALL NEW AND EXISTING LOADS.
- M. REMOVE ALL EQUIPMENT, RACEWAYS, CABLES, ETC. NOT USED IN FINISHED AREAS.

SPECIAL DEMOLITION NOTES:

- A. THE FOLLOWING SYSTEMS SHALL BE REMOVED IN THEIR ENTIRETY THROUGHOUT THE BUILDING AND REPLACED WITH NEW AS INDICATED IN DRAWINGS. ALL ASSOCIATED CABLING, CONDUIT, BOXES, DEVICES, HEAD-END EQUIPMENT ETC. SHALL BE REMOVED.
 - FIRE ALARM SYSTEM
 - TELEPHONE/DATA CABLING SYSTEM
 - SECURITY SYSTEMS (CCTV, INTERCOM, ACCESS CONTROL)

KEY NOTES:

- 1 E.C. SHALL DISCONNECT AND REMOVED EXISTING EMERGENCY GENERATOR, TRANSFER SWITCH AND ALL ASSOCIATED CONDUIT ETC. IN IT'S ENTIRETY.
- 2 EXISTING FIRE ALARM SYSTEM SHALL BE DISCONNECTED AND REMOVED IN IT ENTIRETY AND REPLACED WITH NEW SYSTEM BASE ON I-3 OCCUPANCY PER THE LATEST IFC AND NFPA 72 REQUIREMENTS.
- 3 EXISTING SURFACE MOUNTED RACEWAY WITH LOW VOLTAGE CABLING TO BE DISCONNECTED AND REMOVED. E.C SHALL FIELD VERIFY IF CABLING SUPPORTS EQUIPMENT THAT IS TO REMAIN, IF SO CONTRACTOR SHALL RE-ESTABLISH CONTINUITY TO EQUIPMENT BY INSTALLING NEW RACEWAY/CABLING CONCEALED IN CEILING SPACE.
- 4 ALL EXISTING ELECTRICAL DEVICES, ETC IN THIS ARE SHALL REMAIN ACTIVE. LOCATE AND PROTECT DURING CONSTRUCTION, UNLESS NOTED OTHERWISE OR AS INDICATED IN "SPECIAL DEMOLITION NOTES".
- 5 EXISTING BUILDING TELEPHONE/DATA CABLING SYSTEM SHALL BE DISCONNECTED AND REMOVED IN IT ENTIRETY INCLUDING BUT NOT LIMITED TO: HEAD-END EQUIPMENT, RACKS, PATCH PANELS, HORIZONTAL CABLING, ETC. AND REPLACED WITH NEW SYSTEM AS INDICATED IN DRAWINGS AND SPECIFICATIONS.
- 6 EXISTING JAIL CONTROLS/AUTOMATION HEAD-END EQUIPMENT TO BE DISCONNECTED/REMOVED IN IT'S ENTIRETY AND REPLACED WITH A NEW SYSTEM AND EQUIPMENT. SEE SPECIAL SYSTEMS PLAN FOR ADDITIONAL INFORMATION.
- 7 EXISTING ELECTRICAL PANEL TO BE DISCONNECTED/REMOVED AND REPLACED WITH NEW AS INDICATED, REFER RISER DIAGRAM AND PANEL SCHEDULES. E.C. SHALL DISCONNECT ALL EXISTING BRANCH CIRCUITS THAT ARE TO REMAIN AND RECONNECT TO NEW PANEL. EXTEND EXISTING BRANCH CIRCUITS TO NEW PANEL AS REQUIRED.

1 EXISTING ELECTRICAL PLAN
SCALE: 1/8" = 1'-0"



DATE _____

DATE _____


PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
EXISTING POWER/SYSTEMS PLAN

Laughlin Ricks Architecture
—
architecture/planning
134 3RD AVE. E. # Twin Falls, Idaho 83301
PHONE: (208) 736-8050

DATE: 7.12.24

SAM Drawn	TEP Checked
#23029 PROJECT #	

E1A-03



PROJECT #: 2496
IPAYNE
Engineering Inc.
1823 E. Center
Pocatello, Idaho 83201
tel (208) 232-4439
www.payneengineeringinc.com


GENERAL NOTES:

A. REFER TO SYMBOL SCHEDULE SHEET FOR PROJECT GENERAL NOTES AND GENERAL NOTES ASSOCIATED WITH THE INSTALLATION OF EACH SYSTEM, INCLUDING BUT NOT LIMITED TO: LIGHTING, POWER, FIRE ALARM, SPECIAL SYSTEMS, ETC.

KEY NOTES:

- E.C. SHALL MODIFY EXISTING CIRCUIT(S)/CONTROLS AS REQUIRED FOR CONNECTION TO NEW LIGHT FIXTURE, WHEN APPLICABLE CONNECT "NIGHT-LITE" TO EMERGENCY CIRCUIT AND FIXTURE TO "NORMAL" CIRCUIT. MAINTAIN EXISTING CONTROL FUNCTIONALITY VIA LIGHTING RELAY PANEL AND CONTROL CENTER.
- CONNECT TO EXISTING "NORMAL" LIGHTING CIRCUIT IN AREA MADE AVAILABLE DURING DEMOLITION.
- CONNECT TO EXISTING "EMERGENCY" LIGHTING CIRCUIT IN AREA MADE AVAILABLE DURING DEMOLITION.
- CONNECT TO EXISTING EXTERIOR LIGHTING CIRCUIT/CONTROLS.
- CONNECT ALL OCCUPANCY SENSORS IN ROOM IN PARALLEL SO THAT ANY OCC. SENSOR WILL TURN ON ALL ROOM LIGHTING.
- E.C. SHALL CONNECT NEW LIGHT FIXTURE TO EXISTING CIRCUIT/CONTROLS, PROVIDE NEW CONTROLS WHERE INDICATED.

2 ROOF ACCESS - LIGHTING PLAN
SCALE: 1/8" = 1'-0"



1 LIGHTING PLAN
SCALE: 1/8" = 1'-0"


PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2615 Wright Ave., Twin Falls, ID 83301
LIGHTING PLAN

Laughlin Ricks Architecture
architecture/planning
134 3RD AVE. E., Twin Falls, Idaho 83301
PHONE: (208) 736-8050

DATE: 7.12.24
SAM Drawn
TEP Checked

#23029
PROJECT #

E1A-1.0



PROJECT #: 2496
IPAYNE
Engineering Inc.
1823 E. Center
Pocatello, Idaho 83201
tel (208) 232-4439
www.payneengineeringinc.com

MECH. - ELECTRIC HEATER SCHEDULE

EQUIP. ID	VOLTS / PH.	WATTS	FLA	OCF	CIRCUIT	FEEDER	NOTES
EH-1	208 V / 1 PH.	2000 W	9.6 A	15 A	D - 21,23	1/2"C, 2#12, #12N, #12G	
EH-2	208 V / 3 PH.	4800 W	13.3 A	20 A	C - 25,27,29	1/2"C, 3#12, #12G	

MECH. - PLUMBING EQUIP. SCHEDULE


EQUIP. ID	VOLTS / PH.	WATTS	FLA	CIRCUIT	FEEDER	DISCONNECT	NOTES
WH-1	120 V / 1 PH.	200 W	1.7 A	C - 8	1/2"C, 1#12, #12N, #12G	CORD/PLUG	

GENERAL NOTES:


A. REFER TO SYMBOL SCHEDULE SHEET FOR PROJECT GENERAL NOTES AND GENERAL NOTES ASSOCIATED WITH THE INSTALLATION OF EACH SYSTEM, INCLUDING BUT NOT LIMITED TO: LIGHTING, POWER, FIRE ALARM, SPECIAL SYSTEMS, ETC.

KEY NOTES:


- CONNECTION TO OVERHEAD DOOR MOTOR, COORDINATE CONNECTION WITH EQUIPMENT PRIOR TO ROUGH-IN. PROVIDE CONDUIT AND CONDUCTORS TO PUSH-BUTTON STATION PER MANUFACTURERS REQUIREMENTS.
- ALL 120V CIRCUITS (EXCEPT LIGHTING) IN THIS ROOM SHALL BE PROVIDED WITH A REDUNDANT GROUND AS REQUIRED BY SECTION 517 OF THE NEC.
- FLOORBOX FOR DENTAL CHAIR; COORDINATE EXACT STUB-UP LOCATION AND CONNECTION REQUIREMENTS WITH DENTAL EQUIPMENT INSTALLER PRIOR TO ROUGH-IN. E.C. SHALL SAWCUT AND PATCH EXISTING SLAB AS REQUIRED FOR INSTALLATION.
- PROVIDE AND INSTALL (1) 2" CONDUIT W/ PULLSTRING BETWEEN DENTAL CHAIR AND UTILITY CENTER. COORDINATE EXACT LOCATION OF STUB-UPS WITH EQUIPMENT SUPPLIER/CONTRACTOR PRIOR TO ROUGH-IN. E.C. SHALL SAWCUT AND PATCH EXISTING SLAB AS REQUIRED FOR INSTALLATION.
- PROVIDE AND INSTALL 120V RECEPTACLE AND LOW VOLTAGE OUTLET FLUSH IN CEILING FOR TV. INSTALL DATA CABLING AS INDICATED AND RG6 COAX CABLE. COORDINATE EXACT LOCATION & REQUIREMENTS WITH DENTAL EQUIPMENT INSTALLER PRIOR TO ROUGH-IN.
- CONNECTION TO DENTAL CEILING LIGHT PROVIDED/INSTALLED BY DENTAL EQUIPMENT CONTRACTOR, COORDINATE CONNECTION AND ROUGH-IN REQUIREMENTS WITH INSTALLER PRIOR TO ROUGH-IN.
- ALL EXISTING ELECTRICAL DEVICES, ETC IN THIS ARE SHALL REMAIN ACTIVE. LOCATE AND PROTECT DURING CONSTRUCTION, UNLESS NOTED OTHERWISE OR AS INDICATED IN "SPECIAL DEMOLITION NOTES".
- CONNECT TO EXISTING RECEPTACLE CIRCUIT IN AREA OR THAT WAS MADE AVAILABLE DURING DEMOLITION.
- PROVIDE POWER CONNECTION AND DATA ROUGH-IN TO VIDEO INTERCOM SYSTEM; FIELD VERIFY HEIGHT AND REQUIREMENTS WITH OWNER PRIOR TO ROUGH-IN.
- EXISTING EXHAUST FAN TO BE REPLACED WITH NEW BY M.C. E.C. PROVIDE NEW CIRCUIT AS INDICATED AND CONTROL WITH RESTROOM (RR 32) LIGHTING.
- MOTORIZED DAMPER BY M.C. TO BE INTERLOCKED WITH OPERATION OF ANY DRYER BY E.C. COORDINATE INTERLOCKING REQUIREMENTS OF DAMPER AND GAS DRIVERS WITH M.C.
- E.C. SHALL PROVIDE AND INSTALL (3) CURRENT SENSOR RELAYS (RIB FUNCTIONAL DEVICES OR EQUAL) ONE FOR EACH GAS DRYER AND INSTALL IN A NEMA 1 ENCLOSURE FOR INTERLOCKING WITH MOTORIZED DAMPER. ROUTE EACH DRYER CIRCUIT THROUGH CURRENT SENSOR. IF ANY DRYER IS IN OPERATION RELAY SHALL OPEN MOTORIZED DAMPER. PROVIDE ALL COMPONENTS FOR COMPLETE INSTALLATION.
- PROVIDE LOCAL DISCONNECT FOR EQUIPMENT, FIELD LOCATE IN ACCESSIBLE LOCATION.



2 ENLARGED DENTAL AREA POWER/DATA PLAN
SCALE: 1/4" = 1'-0"




1 POWER PLAN
SCALE: 1/8" = 1'-0"



PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave., Twin Falls, ID 83301
POWER PLAN

Laughlin Ricks Architecture
architecture/planning
134 3RD AVE. E., Twin Falls, Idaho 83301
PHONE: (208) 756-8050



PROJECT #: 2496
IPAYNE
Engineering Inc.
1823 E. Center
Pocatello, Idaho 83201
tel (208) 232-4439
www.paynengineerinc.com

DATE: 7.12.24
SAM Drawn
TEP Checked
#23029 PROJECT #
E1A-2.0

MECH. - SPLIT SYSTEM A/C UNIT SCHEDULE

EQUIP. ID	VOLTS / PH.	MCA	MOCF	CIRCUIT	FEEDER	DISCONNECT	NOTES
INDOOR UNIT							
FC-1	208 V / 1 PH.	1 A	0 A		PER MFGR	0 A - N/A	4
OUTDOOR UNIT							
CU-1	208 V / 1 PH.	14 A	25 A	EA2 - 27.29	1/2"C, 2#10+1#10G	30 A - NONFUSED/3R	3, 4

MECH. - EXHAUST FAN SCHEDULE

EQUIP. ID	VOLTS / PH.	HP	WATTS	FLA	CIRCUIT	FEEDER	CONTROL	NOTES
EF-1(E)	120 V / 1 PH.	1/4		6 A	B - 14	1/2"C, 1#12, #12N, #12G	24/7 CONTINUOUS	2
EF-3(E)	120 V / 1 PH.	1/2		10 A	B - 16	1/2"C, 1#12, #12N, #12G	24/7 CONTINUOUS	2
EF-4(E)	120 V / 1 PH.	N/A	100 W	1 A	B - 2	1/2"C, 1#12, #12N, #12G	W/LIGHTS	1
EF-9(E)	120 V / 1 PH.	1/2		10 A			24/7 CONTINUOUS	2
EF-10(E)	120 V / 1 PH.	1/3		7 A			24/7 CONTINUOUS	2
EF-12	120 V / 1 PH.	3/4		14 A	D - 19	1/2"C, 1#12, #12N, #12G	CO SENSOR BY M.C.	2
EF-13	120 V / 1 PH.	1/4		6 A	D - 17	1/2"C, 1#12, #12N, #12G	24/7 CONTINUOUS	2

MECH. - ROOFTOP UNIT SCHEDULE

EQUIP. ID	VOLTS / PH.	MCA	MOCF	CIRCUIT	FEEDER	DISCONNECT	NOTES
RTU-1(E)	208 V / 3 PH.	20 A	30 A	EA - 11, 13, 15	1/2"C, 3#10, #10G	30 A - W/UNIT	5
RTU-2(E)	208 V / 3 PH.	26 A	30 A	MP - 1	1/2"C, 3#10, #10G	30 A - W/UNIT	5
RTU-3(E)	208 V / 1 PH.	26 A	30 A	MP - 2	1/2"C, 2#10, #10G	30 A - W/UNIT	5
RTU-4(E)	208 V / 3 PH.	20 A	30 A	MP - 3	1/2"C, 3#10, #10G	30 A - W/UNIT	5
RTU-5(E)	208 V / 3 PH.	20 A	30 A	MP - 4	1/2"C, 3#10, #10G	30 A - W/UNIT	5
RTU-6(E)	208 V / 3 PH.	40 A	50 A	D - 25, 27, 29	3/4"C, 3#6, #10G	60 A - W/UNIT	5
RTU-7(E)	208 V / 3 PH.	26 A	30 A	MP - 5	1/2"C, 3#10, #10G	30 A - W/UNIT	5
RTU-8(E)	208 V / 3 PH.	26 A	30 A	MP - 6	1/2"C, 3#10, #10G	30 A - W/UNIT	5
RTU-9	208 V / 3 PH.	45 A	60 A	D - 26, 28, 30	3/4"C, 3#6, #10G	60 A - W/UNIT	5

MECHANICAL SCHEDULE NOTES:

- CIRCUIT AND CONTROL EXHAUST FAN WITH ROOM LIGHTING CIRCUIT.
- E.C. SHALL PROVIDE LOCAL DISCONNECT RATED, THERMAL-OVERLOAD SWITCH FOR EQUIPMENT; SWITCH RATING SHALL NOT BE LESS THEN CIRCUIT BREAKER SUPPLYING EQUIPMENT.
- E.C. SHALL PROVIDE LOCAL DISCONNECT SWITCH FOR EQUIPMENT; SIZE AND TYPE AS INDICATED IN SCHEDULE. IF FUSED DISCONNECT IS SPECIFIED FOR EQUIPMENT, FUSE PER EQUIPMENT NAMEPLATE RATING.
- INDOOR UNIT IS POWERED FROM OUTDOOR UNIT; COORDINATE EXACT NUMBER OF CONDUCTORS BETWEEN UNITS WITH M.C. PRIOR TO ROUGH-IN.
- EQUIPMENT IS FACTORY SUPPLIED WITH DISCONNECT AND CONVENIENCE OUTLET; E.C. SHALL PROVIDE ALL NECESSARY CONNECTIONS.

GENERAL NOTES:


- A. REFER TO SYMBOL SCHEDULE SHEET FOR PROJECT GENERAL NOTES AND GENERAL NOTES ASSOCIATED WITH THE INSTALLATION OF EACH SYSTEM, INCLUDING BUT NOT LIMITED TO: LIGHTING, POWER, FIRE ALARM, SPECIAL SYSTEMS, ETC.

KEY NOTES:

- EXISTING ROOFTOP HVAC EQUIPMENT TO REMAIN ACTIVE, LOCATE AND PROTECT.
- EXISTING ROOFTOP HVAC EQUIPMENT TO BE REMOVED AND REPLACED WITH NEW BY M.C. E.C. SHALL ELECTRICALLY DISCONNECT FOR REMOVAL AND RECONNECT NEW UNIT TO EXISTING CIRCUIT. E.C. SHALL FIELD VERIFY EXISTING BREAKER OR FUSE SIZE AND REPLACE AS NEEDED TO MATCH "MOCF" IN SCHEDULE.
- EXISTING ROOFTOP HVAC EQUIPMENT TO BE DEMOLISHED BY M.C. E.C. SHALL DISCONNECT AND REMOVE ALL ASSOCIATED CONDUIT/CONDUCTORS AS REQUIRED FOR REMOVAL.
- EXISTING ROOFTOP HVAC EQUIPMENT TO BE REMOVED AND REPLACED WITH NEW LARGER UNIT BY M.C. E.C. SHALL ELECTRICALLY DISCONNECT FOR REMOVAL AND REMOVED ASSOCIATED CIRCUIT. E.C. SHALL PROVIDE AND INSTALL NEW CIRCUIT AS INDICATED IN SCHEDULE.
- RECEPTACLE MOUNTED TO HVAC UNIT, COORDINATE MOUNTING WITH M.C. PRIOR TO ROUGH-IN.




1 ELECTRICAL ROOF PLAN
SCALE: 1/8" = 1'-0"



PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
ELECTRICAL ROOF PLAN


Laughlin Ricks Architecture
architecture/planning
134 3RD AVE. E. # Twin Falls, Idaho 83301
PHONE: (208) 736-8050



PROJECT #: 2496
IPAYNE
Engineering Inc.
1823 E. Center
Pocatello, Idaho 83201
tel (208) 232-4439
www.payneengineeringinc.com

DATE: 7.12.24
SAM Drawn
TEP Checked
#23029
PROJECT #

E1A-2.1



JAIL CONTROL & SECURITY SYSTEMS:

- THE BUILDING EXISTING JAIL CONTROL/SECURITY SYSTEM SHALL BE COMPLETELY REMOVED IN PREPARATION FOR A NEW SYSTEM THAT IS TO BE INCLUDED IN PHASE 1B OF THE PROJECT.
- THE NEW JAIL CONTROL/SECURITY SYSTEM DESIGN FOR THIS IS BUILDING WILL BE COMPLETED AS PART OF PHASE 1B CONSTRUCTION DOCUMENTS.
- THE NEW SYSTEM INCLUDES BUT IS NOT LIMITED TO: TOUCH SCREEN CONTROLS, PLC'S, INTERCOM, DOOR CONTROL, LIGHTING CONTROL, SECURITY CAMERAS, ETC. THE SYSTEM WILL HAVE THE ABILITY FOR FUTURE EXPANSION FOR THE TOTAL BUILD-OUT OF THE PROJECT.
- E.C. SHALL SCHEDULE A COORDINATION MEETING A MINIMUM OF 1-WEEK PRIOR TO BEGINNING OF ELECTRICAL ROUGH-IN TO COORDINATE ALL ROUGH-IN REQUIREMENTS FOR THE NEW JAIL CONTROL/SECURITY SYSTEM ASSOCIATED WITH THIS PHASE OF THE PROJECT. ATTENDEES SHOULD INCLUDE:
OWNER'S REP.
OWNER'S SECURITY CONTRACTOR
ELEC. ENGINEER
GENERAL AND ELECTRICAL CONTRACTORS

JAIL CONTROL & SECURITY SYMBOL SCHEDULE

NOTE: ALL SYMBOLS MAY NOT BE USED

SYMBOL	DESCRIPTION
CR	CARD READER LOCATION; ELEC. CONTRACTOR SHALL PROVIDE AND INSTALL 4SQ. BOX W/1-GANG MUNDRING AND 3/4" C. W/ PULL STRING TO IT ROOM ON 2ND FLOOR.
⊙	CONNECTION TO DOOR FRAME FOR ACCESS CONTROL; ELEC. CONTRACTOR SHALL PROVIDE AND INSTALL (1) 3/4" C. W/ PULL STRING FROM DOOR FRAME TO IT ROOM ON 2ND FLOOR.
■	SECURITY CAMERA LOCATION; ELEC. CONTRACTOR SHALL PROVIDE AND INSTALL 4SQ. BOX W/1-GANG MUNDRING AND 3/4" C. W/ CAT6 CABLING TO IT ROOM ON 2ND FLOOR.
SP WALL SP CEILING	INTERCOM SPEAKER.
⋈	TOUCH ACTIVATED INTERCOM SWITCH.
IC	AUDIO ONLY INTERCOM DOOR STATION WITH CALL SWITCH & 2-WAY SPEAKER

GENERAL NOTES:

- E.C. SHALL BE RESPONSIBLE FOR AND INCLUDE IN BASE BID ALL CONDUIT, BACKBOXES ETC FOR SYSTEM ROUGH-IN. FIELD VERIFY SPECIFIC REQUIREMENTS AND LOCATIONS WITH OWNER'S SECURITY CONTRACTOR PRIOR TO WORK BEING DONE.


GENERAL NOTES:

A. REFER TO SYMBOL SCHEDULE SHEET FOR PROJECT GENERAL NOTES AND GENERAL NOTES ASSOCIATED WITH THE INSTALLATION OF EACH SYSTEM. INCLUDING BUT NOT LIMITED TO: LIGHTING, POWER, FIRE ALARM, SPECIAL SYSTEMS, ETC.

KEY NOTES:

- 1 IN (1) 2" C., PROVIDE AND INSTALL 12-STRAND, SINGLE-MODE FIBER OPTIC BACKBONE CABLE IN INNER-DUCT FROM ELECT. ROOM TO NEW IT ROOM. PROVIDE ALL REQUIRED TERMINATIONS, LIU'S, PATCH PANELS AND ETC NEEDED TO EXTEND DATA CABLING SYSTEM.
- 2 PROVIDE POWER CONNECTION AND DATA ROUGH-IN TO VIDEO INTERCOM SYSTEM; FIELD VERIFY HEIGHT AND REQUIREMENTS WITH OWNER PRIOR TO ROUGH-IN.

1 SPECIAL SYSTEMS PLAN
SCALE: 1/8" = 1'-0"




DATE _____


PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2815 Wright Ave, Twin Falls, ID 83301
SPECIAL SYSTEMS PLAN

Laughlin Ricks Architecture
—
architecture/planning
134 3RD AVE. E. # Twin Falls, Idaho 83301
PHONE: (208) 756-8050

DATE: 7.12.24
SAM Drawn TEP Checked
#23029
PROJECT #
E1A-3.0




PROJECT #: 2496
IPAYNE
Engineering Inc.
1823 E. Center
Pocatello, Idaho 83201
tel (209) 232-4439
www.payneengineeringinc.com



- FIRE ALARM SYSTEM NOTES:**
- CONTRACTOR SHALL PROVIDE MONITORING OF FIRE ALARM SYSTEM, INITIATE WITH OWNER IN REGARDS TO SYSTEM MONITORING.
 - FIRE ALARM SYSTEM CONDUIT ROUTING SHALL BE DETERMINED BY THE ELECTRICAL CONTRACTOR AND FIRE ALARM CONTRACTOR TO MEET THE SPECIFIED DESIGN CRITERIA.
 - NOTIFICATION EXTENDER PANEL'S (NAC) SHALL BE PROVIDED AS NEEDED FOR THE CIRCUITING OF THE NOTIFICATION DEVICES AS INDICATED ON DRAWINGS.
 - ALL THE FIRE ALARM SYSTEM CABLING SHALL BE RUN IN CONDUIT.
 - CONTRACTOR SHALL SUBMIT SHOP DRAWINGS AND REQUIRED CALCULATIONS TO THE AUTHORITY HAVING JURISDICTION AND OBTAIN A WRITTEN LETTER OF ACCEPTANCE OF THE PROPOSED SYSTEM. INCLUDE LETTER WITH SHOP DRAWING SUBMITTAL TO ENGINEER.
 - E.C. SHALL PROVIDE AND INSTALL CELLULAR ALARM COMMUNICATOR FOR FIRE ALARM SYSTEM MONITORING, TELGUARD TG-7FS LTE OR EQUAL. SYSTEM SHALL BE UL LISTED AND COMPLIANT WITH NFPA 72 REQUIREMENTS.
 - E.C. SHALL PROVIDE AND INSTALL CELLULAR ALARM COMMUNICATOR FOR FIRE ALARM SYSTEM MONITORING, TELGUARD TG-7FS LTE OR EQUAL. SYSTEM SHALL BE UL LISTED AND COMPLIANT WITH NFPA 72 REQUIREMENTS.
- PROVIDE (1) YEAR RENEWABLE CELLULAR SERVICE COORDINATE SERVICE PROVIDER WITH OWNER.

A FIRE ALARM RISER DIAGRAM
SCALE: NONE

1 FIRE ALARM PLAN
SCALE: 1/8" = 1'-0"



GENERAL NOTES:

A REFER TO SYMBOL SCHEDULE SHEET FOR PROJECT GENERAL NOTES AND GENERAL NOTES ASSOCIATED WITH THE INSTALLATION OF EACH SYSTEM, INCLUDING BUT NOT LIMITED TO: LIGHTING, POWER, FIRE ALARM, SPECIAL SYSTEMS, ETC.

KEY NOTES:

- PROVIDE MONITORING OF FLOW, TAMPER AND PRESSURE SWITCHES; VERIFY EXACT NUMBER OF SWITCHES WITH EXISTING SYSTEM.
- DUCT-SMOKE DETECTOR PROVIDED AND CONNECT BY ELECTRICAL CONTRACTOR, INSTALLED BY MECHANICAL CONTRACTOR. DETECTOR SHALL BE CONNECTED TO FIRE ALARM SYSTEM AND SHALL SHUT-DOWN ASSOCIATED HVAC UNIT UPON ACTIVATION. ELECT. CONTRACTOR SHALL ALSO PROVIDE AND INSTALL REMOTE TEST SWITCH, INSTALL FLUSH IN CEILING NEAR LOCATION OF DUCT-SMOKE DETECTOR.
- FIRE ALARM CONTRACTOR SHALL PROVIDE AND INSTALL AN AUTOMATIC SMOKE DETECTION SYSTEM AS REQUIRED BY SECTION 907.2.6.3.3 OF THE IFC FOR A GROUP I-3 OCCUPANCY. THE AUTOMATIC SMOKE DETECTION SYSTEM SHALL UTILIZE AN INTELLIGENT VESDA AIR SAMPLING SYSTEM. SEE SPECIFICATIONS. CONTRACTOR IS RESPONSIBLE FOR A COMPLETE AN OPERABLE SYSTEM, INCLUDING ALL REQUIRED CORE-DRILLING AND ETC NEEDED TO INSTALL SYSTEM IN EXISTING BUILDING. ALL PIPING SHALL BE INSTALLED ABOVE CEILINGS, EXPOSED PIPING IS PROHIBITED. VESDA SYSTEM HEAD-END EQUIPMENT SHALL BE INSTALLED IT[11] AND MONITORED/CONTROLLED BY NEW FIRE ALARM SYSTEM.

DATE _____

DATE _____


PHASE 1 PART A FOR:
TWIN FALLS COUNTY - WRIGHT AVE JAIL
2615 Wright Ave, Twin Falls, ID 83301
FIRE ALARM SYSTEM PLAN

Laughlin Ricks Architecture
architecture/planning
134 3RD AVE. E. # Twin Falls, Idaho 83301
PHONE: (208) 756-8050

DATE: 7.12.24

SAM	TEP
Drawn	Checked
#23029	
PROJECT #	

E1A-4.0



PROJECT #: 2496
IPAYNE
Engineering Inc.
1823 E. Center
Pocatello, Idaho 83201
tel (209) 232-4439
www.payneengineeringinc.com

LIGHTING FIXTURE SCHEDULE

TYPE	DESCRIPTION	MOUNTING	VOLTS	WATTS	LUMENS	COLOR TEMP.(K)	MFR.	CATALOG #	APPROVED MFR'S	NOTES
F1	1X4 SURFACE HIGH SECURITY CORRECTIONAL LED	SURFACE	120/277	45 W	4450	4000	FAIL-SAFE	FUSL-X12-4-LD4-1HI-40-UNV-80/86-EDC1		
F1E	1X4 SURFACE HIGH SECURITY CORRECTIONAL LED, W/NIGHT-LITE	SURFACE	120/277	45 W	4450	4000	FAIL-SAFE	FUSL-X12-4-LD4-1HI-40-UNV-80/86-EDC2-LLNL		
F1EW	1X4 SURFACE HIGH SECURITY CORRECTIONAL LED, W/NIGHT-LITE, WET LOCATION RATED	SURFACE	120/277	45 W	4450	4000	FAIL-SAFE	FUSL-X12-4-LD4-1HI-40-UNV-80/86-EDC2-LLNL/WL		
F2	2X2 LED CORRECTIONAL SECURITY RECESSED TROFFER	RECESSED	120/277	35 W	4000	4000	FAIL-SAFE	FSR-TG-X24-2-LD4-2STD-40-UNV-80/84-EDD1		
F3	2X4 LED FLAT PANEL, FIELD SELECTABLE LUMENS/CCT	RECESSED	120-277	40 W	5000	4000	LITHONIA	CPX-2X4-AL08-80CRI-SWW7-SWL-MVOLT	COOPER	
F3S	2X4 LED FLAT PANEL, FIELD SELECTABLE LUMENS/CCT, INTEGRAL OCC. SENSOR	RECESSED	120-277	40 W	5000	4000	LITHONIA	CPX-2X4-AL08-80CRI-SWW7-SWL-MVOLT-APDT	COOPER	
F4	2FT LED STRIP, FIELD SELECTABLE LUMENS/CCT	SURFACE	120/277	15 W	2000	4000	COOPER LTG	2SNX-SL3-SLW-UNV-CC83-CD1-U	ACUIITY	
F5	4FT LED STRIP, FIELD SELECTABLE LUMENS/CCT	SURFACE	120-277	30 W	4000	4000	COOPER LTG	4SNX-SL3-SLW-UNV-CC83-CD1-U	ACUIITY	
F6	8FT LED STRIP, FIELD SELECTABLE LUMENS	SUSPENDED	120/277	60 W	8000	4000	COOPER LTG	8SNX-SL3-SLW-UNV-CC83-CD1-U	ACUIITY	
F7	4FT LED WRAPAROUND, FIELD SELECTABLE LUMENS/CCT	SURFACE	120/277	40 W	MED	4000	COOPER LTG	4NWS3C3-UNV	ACUIITY	
F8	HIGHBAY LED, FIELD SELECTABLE LUMENS/CCT	PENDANT	120/277	110 W	15000	4000	COOPER LTG	UHBS-1218-MV-L84050-U	ACUIITY	
FE1	EXTERIOR LED WALL PACK	WALL	MULTI-TAP	50 W	7300	4000	COOPER LTG	ASWPLED2S		
FE2	SQUARE SURFACE LOW PROFILE LED CANOPY LIGHT	SURFACE	120/277	50 W	5000	4000	COOPER LTG	CLCSLED-40-SM-UNV		
FE3	AREA POLE LIGHT HEAD ONLY, TYPE R3 DIST.	EXISTING POLE	MULTI-TAP	0 W	7000	4000	LITHONIA	HEAD ONLY: RSX1 LED-P1-40K-R3-MVOLT-SPA-DBXD	COOPER	
FX1	EXIT SIGN, THERMOPLASTIC, GREEN LED, SINGLE/DOUBLE FACE	WALL OR CEILING	120-277	2 W	N/A	N/A	LITHONIA	LQM-S-W-3-G-120/277	COOPER	

LIGHT FIXTURE SCHEDULE NOTES:

- REFER TO DRAWINGS FOR FIXTURES REQUIRED TO HAVE 0-10V OR STEP-LEVEL DIMMING CONTROL. PROVIDE FIXTURE(S) WITH LED DRIVER(S) AND REQUIRED DIMMING/SWITCH-LEG CONDUCTORS BETWEEN SWITCH(ES) AND FIXTURE(S) TO PROVIDE CONTROL AS INDICATED ON DRAWINGS.
- FIXTURE TO BE CONTINUOUS ROW MOUNTED. LENGTH AS INDICATED ON DRAWINGS. PROVIDE REQUIRED ACCESSORIES/CONNECTORS FOR CONTINUOUS ROW MOUNTING.
- SCBA - STANDARD COLOR BY ARCHITECT/OWNER. COORDINATE COLOR WITH ARCHITECT/OWNER PRIOR TO ORDERING.)
- FIELD ADJUST PENDANT LENGTH AS REQUIRED. VERIFY LENGTH WITH COUNTER AS DIRECTED BY ARCHITECT.
- PROVIDE ALL COMPONENTS FOR COMPLETE INSTALLATION, INCLUDING BUT NOT LIMITED TO: END FEEDS, CONNECTORS AND ETC.

GENERAL LIGHTING SCHEDULE NOTES:

- LIGHTING FIXTURES INDICATED IN SCHEDULE ARE BASIS OF DESIGN. ALTERNATE MANUFACTURERS SHALL BE PRE-APPROVED BY ADDENDUM. ALTERNATE MANUFACTURERS SHALL SUBMIT PER-APPROVALS TO ENGINEER A MINIMUM OF 10 DAYS PRIOR TO PROJECT BID DATE.

LIGHTING CONTROL/OCCUPANCY SENSOR SCHEDULE


TYPE	DESCRIPTION	MFR.	CATALOG #	APPROVED EQUALS	NOTES
DIMMER SWITCHES - LINE VOLTAGE					
D1	LINE VOLTAGE 0-10V DIMMER, ON/OFF/DIMMING PUSH-BUTTONS	SENSOR SWITCH	sPODMRA-D-**		2,3,4
OCC. SENSORS - CEILING (LINE VOLTAGE)					
CD2	DUAL-TECHNOLOGY, LINE VOLTAGE, SMALL MOTION 800W MAX LOAD	SENSOR SWITCH	CMR-PDT 9	COOPER, WATTSOPPER, HUBBELL	
CD4	DUAL-TECHNOLOGY, LINE VOLTAGE, 2-POLE SMALL MOTION, 800W MAX LOAD	SENSOR SWITCH	CMR-PDT-9-2P	COOPER, WATTSOPPER, HUBBELL	
OCC. SENSORS - CEILING (LOW VOLTAGE)					
CD1	DUAL-TECHNOLOGY, SMALL MOTION 360 DEGREE COVERAGE, LOW VOLTAGE, W/ISOLATED RELAY	SENSOR SWITCH	CM-PDT 9 R	COOPER, WATTSTOPPER, HUBBELL	1
OCC. SENSORS - WALL MOUNTED					
WDD	DUAL-TECHNOLOGY, 0-10V DIMMING	SENSOR SWITCH	WSX-PDT-D	COOPER, WATTSTOPPER, HUBBELL	2,5
WP1	PASSIVE-INFRARED, 1-POLE, NEUTRAL REQUIRED	SENSOR SWITCH	WSX-**	COOPER, WATTSTOPPER, HUBBELL	2

CONTROL & OCCUPANCY SENSOR SCHEDULE NOTES:

- PROVIDE ADDITIONAL POWER PACKS, SENSOR SWITCH PP20 AS NEED FOR QTY OF OCCUPANCY SENSORS/SWITCHES.
- DEVICE COLOR SHALL MATCH WIRING DEVICES; REFER TO SPECIFICATIONS.
- REFER TO MANUFACTURER DOCUMENTATION FOR QTY AND SIZE OF CONDUCTORS BETWEEN LOW VOLTAGE SWITCH, SENSOR(S) AND POWER/RELAY PACKS.
- PROVIDE SECONDARY RELAY PACK; SENSOR SWITCH SP20 AS NEEDED TO PROVIDE DUAL-LEVEL SWITCHING OF FIXTURES.
- PROVIDE 0-10V DIMMING CONDUCTORS (GRAY & VIOLET) BETWEEN SWITCH AND LIGHT FIXTURES FOR DIMMING CONTROL.
- PROGRAM ON/OFF TIMES OF RELAY'S AS DIRECTED BY OWNER. PROVIDE COMMISSIONING AS INDICATED IN GENERAL NOTES BELOW.
- CUSTOM WALL STATION ENGRAVINGS IS REQUIRED FOR WALL STATION(S) AND SHALL BE SPECIFIED/COORDINATED WITH OWNER AFTER PROGRAMING OF SYSTEM.


GENERAL LIGHTING CONTROL NOTES:

- E.C. SHALL BE RESPONSIBLE FOR THE PROGRAMMING/COMMISSIONING OF THE LIGHTING CONTROL SYSTEMS TO FUNCTION AS INDICATED ON THE DRAWINGS AND SHALL INCLUDE ALL REQUIRED COST IN THE BASE BID. FOR AREAS WITH DAYLIGHTING CONTROL, THE DAYLIGHTING SET-POINTS SHALL BE COORDINATED WITH THE OWNER FOR EACH AREA PRIOR TO FINAL PROGRAMMING OF THE DAYLIGHTING SENSOR(S). ALL PROGRAMMING/COMMISSIONING SHALL BE DONE BY A FACTORY CERTIFIED OR TRAINED PERSON.
- LIGHTING IS SPACES WITH WIRELESS CONTROLS SHALL BE FIELD TUNED TO FOOTCANDLE LEVELS THAT ARE SATISFACTORY TO THE OWNER DURING PROGRAMMING AND COMMISSIONING OF THE WIRELESS CONTROL SYSTEM.




1 LIGHT FIXTURE RECESSED DETAIL

SCALE: NONE



3 RECEPTACLE MOUNTING DETAIL

SCALE: NONE



2 LV OCC. SENSOR W/ TYPE 'D1' SWITCH DIAGRAM

SCALE: NONE

GENERAL DETAIL NOTES:

- THIS WIRING DIAGRAM IS BASED ON SENSOR SWITCH CONTROLS DEVICES AS THE BASIS OF DESIGN SHOWN ON DRAWINGS. IF AN ALTERNATE MANUFACTURER IS USED THE ELEC. CONTRACTOR IS RESPONSIBLE TO PROVIDING ALL WIRING AND COMPONENTS REQUIRED TO PROVIDE THE SWITCHING SCHEME THAT IS REPRESENTED.
- EQUIPMENT GROUNDING CONDUCTOR IS NOT SHOWN FOR SIMPLICITY. AN EQUIPMENT GROUND SHALL BE RAN TO ALL SWITCHES, LIGHT FIXTURES, ETC.

PHASE 1 PART A FOR:

TWIN FALLS COUNTY - WRIGHT AVE JAIL

2815 Wright Ave, Twin Falls, ID 83301

ELECTRICAL SCHEDULES & DETAILS

Laughlin Ricks Architecture

architecture/planning


134 3RD AVE. E. # Twin Falls, Idaho 83301

PHONE: (208) 756-8050

DATE: 7.12.24

SAM Drawn
TEP Checked
#23029
PROJECT #

E1A-5.1



PROJECT #: 2496
IPAYNE
Engineering Inc.
1823 E. Center
Pocatello, Idaho 83201
tel (208) 232-4439
www.payneengineeringinc.com